

## 1. Details of Soft Landscaping

### 1.a Planting plans (at not less than a scale of 1:100),

Please see landscape plan.

### 1.b Written specification of planting and cultivation works to be undertaken,

### 1.c Schedule of plants giving species, plant sizes, and proposed numbers/densities where appropriate

<u>Planting Schedule</u>	<u>English name</u>	<u>Latin name</u>
P01	Privet Hedge	Ligustrum vulgare
P02	Existing hedge and shrubs	
P03	Privet hedge	Ligustrum vulgare
P04	Laurel hedge	Laurus nobilis
P05	Privet hedge	Ligustrum vulgare
P06	Existing conifer hedge	Cuprocyparis leylandii
P07	Existing hawthorn hedge	Crataegus
P08	Existing conifers mixed with red robin	Cuprocyparis leylandii/ Photinia fraseri
P09	Existing golden privet shrubs	Ligustrum ovalifolium Aureum
P10	Existing conifers	Cuprocyparis leylandii
P11	Junipers	Juniperus communis
P12	French Marigold	Tagetes patula
P13	Mixed heather	Calluna vulgaris
P14	Mixed heather	Calluna vulgaris
P15	French Marigold	Tagetes patula
P16	Red robin	Photinia fraseri
P17	Red robin	Photinia fraseri

## 2. Details of Hard Landscaping

### 2.a Refuse Storage

Refuse and recycling bins are placed in the side/rear gardens, detailed on the landscape plan.

### 2.b Cycle Storage

2 cycle storage racks for unit 88 will be provided within the garage.

2 cycle storage racks for unit 90 will be provided in a bicycle shed, at the flank of the dwelling, the exact position is denoted in the landscape plan. The following link provides an example of the type of shed that is proposed.

[https://www.manomano.co.uk/p/empire-5000-with-windows-available-in-different-sizes-6951722?model\\_id=6951724](https://www.manomano.co.uk/p/empire-5000-with-windows-available-in-different-sizes-6951722?model_id=6951724)

## 2.c Means of enclosure/boundary treatments

The boundary fence for each unit is specified on the landscape plan. This is 1800mm high closeboard fence along the rear of both plots and the flank of no.90. A 1200mm closeboard fence will split the rear gardens of no. 88 and 90. A laurel hedge will be planted separating the front gardens of no 88 and 90.

## 2.d Car Parking Layouts

2 car parking spaces are proposed for each unit, with each unit having separate crossover. The crossover for unit 90 has been applied for and accepted by Hillingdon Local Authority. It will be constructed on completion of the driveway.

## 2.e Hard Surfacing Materials

The rear garden patios will be finished with a sandstone tile, as below, or similar.

<https://www.simplypaving.com/products/paving/natural-stone-paving/bradstone-blended-natural-sandstone/rustic-grey/>

The front garden driveways will be finished with a permeable surface, as specified by the SUDS report. This will be of resin or gravel finishing layer.

[https://www.specialistaggregates.com/gravel-resin-bound-flooring-sandal-p-6670.html?gclid=CjwKCAjwmKLzBRBeEiwACCVihjn9RBCXz6xrejnAmS\\_eAv5QZQqelWIwW9Mld4JLLjC-lqpAozZXBjxoCGj0QAvD\\_BwE](https://www.specialistaggregates.com/gravel-resin-bound-flooring-sandal-p-6670.html?gclid=CjwKCAjwmKLzBRBeEiwACCVihjn9RBCXz6xrejnAmS_eAv5QZQqelWIwW9Mld4JLLjC-lqpAozZXBjxoCGj0QAvD_BwE)

## 2.f External Lighting

Each side of the front entrance and rear patio door to 88 and 90 will have a wall light placed at 2m above ground level. The following link provides an example of the type of product that is proposed.

[https://www.lighting-direct.co.uk/riga-twin-led-outdoor-wall-light-anthracite.html?utm\\_source=google&utm\\_medium=cpc&utm\\_campaign=shopping&customer\\_tax\\_visibility=2&gclid=CjwKCAjwmKLzBRBeEiwACCVihruYWihZonnzZ08W6u0OGYgo32KD8gyTactrgqPI7qnUBOwVpSHswhoCM8oQAvD\\_BwE](https://www.lighting-direct.co.uk/riga-twin-led-outdoor-wall-light-anthracite.html?utm_source=google&utm_medium=cpc&utm_campaign=shopping&customer_tax_visibility=2&gclid=CjwKCAjwmKLzBRBeEiwACCVihruYWihZonnzZ08W6u0OGYgo32KD8gyTactrgqPI7qnUBOwVpSHswhoCM8oQAvD_BwE)

Adequate security lighting will be placed on automatic sensor in both front and rear gardens. The following link provides an example of the type of product that is proposed.

<https://www.lighting-direct.co.uk/lyco-50w-cool-white-led-floodlight-with-pir-sensor.html>

The driveways are proposed to be lined with LED stake lights, spaced at 2m intervals, on both sides of each drive. The following link provides an example of the type of product that is proposed.

<https://www.lighting-direct.co.uk/eglo-solar-led-stake-lights-stainless-steel-set-of-3.html>