



## SITE INVESTIGATION FACTUAL REPORT

Report No: SI-977919  
Client: Crawford Claims Management  
Site: 6 Nicholas Way  
Hillingdon  
Client Ref: 1785373  
Date of Visit: 11/3/2025



**Home Emergency Response - Subsidence Investigation - Drainage Services – Crack & Level Monitoring – Property Video Surveys**

East Building, Cable Drive, Walsall, WS2 7BN

☎ 0333 016 4477

CET is the trading name of CET Structures Ltd

✉ [siinstructions@cet-uk.com](mailto:siinstructions@cet-uk.com)

Registered in England No. 02527130

🌐 [www.cet-uk.com](http://www.cet-uk.com)

# Investigation Layout Plan

Sheet: 1 of 1

Job No: 977919

Date: 11.03.2025

Site: 6 Nicholas Way


Work carried out for: Crawford Claims Management

DB  
(SI)

AM  
(Checked)

AM  
(Drawn)

Weather: Dry



Remarks:

Key:

- Combined Gully RWWG
- Manhole MH
- Rain Water Pipe RWP
- Rain Water Gully RWG
- Soil Vent Pipe SVP
- Waste Gully WG
- Waste Pipe WP

Surface Water Drain

Foul Water Drain

Tree / Bush  
(approx. ht in m)


Trial Pit

Borehole

O/D - Open Discharge

Scale: N.T.S.

REPORT NUMBER: C5008116 / 337861.1.1.2  
 TRIAL PIT REF: TP1 (B) DATE: 12/03/2025  
 CLIENT: Crawford & Co SITE: 6 NICHOLAS WAY  
 JOB NO: 977919 WEATHER: Dry  
 EXCAVATION METHOD: Hand tools



For Strata below 1700mm see Trial Pit log

Key:

D Small disturbed sample J Jar sample  
 B Bulk disturbed sample V Pilcon vane (kPa)  
 W Water sample M Mackintosh probe  
 TDTD Too dense to drive

Remarks:

Test results reported relate only to the items tested.  
 This report shall not be reproduced except in full without approval of the Laboratory.  
 The laboratory does not apply a conformity statement to test reports as standard, unless specifically requested by the customer.


For and on behalf of CTS  
 Adam Mason - Quality Control



Approved Signatory  
 Report date 12-Mar-25

REPORT NUMBER: C5008116 / 337861.1.1.1  
 TRIAL PIT REF: TP1 (A)  
 CLIENT: Crawford & Co  
 JOB NO: 977919  
 EXCAVATION METHOD: Hand tools

DATE: 12/03/2025  
 SITE: 6 NICHOLAS WAY  
 WEATHER: Dry



For Strata below 1700mm see Bore Hole log

Key:

- D Small disturbed sample J Jar sample
- B Bulk disturbed sample V Pilcon vane (kPa)
- W Water sample M Mackintosh probe
- TDTD Too dense to drive

Remarks:  
 Test results reported relate only to the items tested.  
 This report shall not be reproduced except in full without approval of the Laboratory.  
 The laboratory does not apply a conformity statement to test reports as standard, unless specifically requested by the customer.


For and on behalf of CTS  
 Adam Mason - Quality Control



Approved Signatory  
 Report date 12-Mar-25

<b>Borehole</b>		<b>1</b>		Sheet:	1 of 1	Site:	6 NICHOLAS WAY			
				Job No:	977919					
				Date:	11/03/2025					
Boring Method:	Hand Auger			Ground Level:		Client:	Crawford Claims Management			
Diameter (mm):	75	Weather:	Dry							
Depth	Soil Description					Thickness	Legend	Samples and Tests		
(m)								Depth	Type	Result
0.00	See Trial Pit					1.70				
1.70	Stiff orange-brown silty CLAY					1.30				
							2.00	DV	88	
									98	
							2.50	DV	120	
									130	
3.00	End of BH							3.00	DV	130+
									130+	
Remarks:						Key:			To	Max
Bh ends at 3.0m. BH open with standing water level at 1.0m on completion, no roots observed						D - Disturbed Sample			Depth	Dia
						B - Bulk Sample			(m)	(mm)
						W - Water Sample				
						J - Jar Sample				
						V - Pilcon Shear Vane (kPa)				
						M - Mackintosh Probe			1.00	
						TDTD - Too Dense To Drive				
Logged:	DB	AM	Checked:	Approved:	Version	V1.0 28/01/16		N.T.S.		

REPORT NUMBER: C5008116 / 337861.1.1.3  
 TRIAL PIT REF: TP2 DATE: 12/03/2025  
 CLIENT: Crawford & Co SITE: 6 NICHOLAS WAY  
 JOB NO: 977919 WEATHER: Dry  
 EXCAVATION METHOD: Hand tools



For Strata below 600mm see Bore Hole log

Key:

D Small disturbed sample J Jar sample  
 B Bulk disturbed sample V Pilcon vane (kPa)  
 W Water sample M Mackintosh probe  
 TDTD Too dense to drive

Remarks:

Test results reported relate only to the items tested.  
 This report shall not be reproduced except in full without approval of the Laboratory.  
 The laboratory does not apply a conformity statement to test reports as standard, unless specifically requested by the customer.  
 Amended report. This test report supersedes test report version 2 -

For and on behalf of CTS  
 Adam Mason - Quality Control

Approved Signatory  
 Report date 12-Mar-25

Borehole		2		Sheet:	1 of 1		Site:	6 NICHOLAS WAY			
Boring Method:		Hand Auger		Job No:	977919		Client:	Crawford Claims Management			
Diameter (mm):		75		Date:	11/03/2025						
Weather:		Dry		Ground Level:							
Depth	Soil Description						Thickness	Legend	Depth	Type	Result
(m)											
0.00	See Trial Pit						0.80				
0.80	Firm orange-brown silty CLAY						0.20	x — x			
1.00	Soft wet orange-brown silty CLAY						0.50	x — x	1.00	DV	22
								x — x			22
								x — x			
								x — x			
								x — x			
1.50	Stiff orange-brown silty CLAY						1.50	x — x	1.50	DV	78
								x — x			82
								x — x			
								x — x			
								x — x			
								x — x	2.00	DV	98
								x — x			90
								x — x			
								x — x			
								x — x	2.50	DV	98
								x — x			108
								x — x			
								x — x			
								x — x			
3.00	End of BH								3.00	DV	130+
											130+
Remarks:							Key:				
Bh ends at 3.0m. BH open with standing water level at 1.1m on completion, no roots observed below 1.7m.							D - Disturbed Sample				
							B - Bulk Sample				
							W - Water Sample      Roots				
							J - Jar Sample      Roots				
							V - Pilcon Shear Vane (kPa) Roots				
							M - Mackintosh Probe      Depth to Water (m)				
							TDTD - Too Dense To Drive				
							To      Max				
							Depth      Dia				
							(m)      (mm)				
							1.70      1				
							1.10				
Logged:	DB	AM	Checked:	Approved:	Version	V1.0 28/01/16		N.T.S.			

## SITE INVESTIGATION LABORATORY TEST REPORT

**SI REPORT NUMBER:** 977919

**CLIENT :** CET Property Assurance (Crawford Claims Management)

**SITE:**  
6 Nicholas Way  
Northwood  
HA6 2TS

**DATE OF SITE VISIT:**  
11/03/2025

**DATE RECEIVED BY LABORATORY:**  
14/03/2025

Approved by :   
C Kosma - Project Delivery Supervisor

**DATE REPORTED:** 18-Mar-2025

# The testing on this report has been subcontracted, see Summary for testing  
Laboratory details

# Laboratory Summary Results

Our Ref : 977919  
 Location : 6 Nicholas Way  
 Client: CET Property Assurance (Crawford Claims Management)  
 Address: CET, Unit 4, Boundary Court, Willow Farm Business Park, Castle Donington, DE74 2NN

Date Sampled: 11/03/2025  
 Date Received : 14/03/2025  
 Date Tested : 17/03/2025  
 Date of Report : 18/03/2025

Sample Ref		Type	# Moisture Content (%) [11]	# Soil Fraction > 0.425mm (%) [2]	# Liquid Limit (%) [3]	# Plastic Limit (%) [4]	~ Plasticity Index (%) [5]	~ Liquidity Index [5]	~ Modified * Plasticity Index (%) [6]	~ Soil * Class [7]	# Filter Paper Contact Time (d)	# Soil Sample Suction (kPa) [8]	# Oedometer Strain [9]	~ Estimated * Heave Potential (Dd) (mm)[10]	In situ * Shear Vane Strength (kPa) [11]	Organic * Content (%) [12]	pH Value [13]	Sulphate Content		* Class [16]
TP/BH No	Depth (m)																	SO <sub>3</sub> (g/l)* [14]	SO <sub>4</sub> (mg/l) [15]	
1	U/S B 0.30	D	37	<5	70	27	43	0.23	43	CV					32					
	U/S A 1.50	D	32	<5	67	25	42	0.16	42	CH					102					
	2.0	D	37	<5	73	27	46	0.22	46	CV					94					
	2.5	D	38	<5											126					
	3.0	D	39	<5	77	30	47	0.19	47	CV					> 130					

**Test Methods / Notes**

- [1] BS 1377 - Part 2 : 2022 : Clause 4
- [2] Estimated if <5%, otherwise measured
- [3] BS 1377 - Part 2 : 2022 : Clause 5
- [4] BS 1377 - Part 2 : 2022 : Clause 6
- [5] BS 1377 - Part 2 : 2022 : Clause 6
- [6] BRE Digest 240 : 1993
- [7] BS 5930 : 2018 : Figure 8 - Plasticity Chart for the classification of fines soils

[8] Building Research Establishment Information Paper 4/93

[9] In Accordance with BS 1377-5 : 1990 : Clause 3

[10] Estimated Heave Potential (Dd)

[11] Values of shear strength were determined in situ by CTS using

a Pilcon hand vane or Geonor vane (GV).

[12] BS 1377 : Part 3 : 2018 + A1 2021 Clause 4 - Tested By CTS Leicester

[13] BS 1377 : Part 3 : 2018 + A1 2021 Clause 12 - Tested By CTS Leicester

[14] Sulphate content as SO<sub>3</sub> as required by BS 1377: Part 3: 1990 has been provided for information purposes - Tested By CTS Leicester

[15] BS 1377 : Part 3 : 2018 + A1 2021 Clause 7.6 - Tested By CTS Leicester

[16] BRE Special Digest One (Concrete in Aggressive Ground) August 2005

Note that if the SO<sub>4</sub> content falls into the DS-4 or DS-5 class, it would be prudent to consider the sample as falling into the DS-4M or DS-5M class respectively unless water soluble magnesium testing is undertaken to prove otherwise.

PSD Chart - BS 1377: Part 2 : 1990, Test No 9.2

~ Calculations performed using subcontracted data.

\* These tests are not UKAS accredited

**# These tests have been subcontracted and carried out by PSL (Part of the Phenna Group)**

Full reports can be provided upon request.

**Key**

- D Disturbed sample ( small )
- B Disturbed sample ( bulk )
- U Undisturbed sample
- W Groundwater sample
- ENP Essentially Non-Plastic by inspection
- U/S Underside of Foundation

Test results reported relate only to the items tested.

This report shall not be reproduced except in full without approval of the laboratory.

The laboratory does not apply a conformity statement to test reports as standard, unless specifically requested by the customer.

Opinions and interpretations expressed herein are outside of the scope of UKAS accreditation.

Version: BH V1 SUBCON - 28.03.2023

# Laboratory Summary Results

Our Ref : 977919  
 Location : 6 Nicholas Way  
 Client: CET Property Assurance (Crawford Claims Management)  
 Address: CET, Unit 4, Boundary Court, Willow Farm Business Park, Castle Donington, DE74 2NN

Date Sampled : 11/03/2025  
 Date Received : 14/03/2025  
 Date Tested : 17/03/2025  
 Date of Report : 18/03/2025

Sample Ref.		Type	# Moisture Content (%) [11]	# Soil Fraction > 0.425mm (%) [2]	# Liquid Limit (%) [3]	# Plastic Limit (%) [4]	~ Plasticity Index (%) [5]	~ Liquidity Index [5]	~ Modified Plasticity Index (%) [6]	~ Soil Class [7]	# Filter Paper Contact Time (d)	# Soil Sample Suction (kPa) [8]	# Oedometer Strain [9]	~ Estimated Heave Potential (Dd) (mm) [10]	In situ Shear Vane Strength (kPa) [11]	Organic Content (%) [12]	pH Value [13]	Sulphate Content		* Class [16]	
TP/BH No.	Depth (m)																	SO3 (g/l)* [14]	SO4 (mg/l) [15]		
2	U/S 0.32	D	35	<5	76	29	47	0.12	47	CV					52						
	1.0	D	90	<5	99	39	60	0.84	60	CE					22						
	1.5	D	36	<5											80						
	2.0	D	36	<5	63	24	39	0.32	39	CH					94						
	2.5	D	41	<5											103						
	3.0	D	43	<5	70	29	41	0.35	41	CV					> 130						

**Test Methods / Notes**

- [1] BS 1377 - Part 2 : 2022 : Clause 4
- [2] Estimated if <5%, otherwise measured
- [3] BS 1377 - Part 2 : 2022 : Clause 5
- [4] BS 1377 - Part 2 : 2022 : Clause 6
- [5] BS 1377 - Part 2 : 2022 : Clause 6
- [6] BRE Digest 240 : 1993
- [7] BS 5930 : 1981 : Figure 31 - Plasticity Chart for the classification of fine soils.

[8] Building Research Establishment Information Paper 495

- [9] In Accordance with BS 1377-5 : 1990 : Clause 3
- [10] Estimated Heave Potential (Dd)
- [11] Values of shear strength were determined in situ by CTS using a Pilcon hand vane or Geonor vane (GV).
- [12] BS 1377 : Part 3 : 2018 + A1 2021 Clause 4 - Tested By CTS Leicester
- [13] BS 1377 : Part 3 : 2018 + A1 2021 Clause 12 - Tested By CTS Leicester
- [14] Sulphate content as SO3 as required by BS 1377: Part 3: 1990 has been provided for information purposes - Tested By CTS Leicester
- [15] BS 1377 : Part 3 : 2018 + A1 2021 Clause 7.6 - Tested By CTS Leicester

[16] BRE Special Digest One (Concrete in Aggressive Ground) August 2005

Note that if the SO4 content falls into the DS-4 or DS-5 class, it would be prudent to consider the sample as falling into the DS-4M or DS-5M class respectively unless water soluble magnesium testing is undertaken to prove otherwise.

PSD Chart - BS 1377: Part 2 : 1990, Test No 9.2

**Key**

- D Disturbed sample ( small )
- B Disturbed sample ( bulk )
- U Undisturbed sample
- W Groundwater sample
- ENP Essentially Non-Plastic by inspection
- U/S Underside of Foundation

~ Calculations performed using subcontracted data.

\* These tests are not UKAS accredited

**# These tests have been subcontracted and carried out by PSL (Part of the Phenna Group)**

Full reports can be provided upon request.



Test results reported relate only to the items tested.  
 This report shall not be reproduced except in full without approval of the laboratory.  
 The laboratory does not apply a conformity statement to test reports as standard, unless specifically requested by the customer.  
 Opinions and interpretations expressed herein are outside of the scope of UKAS accreditation.

Version: BH V1 SUBCON - 28.03.2023

# Moisture Content Profiles

Our Ref : 977919  
 Location : 6 Nicholas Way  
 Work carried out for: CET Property Assurance (Crawford Claims Management)

Date Sampled : 11/03/2025  
 Date Received : 14/03/2025  
 Date Tested : 17/03/2025  
 Date of Report : 18/03/2025



Notes

1. If plotted, 0.4 LL and PL+2 ( after Driscoll, 1983 ) should only be applied to London Clay ( and similarly overconsolidated clay) at shallow depths.
2. Unless specifically noted the profiles have not been related to a site datum.

Note

1. Unless otherwise stated, values of Shear Strength were determined in situ by CTS using a Picon Hand Vane the calibration of which is limited to a maximum reading of 130 kPa.
2. Unless specifically noted the profiles have not been related to a site datum.

Construction Testing Solutions  
4 Oak Spinney Park  
Ratby Lane  
Leicester Forest East  
Leicestershire  
LE3 3AW

Intec  
Parc Menai, Bangor,  
Gwynedd, North Wales  
LL57 4FG  
Tel: 01248 672652  
Fax: 01248 672601

# ROOT IDENTIFICATION

**6 Nicholas Way,**

Client Reference: 977919  
Report Date: 19 March 2025  
Our Ref: R60157

Sub Sample	Species Identified		Root Diameter	Starch
<b>TP1B:</b>				
USF	<i>Aesculus</i> spp.	1	30 mm	Abundant
USF	<i>Hedera</i> or <i>Fatsia</i> spp.	2	5 mm	Abundant
<b>TP2:</b>				
USF	<i>Quercus</i> spp.	3	12 mm	Abundant
USF	<i>Aesculus</i> spp.		1.5 mm	Low
<b>BH2:</b>				
to 1.7m	<i>Quercus</i> spp.	4	1 mm	Abundant

**Comments:**

- 1 - Plus 3 others also identified as *Aesculus* spp.
- 2 - Plus 2 others the same.
- 3 - Plus 2 others also identified as *Quercus* spp.
- 4 - Plus 2 others also identified as *Quercus* spp.

*Aesculus* spp. are horse chestnuts.  
*Hedera* spp. include ivy; *Fatsia* spp. are shrubs closely related to ivy.  
*Quercus* spp. are oaks (both deciduous and evergreen).

**Signed:** M D Mitchell

Unless we are otherwise instructed in writing, the above sample material will normally be disposed of 6 years after the date of this report.

