

134	383	6000	23	3	4	0.3 + 0.1 (2.6)	58 (3.9)	5 (0.0)*	9.0	13	13	26
135	168	2300	26	18	18	0.6 + 0.2 (4.7)	77 (2.2)	2	6.9	13	13	26
136	693	1800	72	2	7	0.0 + 1.3 (7.3)	0 (0.0)	1	7.3			
141	975	4000	25	7	1	0.0 + 0.2 (1.0)	0 (0.0)	0	1.0			
142	1249	8000	34	7	9	2.7 + 0.3 (17.0)	62 (18.4)	12	35.4	14	24	46
143	2860	8000	78	2	6	3.1 + 1.7 (27.5)	20 (10.0)	8 (0.0)*	37.5	14	24	46
144	80	1800	12	3	13	0.2 + 0.1 (1.7)	65 (0.9)	1 (0.0)*	2.6	14	1	19
145	344	1800	50	4	17	1.1 + 0.5 (9.1)	86 (2.3)	4 (0.0)*	14.1	14	1	19
146	452	2600	46	4	15	1.5 + 0.4 (10.7)	73 (5.7)	5 (0.0)*	16.4	14	1	19
151	334	1000	37	4	4	0.0 + 0.3 (1.9)	16 (0.9)	1 (0.0)*	2.8			
152	628	1800	56	2	7	0.6 + 0.6 (7.3)	36 (1.7)	3 (0.0)*	10.0	15	36	16
153	357	1800	32	4	9	0.6 + 0.2 (4.9)	56 (3.5)	3 (0.0)*	8.5	15	36	16
154	361	1000	42	3	4	0.0 + 0.4 (2.1)	0 (0.0)	0	2.1			
155	26	2300	5	18	19	0.1 + 0.0 (0.8)	79 (0.4)	0	1.1	15	21	31
156	509	6000	39	3	12	1.4 + 0.3 (9.6)	94 (8.3)	7 (0.1)*	30.4	15	21	31
161	383	6000	23	2	14	1.4 + 0.1 (8.7)	82 (5.5)	5 (0.0)*	14.2	16	7	20
162	2860	8000	64	3	4	2.3 + 0.9 (17.9)	21 (14.1)	9 (0.0)*	32.0	16	25	2
163	509	6000	30	2	14	1.8 + 0.2 (11.5)	69 (6.1)	5 (0.0)*	17.6	16	7	20
164	1329	8000	30	2	1	0.3 + 0.2 (3.0)	6 (1.4)	1 (0.0)*	4.4	16	25	2
171	789	3600	55	18	14	2.5 + 0.6 (17.9)	74 (18.0)	9	35.8	17	34	3
172	1607	3000	54	18	1	0.0 + 0.6 (3.3)	3 (1.3)	1	4.6			
173	617	3949	36	6	9	1.2 + 0.3 (8.3)	43 (8.3)	4 (0.0)*	16.6	17	8	29
174	956	3752	61	6	4	0.2 + 0.8 (5.6)	9 (2.7)	3 (0.0)*	8.3	17	9	29
181	1024	2000	51	12	2	0.1 + 0.5 (3.8)	17 (3.0)	8	6.8			
182	1839	4000	88	7	15	3.8 + 3.7 (42.5)	56 (18.0)	18	60.5	18	24	49
183	956	3880	77	6	25	5.1 + 1.7 (38.5)	72 (8.3)	10 (0.0)*	46.8	18	4	19
184	789	5100	52	4	15	2.8 + 0.5 (19.2)	100 (24.3)	11 (0.0)*	43.5	18	5	19
191	1125	3500	32	9	1	0.0 + 0.2 (1.3)	2 (0.5)	0	1.9			

0	50	SECOND	CYCLE	25	STEPS							
0 LINK	FLOW	SAT	DEGREE	MEAN	TIMES	-----DELAY-----	-----STOPS-----	-----QUEUE-----	PERFORMANCE	EXIT	GREEN	TIMES
NUMBER	INTO	FLOW	OF	PER	PCU	UNIFORM	RANDOM	COST	INDEX	NODE	START	START
	LINK		SAT	CRUISE		(U+R+O=MEAN Q)	OVERSAT	OF	OF		END	END
		(PCU/H)	(PCU/H)	(%)	(SEC)	(PCU-H/H)	(%)	(\$/H)	(PCU)		1ST	2ND
192	227	3800	33	13	22	1.1 + 0.2 (7.8)	87 (6.1)	3	13.9	19	9	17
193	1227	5400	36	8	5	1.5 + 0.3 (10.0)	53 (20.2)	11 (0.0)*	30.2	19	22	3
194	1852	3600	83	6	6	0.7 + 2.4 (17.4)	20 (11.4)	13 (0.0)*	28.9	19	23	3
201	2078	5714f	87	9	18	7.4 + 3.2 (60.3)	89 (57.0)	29	117.3	20	5	25
202	956	3200f	71	9	16	2.9 + 1.2 (23.7)	76 (22.4)	11	46.0	20	5	25
203	1852	5580	83	7	16	5.8 + 2.4 (46.9)	60 (13.5)	18 (0.0)*	62.9	20	31	0
204	227	4000	16	5	20	1.1 + 0.1 (7.0)	102 (7.2)	3 (0.0)*	14.2	20	33	0
1820	451	2000	43	7	9	0.8 + 0.4 (6.6)	41 (3.2)	3	9.8	18	24	49
2020	390	1950	48	9	15	1.1 + 0.5 (9.1)	72 (8.7)	4	17.7	20	5	25

*** f - average saturation flow for flared link ***

0	TOTAL	TOTAL	MEAN	TOTAL	TOTAL	TOTAL	TOTAL	PENALTY	TOTAL			
DISTANCE	TIME	JOURNEY	SPEED	UNIFORM	RANDOM	COST	COST	FOR	PERFORMANCE			
TRAVELLED	SPENT			DELAY	OVERSAT	OF	OF	EXCESS	INDEX			
(PCU-KM/H)	(PCU-H/H)	(KM/H)		(PCU-H/H)	(PCU-H/H)	(\$/H)	(\$/H)	(\$/H)	(\$/H)			
0	5176.6	175.0	29.6	66.8	31.3	(559.3)	+ (375.8)	+ (89.8)	= 1024.9	TOTALS		