



3NO. LAMBETH BIKEHANGER
SECURE CYCLE STORES.

BOTWELL LANE

GOLDEN
CRESCENT

CHURCH ROAD

CENTRAL AVENUE

2NO. EXISTING LONDON PLANE
TREES TO BE REMOVED.

NEW 500KVA ELECTRICITY
SUB STATION.

HATCH INDICATES AREA OF
UNRESTRICTED VEHICULAR
ACCESS AT ALL TIMES TO
ELECTRICITY SUB STATION.

LEGEND

- STONE MASTIC ASPHALT TO ENGINEER'S DETAILS TO LIDL 2012 SPECIFICATION AND BS EN 13108-5. MAXIMUM 2% GRADIENT. MINIMUM 44 TON HGV LOADING CAPACITY.
- POLYMER MODIFIED BITUMEN (PMB) WITH GRAVEL 0/10 TO HGV TURNING AREA AS LIDL HARDSTANDING FUNCTIONAL DESCRIPTION SPECIFICATION. MINIMUM 44 TON HGV LOADING CAPACITY.
- 200 x 100 x 80MM THICK INTERLOCKING CONCRETE BLOCK PAVING. NON-BEVELLED PENCIL-EDGE PROFILE. MAXIMUM 2% FALLS. BLOCK COLOUR: ANTHRACITE WITH LIGHT GREY BLOCKS AS PARKING SPACE DEMARCATION. MINIMUM 44 TON HGV LOADING CAPACITY.
- 200 x 100 x 80MM THICK INTERLOCKING CONCRETE BLOCK PAVING LAID TO PROVIDE FLUSH THRESHOLD TO ENTRANCE AND EXIT DOORS: NON-BEVELLED PENCIL-EDGE PROFILE ON SEMI-DRY LEAN-MIX BEDDING MORTAR. MAXIMUM 2% FALLS. HERRINGBONE LAYING PATTERN. BLOCK COLOUR: ANTHRACITE.
- 300 x 300MM CONCRETE PAVINGS. COLOUR: GREY.
- TOBERMORE 'PEDESTA' 200 x 100 x 80MM THICK INTERLOCKING CONCRETE BLOCK PAVING WITH PENCIL EDGES. MAXIMUM 2% FALLS. MINIMUM 1% FALLS.
- REINFORCED CONCRETE RAMP TO DELIVERY BAY. BRUSHED SURFACE FINISH (TRAVERSELY TO DIRECTION OF TRAVEL). MAXIMUM 6% GRADIENT.
- TACTILE PAVING TO DIAGRAM 1 OF APPROVED DOCUMENT M. COLOUR: BUFF

KERBING

BLOCK PAVING	SMA	FLUSH KERB 125 x 255MM TYPE CS1 TO BS EN 1340
FOOTPATH / LANDSCAPING	BLOCK PAVING	CHAMFERED KERB 125 x 255MM TYPE HB2 TO BS EN 1340
FOOTPATH	CONCRETE RAMP	TRIEF CONTAINMENT KERB 415 x 380MM TO BS EN 1317

