


LEGEND

-  STONE MASTIC ASPHALT TO ENGINEER'S DETAILS TO LIDL 2012 SPECIFICATION AND BS EN 13108-5. MAXIMUM 2% GRADIENT. MINIMUM 44 TON HGV LOADING CAPACITY.
-  200 x 100 x 80MM THICK INTERLOCKING CONCRETE BLOCK PAVING. NON-BEVELLED PENCIL-EDGE PROFILE. MAXIMUM 2% FALLS. BLOCK COLOUR: ANTHRACITE WITH LIGHT GREY BLOCKS AS PARKING SPACE DEMARCATION. MINIMUM 44 TON HGV LOADING CAPACITY.
-  200 x 100 x 80MM THICK INTERLOCKING CONCRETE BLOCK PAVING LAID TO PROVIDE FLUSH THRESHOLD TO ENTRANCE AND EXIT DOORS: NON-BEVELLED PENCIL-EDGE PROFILE ON SEMI-DRY LEAN-MIX BEDDING MORTAR. MAXIMUM 2% FALLS. HERRINGBONE LAYING PATTERN. BLOCK COLOUR: ANTHRACITE.
-  REINFORCED CONCRETE RAMP TO DELIVERY BAY. BRUSHED SURFACE FINISH (TRAVERSELY TO DIRECTION OF TRAVEL). MAXIMUM 6% GRADIENT.
-  300 x 300MM CONCRETE PAVINGS. COLOUR: GREY.
-  TACTILE PAVING TO DIAGRAM 1 OF APPROVED DOCUMENT M. COLOUR: BUFF.

