


QUOTATION

	Abacus Windows Commercial Ltd	Quotation No : 26400
	Abacus House 29a RobJohns Road Widford Industrial Estate Chelmsford CM1 3AG Tel : 01245 349797 Fax : 01245 349095	Printed Date : 11-Aug-2025 Representative : SR Customer : Pricing Method : Manual
	Quotation Spec Glazed / Supply Only	
THISTLE WINDOWS UNIT 5 , 177/181 HORNCHURCH RO HORNCHURCH ESSEX RM12 4TE Tel:01708 474 805 Fax: 01708 474 806	Quotation Reference Acelux	

System 10 MkII Multi Segment	Back Door	
	Specification	

680x900 >




680x900 >

1580 x 2058


Colour	White
Sash colour	White
Cill colour	White
Reinforcing rule	Standard Reinforcing
Cill	P90042 150mm Cill
Drainage	Concealed Drainage
Rated Products	A Rated

Notes :

1	System 10 MkII Casement	Back Door 1 of 2 of Multi-segment	
	O/A Sizes 680mm x 2028mm (Style 1)	Specification	
		Colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Reinforcing rule Bead type Drainage Add-on (Right jamb) Rated Products	White P10502 72mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram Standard Reinforcing Ovolo Bead Concealed Drainage 6mm Ali Coupler A Rated


Glazing Details & Apertures
4-20-4 A Rated Clr Tuff Softcoat/Low Iron Arg Gas : 20mm Blk W/Edge Sp
Georgian Bar 18mm 18mm Bar White Std Joints
A1 - (592 x 1930)

Notes :

2	System 10 MkII Single Door	Back Door 2 of 2 of Multi-segment	
	O/A Sizes 900mm x 2028mm (Style 2 - Dr)	Specification	
		Colour Sash colour Frame (Head) Frame (Left jamb) Frame (Right jamb) Sash Reinforcing rule Threshold Bead type Drainage Open in/out Handle Cylinder Door lock Door hinge Rated Products	White White P10502 72mm Sys 10 O/Fram P10502 72mm Sys 10 O/Fram P10502 72mm Sys 10 O/Fram P10510/P10511 110mm SysDr Standard Reinforcing AM3EX-78 Ali Thr O/IN - Sil Ovolo Bead Concealed Drainage **** OPEN IN **** Lever/Lever - White Standard Cylinder Milenco Door Lock SFS Adj Hinges - White A Rated

Glazing Details & Apertures
4-20-4 A Rated Clr Tuff Softcoat/Low Iron Arg Gas : 20mm Blk W/Edge Sp
Georgian Bar 18mm 18mm Bar White Std Joints
A1 - (624 x 1776)

Notes :

3	Single Rebate Comp (Sys 10)	
O/A Sizes 1070mm x 2220mm (3 - Comp D	Specification	
	Colour Cill colour Frame (Head) Frame (Left jamb) Frame (Right jamb) Sash Transom Reinforcing rule Threshold Cill Drainage Open in/out Add-on (Left jamb) Add-on (Right jamb) Handle Cylinder Door lock Door hinge	White White P10502 72mm Sys 10 O/Fram P10502 72mm Sys 10 O/Fram P10502 72mm Sys 10 O/Fram Single Rebate Comp Sash P10503/P10506 70mm Sys10 Fully Reinforced AM3EX-70 Ali Thr O/IN - Sil P90042 150mm Cill Concealed Drainage **** OPEN IN **** P01091 30mm Frame Extensi P01092 50mm Frame Extensi Lev/Lev Split Spindle - Chrom Standard Cylinder VBH Composite Door Lock SFS Adj Hinges - White


Glazing Details & Apertures

4-20-4 A Rated Obs Tuff Softcoat/Low Iron Arg Gas : 20mm Blk W/Edge Sp
Stippolyte Single Geo Bar (V) 18mm Bar White Std Joints
A1 - (876 x 103)

Panel Details & Apertures

Door Stop Composite Door / K 2 Panel 1 Grill / Glazed / White External
Slab / Glazed / Satin / Chrome Letterbox (Middle) White Internal Slab /
High Security /
A3 - (874 x 1971)

Notes :

4	Single Rebate Comp (Sys 10)	
O/A Sizes 890mm x 2500mm (3 - Comp D	Specification	
	Colour Cill colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Sash Transom Reinforcing rule Cill Drainage Open in/out Handle Cylinder Door lock Door hinge	White White P10502 72mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10502 72mm Sys 10 O/Fram P10502 72mm Sys 10 O/Fram Single Rebate Comp Sash P10503/P10506 70mm Sys10 Fully Reinforced P90042 150mm Cill Concealed Drainage **** OPEN IN **** Lever/Lever - Chrome Standard Cylinder VBH Composite Door Lock SFS Adj Hinges - White

Glazing Details & Apertures

4-20-4 A Rated Obs Tuff Softcoat/Low Iron Arg Gas : 20mm Blk W/Edge Sp
Stippolyte Single Geo Bar (V) 18mm Bar White Std Joints
A1 - (776 x 343)

Panel Details & Apertures

Door Stop Composite Door / K 2 Panel 1 Grill / Glazed / White External
Slab / Glazed / Satin / Chrome Letterbox (Middle) White Internal Slab /
High Security /
A3 - (774 x 1989)


Notes :

5	System 10 MkII Casement	
O/A Sizes 990mm x 1610mm (Style 6)		Specification
		Colour Sash colour Cill colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Sash (Head) Sash (Cill) Sash (Left jamb) Sash (Right jamb) Transom Reinforcing rule Bead type Cill Drainage Add-on (Left jamb) Casement locking Handle Friction stay Rated Products
		White White White P10502 72mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10503/P10506 70mm Sys10 Standard Reinforcing Ovolo Bead P90042 150mm Cill Concealed Drainage 6mm Ali Coupler ShootBolt Espaq White Handle Standard Stay A Rated

Glazing Details & Apertures

4-20-4 A Rated Clear Softcoat/Low Iron Argon Gas : 20mm Blk W/Edge Sp
Georgian Bar 18mm 18mm Bar White Std Joints
A1 - (808 x 249)
4-20-4 A Rated Clr Tuff Softcoat/Low Iron Arg Gas : 20mm Blk W/Edge Sp
Georgian Bar 18mm 18mm Bar White Std Joints
A4 - (902 x 1099)

Notes :

6	System 10 MkII Casement	
O/A Sizes 1270mm x 1580mm (Style 43)		Specification
		Colour White Sash colour White Cill colour White Frame (Head) P10501 56mm Sys 10 O/Fram Frame (Cill) P10501 56mm Sys 10 O/Fram Frame (Left jamb) P10501 56mm Sys 10 O/Fram Frame (Right jamb) P10501 56mm Sys 10 O/Fram Sash (Head) P10508 Sys 10 T Casement S Sash (Cill) P10508 Sys 10 T Casement S Sash (Left jamb) P10508 Sys 10 T Casement S Sash (Right jamb) P10508 Sys 10 T Casement S Transom P10503/P10506 70mm Sys10 Mullion P10503/P10506 70mm Sys10 Reinforcing rule Standard Reinforcing Bead type Ovolo Bead Cill P90042 150mm Cill Drainage Concealed Drainage Add-on (Left jamb) P01068 15mm Frame Extensi Add-on (Right jamb) P01068 15mm Frame Extensi Casement locking ShootBolt Espaq Handle White Handle Friction stay Standard Stay Rated Products A Rated Ventilator (Sash) 4000 Trickle Vent
Aperture Options		
Ventilator (Sash) 4000 Trickle Vent (F1)		

Glazing Details & Apertures


4-20-4 A Rated Clear Softcoat/Low Iron Argon Gas : 20mm Blk W/Edge Sp

Georgian Bar 18mm 18mm Bar White Std Joints

F7 - (480 x 975) A1 - (544 x 359)

A7 - (544 x 1069) F1 - (480 x 265)


Notes :

7	System 10 MkII Casement	
O/A Sizes 1890mm x 1580mm (Style 62)	Specification	
	Colour Sash colour Cill colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Sash (Head) Sash (Cill) Sash (Left jamb) Sash (Right jamb) Transom Mullion Reinforcing rule Bead type Cill Drainage Add-on (Left jamb) Add-on (Right jamb) Casement locking Handle Friction stay Rated Products Ventilator (Sash) Ventilator (Sash)	White White White P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10503/P10506 70mm Sys10 P10503/P10506 70mm Sys10 Standard Reinforcing Ovolo Bead P90042 150mm Cill Concealed Drainage P01068 15mm Frame Extensi P01068 15mm Frame Extensi ShootBolt Espag White Handle Standard Stay A Rated 4000 Trickle Vent 4000 Trickle Vent
Aperture Options		
Ventilator (Sash) 4000 Trickle Vent (H7)(A7)		

Glazing Details & Apertures

4-20-4 A Rated Clear Softcoat/Low Iron Argon Gas : 20mm Blk W/Edge Sp
Georgian Bar 18mm 18mm Bar White Std Joints
A1 - (559 x 359) H7 - (465 x 975)
A7 - (465 x 975) D1 - (486 x 265)
D7 - (580 x 1069) H1 - (559 x 359)


Notes :

8	Vertical Slider - 1.4 U Value	
Qty (6) O/A Sizes 1100mm x 1755mm (Bot	Specification	
	Colour Frame (Head) Frame (Left jamb) Frame (Right jamb) Sash Cill Ventilator (Head) Rated Products V/S Sash Horns V/S Furniture Colour V/S Travel Restrictors V/S Pole Eyes V/S 'D' Handle V/S Sash Lifts	V/S Standard White VS Frame VS Frame VS Frame VS Sash V/S 152mm Cill V/S Night Vent A Rated Run Through Sash Horns White Furniture V/S Travel Restrictors. V/S Pole Eyes NO 'D' Handle V/S Sash Lifts

Glazing Details & Apertures

V/S 4-16-4 Clear Tuff Softcoat - A+ Rated : 16mm Blk W/Edge Sp
A1 - (926 x 717) A6 - (926 x 753)

Notes :


9	System 10 MkII Casement	
O/A Sizes 680mm x 755mm (Style 6)		Specification
		Colour Sash colour Cill colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Sash (Head) Sash (Cill) Sash (Left jamb) Sash (Right jamb) Transom Reinforcing rule Bead type Cill Drainage Casement locking Handle Friction stay Ventilator (Sash) Rated Products
		White White White P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10503/P10506 70mm Sys10 Standard Reinforcing Ovolo Bead P90042 150mm Cill Concealed Drainage ShootBolt Espag White Handle Standard Stay 4000 Trickle Vent A Rated

Glazing Details & Apertures

4-20-4 A Rated Obs Softcoat/Low Iron Argon Gas : 20mm Blk W/Edge Sp Stippolyte

A1 - (504 x 220) A4 - (598 x 289)

Notes :


10	System 10 MkII Casement	
O/A Sizes 680mm x 755mm (Style 6)		Specification
		Colour Sash colour Cill colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Sash (Head) Sash (Cill) Sash (Left jamb) Sash (Right jamb) Transom Reinforcing rule Bead type Cill Drainage Casement locking Handle Friction stay Ventilator (Sash) Rated Products
		White White White P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10503/P10506 70mm Sys10 Standard Reinforcing Ovolo Bead P90042 150mm Cill Concealed Drainage ShootBolt Espag White Handle Standard Stay 4000 Trickle Vent A Rated

Glazing Details & Apertures

4-20-4 A Rated Obs Softcoat/Low Iron Argon Gas : 20mm Blk W/Edge Sp Stippolyte

A1 - (504 x 220) A4 - (598 x 289)

Notes :

11	System 10 MkII Casement	
O/A Sizes 500mm x 620mm (Style 6)		Specification
		Colour Sash colour Cill colour Frame (Head) Frame (Cill) Frame (Left jamb) Frame (Right jamb) Sash (Head) Sash (Cill) Sash (Left jamb) Sash (Right jamb) Transom Reinforcing rule Bead type Cill Drainage Casement locking Handle Friction stay Ventilator (Sash) Rated Products
		White White White P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10501 56mm Sys 10 O/Fram P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10508 Sys 10 T Casement S P10503/P10506 70mm Sys10 Standard Reinforcing Ovolo Bead P90042 150mm Cill Concealed Drainage ShootBolt Espag White Handle Standard Stay 2500 Trickle Vent A Rated

Glazing Details & Apertures

4-20-4 A Rated Obs Softcoat/Low Iron Argon Gas : 20mm Blk W/Edge Sp Stippolyte

A1 - (324 x 140) A4 - (418 x 234)

Notes :

Total	£0.00
VAT @ 20.00%	£0.00
Total (Incl. VAT)	£0.00