

Notes

ALL MEASUREMENTS, DIMENSIONS SHOULD BE VERIFIED ON SITE AND IN ACCORDANCE TO EXISTING SITE CONDITIONS. DRAWING SHOWN FOR DESIGN INTENT ONLY. SHOP DRAWING TO BE PREPARED BY SPECIALIST AND SUBMITTED FOR LANDSCAPE ARCHITECT'S APPROVAL.

ALL PAVING MATERIAL FOR EVA OR VEHICLE AREAS USE 80mm THK.

Rev.	Description	Date Issued

05	TREE GRILLE OMITTED	[22/10/2015
04	LIGHTING REVISION	[02/07/2015
03	CONSTRUCTION DOCUMENTS	[21/11/2014
02	VE SUBMISSION	[29/05/2014
01	TENDER SUBMISSION	[10/12/2013
00	1ST SUBMISSION	[28/11/2013



Client

MAGILL INVESTMENTS LIMITED

Project

HEATHROW GATE HOTEL
27 UXBRIDGE ROAD
HAYES, MIDDLESEX
UB4 0JN



ST LEGERE
EST 1999

St. Legere Design International Ltd.
7/F, Pacific Plaza,
410 Des Voeux Road West,
Shek Tong Tsui, HK

Project Phase

CONSTRUCTION DOCUMENTS

Drawing Title

LIGHTING PLAN
G/F

Designed by: VV BW TY

Drawn by: BW TY

Checked by: VV DS

Project no. Scale

1305

1:200 (A1)

DWG no. Rev.

LP-5.01

5

LIGHTING SCHEDULE		
REFERENCE	DESCRIPTION	PICTURE
X1	ARCHITECTURAL POLE MOUNT FITTING WITH ZERO UPWARD LIGHT. 70W CDM. 4000K. SILVER. IP65. AS CONCORD SKYLINE WITH ACCESSORY ON 6M COLUMN.	
X2	POLE MOUNT STREET LIGHT WITH ASYMMETRIC DISTRIBUTION. IP67. ZERO UPWARD LIGHT. 70W CDM. 4000K. ON 6M COLUMN. AS CONCORD MERCURY	
X3	ARCHITECTURAL SLIMLINE LED FLOODLIGHT. SILVER. 25W. 4500K. IP65. IK08. AS SYLVANIA FLOODED.	
X4	ARCHITECTURAL SURFACE MOUNTED LED UP/DOWNLIGHT. SILVER. 26W. 4000K. IP65. E = 3HR EMERGENCY. MOUNTED AT 3m AFFL TO CENTRE AS LUMIANCE INVERTO.	
X5	ARCHITECTURAL SURFACE MOUNTED LED DOWNLIGHT. SILVER. 26W. 4000K. IP65. E = 3HR EMERGENCY. AS LUMIANCE INVERTO.	
X6	LED CORROSION PROOF FITTING WITH STAINLESS STEEL V.R TOGGLES. 48W. 4000K. IP65. IK07. E = 3HR EMERGENCY. AS SYLVANIA SYLPROOF LED.	
K1	LED CORROSION PROOF FITTING WITH STAINLESS STEEL CIRCULAR TUBULAR V.R TOGGLES. 28W. 4000K. IP65. MOUNTED 1m AFFL. AS SYLVANIA SYLPROOF TUBULAR	

CCTV SYMBOL SCHEDULE	
REFERENCE	DESCRIPTION
	SURFACE MOUNTED ANALOGUE DAY & NIGHT COLOUR HIGH DEFINITION DOME CCTV CAMERA. CAMERA COMES WITH 1/2" SENSOR AND 2.8mm LENS. CAMERA COMES WITH IP68 RATING
PTZ	SURFACE MOUNTED PAN, TILT AND ZOOM ANALOGUE DAY & NIGHT COLOUR HIGH DEFINITION DOME CCTV CAMERA. CAMERA COMES WITH 1/2" SENSOR, 2.8mm LENS, 16x DIGITAL ZOOM. CAMERA COMES WITH IP68 RATING
	CCTV CAMERA MOUNTED ON 4.5M FIXED COLUMN. AS ACC1 FIXED BASE
	2No CCTV CAMERA MOUNTED ON TWIN BRACKET ON 4.5M FIXED COLUMN. AS ACC1 EMBEDDED BASE FOR GROUND FLOOR AREAS AND FIXED BASE ON FIRST FLOOR CAR PARK

A LIGHTING PLAN
SCALE 1:200