

KEY



	FOOTPATH CONCRETE SETTPAVING, 140 x 210 x 60mm (80mm for vehicular areas) To be laid as single or double staggered brick paving blocks. 140mm above ground depth for pedestrian areas, 80mm depth for vehicle areas (type 100mm Antique Turned Block from Brett to match adjacent surfaces or other similar and approved. Laid over firmed ground over 250 x 50mm C20/P mix strip foundation.
	CONCRETE SETT EDGING, 140mm wide, laid as double staggered brick paving blocks. 140mm above ground depth for pedestrian areas, 80mm depth for vehicle areas (type 100mm Antique Turned Block from Brett to match adjacent surfaces or other similar and approved. Laid over firmed ground over 250 x 50mm C20/P mix strip foundation.
	PORCELAN SLAB PAVING: Type such as 'Ecliptic' by Brett 600 x 600 x 35mm. Colour such as 'Lunar', or similar and approved. To be dry laid in stack bond, on 20mm mortar over 100mm depth permeable granular fill, over firmed ground surface.
	ROADWAYS AND FOOTPATHS: To be Blumen Macadam with 6mm gauge aggregate thickness, 100mm depth. To be laid as single or double staggered brick paving blocks. 150mm above ground depth for pedestrian areas, 100mm depth for vehicle areas (type 100mm Antique Turned Block from Brett to match adjacent surfaces or other similar and approved. To be dry laid in stack bond, on 20mm mortar over 100mm depth permeable granular fill, over firmed ground surface.
	Hoggin board with 100mm centres or steeper, compacted sand & 50mm, over 100mm depth. To be laid as single or double staggered brick paving blocks. 150mm above ground depth for pedestrian areas, 100mm depth for vehicle areas (type 100mm Antique Turned Block from Brett to match adjacent surfaces or other similar and approved. To be dry laid in stack bond, 50mm x 150mm attached with galvanised nails to 50mm at 1.5m centres or closer as required. Hoggin board to be kerfed with cuts 10mm deep and 10mm wide for sharp curves, gravel board to be kerfed with cuts 5mm vertically along the back edge.
	PRECANT CONCRETE BLOCK EDGING, 50 x 100 x 214mm, flat topped and laid flush with paving. Eging to be bedded into C20/P mix concrete strip foundation 350 x 300mm, haunched.
	DROPPED KERB, 25mm upstand to engineer's specification.
	Reinforced gravel parking bays and road ways, washed, rounded, buff coloured gravel, 20mm gauge, 40mm depth, finished level 10mm below adjacent surfaces. Gravel to be washed and rounded. Colour to be 'Lunar' or similar and approved. To be laid over firmed ground over 250 x 50mm C20/P mix strip foundation.
	SECTION OF TIMBER BOARD WALK INCLUDING HAND RAILS

REF.	DATE	INITIALS	DETAILS
CLIENT			DWG. TITLE
Corner Homes			Proposed Hard Landscape
SITE			
Hornfield Grove			
PURPOSE OF ISSUE			
DRAWN BY			
CHECHED			
AUTH'D			
SCALE			
DATE			
DWGS NO			
REF.			

JAMES BLAKE
ASSOCIATES

Head Office: 34-52 Out Westgate, Bury St Edmunds, Suffolk, IP33 3PA. Tel: (01284) 333797
jamesblake@jbl-associates.com www.jbl-associates.com

LANDSCAPE ARCHITECTURE o ARBORICULTURE o ECOLOGY

GENERAL NOTES
-ALL DIMENSIONS IN MILLIMETRES
-DO NOT SCALE OFF THIS DRAWING
-ALL DIMENSIONS TO BE CHECKED ON SITE
(C)JAMES BLAKE ASSOCIATES LTD 2023

