



KEY

- FOOTPATH CONCRETE SETTING, 140 x 210 x 60mm (80mm for vehicular areas) Type such as Alpha Antique Tumbled Black Paving from Street; Colour such as Silver Flare, or similar and approved.
- CONCRETE SETTING EDGING 140mm wide, laid as double staggered string using blocks, 140mm x 140mm, 100mm depth for vehicular areas, 50mm depth for vehicular areas (per Alpha Antique Tumbled Black from Street to match adjacent surfaces or other similar and approved). Laid over 100mm concrete mortar bed, 1:3 mix, haunched over 250 x 100mm C20/P 8 reinforcement concrete strip foundation.
- PORCELAIN SLAB PAVING, Type such as 'Eclat' by 'Bent' 600 x 600 x 20mm, Colour such as 'Lunar', or similar and approved. To be dry laid in each bed, over 20mm mortar, over 100mm depth of suitable granular fill, over firm sub-grade and geotextile. - Tensar 1000, all to fall and cross-fall, minimum 1:70 and all to Highway's Authority approval.
- ROADWAYS AND FOOTPATHS to be Blumex Macadam with 6mm gauge aggregate wearing course to be laid over 20mm gauge aggregate base course, all laid over base course of hardcore, all depths to Engineer's specification, laid over firm sub-grade and geotextile. - Tensar 1000, all to fall and cross-fall, minimum 1:70 and all to Highway's Authority approval.
- Hedge path with pressure treated timber edge, over compacted met & subgrade, over 1000 granular or similar and approved. Sawn pressure treated softwood gravel board 30mm x 100mm attached with galvanised nails to 50mm at 1.5m centres or closer as required at junctions or curves, 50mm x 600mm long softwood stakes for sharp corners, gravel board to be kerfed with cuts seen vertically along the back side.
- Natural compacted ground path with treated timber edge to mark route, for sharp corners timber to be kerfed with vertical slots in back of timber. Sawn pressure treated softwood gravel board 30mm x 100mm attached with galvanised nails to 50mm at 1.5m centres or closer as required at junctions or curves, 50mm x 600mm long softwood stakes for sharp corners, gravel board to be kerfed with cuts seen vertically along the back side.
- PRECAST CONCRETE BLOCK EDGING, 50 x 150 x 95mm, flat topped and laid flush with paving. Edging to be bedded into C20/P 8 mortar concrete strip foundation 300 x 300mm, haunched.
- DROPPED KERB, 20mm upstand or flush TO BS7263, to engineer's specification.
- Reinforced gravel parking bays and road ways, wheeled, rounded, buff coloured gravel, 20mm gauge, 40mm depth, finished level 15mm below adjacent surfaces. Gravel to be reinforced using 'Colwell' with pressure treated timber edge available from Greenwold 01455 617 139 or similar and approved all laid over base course of hardcore, all depths to Engineer's specification, laid over firm sub-grade and geotextile. - Tensar 1000.
- SECTION OF TIMBER BOARD WALK INCLUDING HAND RAILS

GENERAL NOTES

- ALL DIMENSIONS IN MILLIMETRES
- DO NOT SCALE OFF THIS DRAWING
- ALL DIMENSIONS TO BE CHECKED ON SITE

(C)JAMES BLAKE ASSOCIATES LTD 2023

REV	DATE	INITIALS	DETAILS
CLIENT		DWG. TITLE	
Corner Homes		Proposed front Landscape	
SITE			
Hatched Grove			
PURPOSE OF ISSUE			
Planning			
DRS BY	CHECKED	AUTH'D	SCALE
DCS	JBA	JBA	1:250@A1
DATE	DWG NO.		REV.
SEPT 2023	JBA 21/02/22		-

JAMES BLAKE

ASSOCIATES

Head Office: 34-42 Out Westgate, Bury St Edmunds, Suffolk, IP33 3PA Tel: (01284) 335797

LANDSCAPE ARCHITECTURE • ARBORICULTURE • ECOLOGY