



- FOOTPATH CONCRETE SETTPAVING, 140 x 220 x 60mm (80mm for vehicular areas) Type such as Alpha Antique Tumbled Black Paving from Bluet; Colour such as Silver Flare, or similar and approved.
- CONCRETE SETT EDGING 140mm wide, laid as double staggered string using blocks, 140mm x 140mm, 60mm depth for pedestrian areas, 80mm depth for vehicular areas laid Alpha Antique Tumbled Black from Bluet to match adjacent surfaces or other similar and approved. Laid over 150mm compacted subgrade, 1.2 m, haunched over 250 x 150mm C20/P 10 in situ concrete strip foundation.
- PORCELAIN SLAB PAVING, Type such as 'Eclispar' by 'Bent' 600 x 600 x 20mm, Colour such as 'Lunar', or similar and approved. To be dry laid in stack bond, over 20mm mortar, over 150mm depth of suitable granular fill, over firm sub-grade, all to fall and cross-slopes, minimum 1:75.
- ROADWAYS AND FOOTPATHS to be Blumex Macadam with 6mm gauge aggregate wearing course to be laid over 20mm gauge aggregate base course, all laid over base course of hardcore, all depths to Engineer's specification, laid over firm sub-grade and granolithic - Tensar 1000, all to fall and cross-slopes, minimum 1:75 and all to Highway's Authority approval.
- Hedge path with pressure treated timber edge, over compacted met & subgrade, over 1000 granolithic or similar and approved. Sawn pressure treated softwood gravel board 30mm x 150mm attached with galvanised nails to 50mm at 1.5m centres or closer as required at junctions or curves, 50mm x 600mm long softwood stakes for sharp corners, gravel board to be lashed with cuts down vertically along the back side.
- Natural compacted ground path with treated timber edge to mark route, for sharp corners timber to be lashed with vertical site in back of timber Sawn pressure treated softwood gravel board 30mm x 150mm attached with galvanised nails to 50mm at 1.5m centres or closer as required at junctions or curves, 50mm x 600mm long softwood stakes for sharp corners, gravel board to be lashed with cuts down vertically along the back side.
- PRECAST CONCRETE BLOCK EDGING, 50 x 150 x 94mm, flat topped and laid flush with paving. Edging to be bedded into C20/P 10 in situ concrete strip foundation 200 x 300mm, haunched.
- DROPPED KERB, 20mm upstand or flush to BS7263, to engineer's specification.
- Reinforced gravel parking bays and road ways, washed, rounded, buff coloured gravel, 20mm gauge, 40mm depth, finished level 15mm below adjacent surfaces. Gravel to be reinforced using 'Colwell' with pressure treated timber edge available from Greenweld 617 129 or similar and approved all laid over base course of hardcore, all depths to Engineer's specification, laid over firm sub-grade and granolithic - Tensar 1000.
- SECTION OF TIMBER BOARD WALK INCLUDING HAND RAILS

GENERAL NOTES
-ALL DIMENSIONS IN MILLIMETRES
-DO NOT SCALE OFF THIS DRAWING
-ALL DIMENSIONS TO BE CHECKED ON SITE
©JAMES BLAKE ASSOCIATES LTD 2023

REV	DATE	INITIALS	DETAILS

CLIENT Coral Homes		DWG. TITLE Proposed front Landscape	
SITE Horsfield Grove			
PURPOSE OF ISSUE Planning			
DRS BY DCG	CHECKED JBA	AUTH'D JBA	SCALE 1:250@A1
DATE SEPT 2023	DWG NO. JBA 21 027 16	REV. -	

JAMES BLAKE
ASSOCIATES

Head Office:
34-42 Out Westgate, Bury St Edmunds, Suffolk, IP33 3PA Tel: (01284) 335797
LANDSCAPE ARCHITECTURE • ARBORICULTURE • ECOLOGY