



KEY

- FOOTPATH CONCRETE SETTING: 140 x 210 x 60mm (80mm for vehicular areas) Type such as Alpha Anique Tumbled Black Paving from Bluet; Colour such as Silver Flare, or similar and approved.
- CONCRETE SETTING: 140mm wide, laid as double staggered string using blocks, 140mm x 140mm, 60mm depth for vehicular areas, 80mm depth for vehicular areas (see Alpha Anique Tumbled Black from Bluet to match adjacent surfaces or other similar and approved. Laid over 100mm cement mortar bed, 1:3 mix, haunched over 200 x 100mm C20/P10 rebar concrete prep foundation.
- SLAB PAVING: Type such as Heritage Paving by Marshall's 300 x 300 x 30mm, Colour such as Weathered York, or similar and approved. To be dry laid in stack bond over 20mm mortar over 100mm depth of suitable granular fill, over 100mm cement mortar bed, 1:3 mix, haunched over 200 x 100mm C20/P10 rebar concrete prep foundation.
- Reclaimed York Stone slabs, laid in random pattern available from Yorkton/Seale or similar and approved. To be dry laid in stack bond over 20mm mortar over 100mm depth of suitable granular fill, over 100mm cement mortar bed, 1:3 mix, haunched over 200 x 100mm C20/P10 rebar concrete prep foundation.
- ROADWAYS, FOOTPATHS AND SPORTS COURT: To be Bluetan Macadam with 60mm gauge aggregate wearing course to be laid over 20mm gauge aggregate base course, all laid over level course of formation, all depths to Engineer's specification, laid over firm sub-grade and geotextile - Tensar 1000, all to fall and crossfalls, minimum 1:70 and all to Highway's Authority approval.
- Hedge path with pressure treated timber edge, over compacted met & subgrade, over better 1000 geotextile or similar and approved. Saw pressure treated softwood gravel board 38mm x 100mm attached with galvanised nails to 50mm at 1.5m centres or closer as required at junctions or curves. 50mm x 600mm long softwood stakes for sharp corners, gravel board to be fixed with cuts seen vertically along the back side.
- natural compacted ground path with treated timber edge to mark route, for sharp corners refer to be fixed with vertical stakes to back of treated saw pressure treated softwood gravel board 38mm x 100mm attached with galvanised nails to 50mm at 1.5m centres or closer as required at junctions or curves. 50mm x 600mm long softwood stakes for sharp corners, gravel board to be fixed with cuts seen vertically along the back side.
- PRECAST CONCRETE BLOCK EDGING: 50 x 150 x 94mm, flat topped and laid flush with paving. Edging to be bedded into C20/P10 rebar concrete prep foundation 500 x 300mm, haunched.
- DROPPED KERBS, 20mm upstand or flush TO BS7263, to engineer's specification.
- Reinforced gravel parking bays and road ways, washed, rounded, buff coloured gravel, 20mm gauge, 40mm depth, finished level 15mm below adjacent surface. Gravel to be reinforced using Schied, with pressure treated timber edge available from Greenworld EIT 120 or similar and approved as laid over level course of formation, all depths to Engineer's specification, laid over firm sub-grade and geotextile - Tensar 1000.
- SECTION OF TIMBER BOARD WALK INCLUDING HAND RAILS

GENERAL NOTES
- ALL DIMENSIONS IN MILLIMETRES
- DO NOT SCALE OFF THIS DRAWING
- ALL DIMENSIONS TO BE CHECKED ON SITE
©JAMES BLAKE ASSOCIATES LTD 2025

REV	DATE	BY	CHKD	DETAILS
1	24.08.20	DCG	DCG	UPDATED TO COMMENTS & NEW LAYOUT
2	27.08.20	DCG	DCG	UPDATED TO COMMENTS

CLIENT	Corner Homes		DWG. TITLE	Proposed Hard Landscape	
SITE	Harefield Grove				
PURPOSE OF ISSUE	Planning				

DRG BY	CHECKED	AUTHD	SCALE	DATE	DWG NO.	REV.
DCG	JBA	JBA	1:250@A1	SEPT 2023	JBA 21/02/23	8

JAMES BLAKE

ASSOCIATES

Head Office: 34-42 Out Westgate, Bury St Edmunds, Suffolk, IP33 3PA Tel: (01284) 335797

LANDSCAPE ARCHITECTURE • ARBORICULTURE • ECOLOGY