

PLANNING CONDITION 12

Issued 02/10/24

INDEX

SECTION 1: Green roofs and Terraces

SECTION 2: Living Wall South Elevation

SECTION 3: Living Wall East Elevation

SECTION 4: Fire Strategy Extract for Green wall
ratings

SECTION 1: Green roofs and Terraces

1.1 General Arrangement Plans


1.2 Architects details

1.3 Subcontractor roof specifications

1.4 Drainage plans



1.2 Architects details



1 Brown Roof System 1 : 10

2 Paving Slabs Roof - Warm 1 : 10


3 Bitumen Roof - Warm 1 : 10

O Bitumen Roof - Non insulated 1 : 10






6 Terrace Edge Detail - Level 0

3 Terrace Curtain Walling Upstand - Level 03
1 : 10



4 Terrace Curtain Wall Upstand - Level 01

Typical - Gantry to Roof 01 Upstand
1 : 10



General Notes:

- Do not scale from this drawing. All dimensions quoted are in millimetres unless otherwise stated. Values of measurements on site.
- Any discrepancies between the drawing and other documents should be brought to the attention of the responsible contractor.
- This drawing is not an installation drawing. It is the Contractors responsibility to make final site measurements and to install the system.
- The contents of this drawing shall be read in conjunction with the current revisions of the relevant sections of the specifications.

Scale: 2000 0 2000 4000 6000 8000
N
2000 0 2000 4000 6000 8000
SCALE: 1:200

Key Plan:

SS B2 B1 GH OF

Scale: 2000 0 2000 4000 6000 8000
N
2000 0 2000 4000 6000 8000
SCALE: 1:200

01 Level 01
35400

01_Roof Level 02
64030

01 47500 - Typ Staircase Parapet
1 : 10

03 Recessed Curtain Wall DEtil
1 : 10

02 47500 - Typical AOV Upstand detail
1 : 5

04 Typical RWO to Green Roof
1 : 5

Project Title: London 4

Drawing Title: Building 1

Project Status: STAGE 4A ISSUE

Discipline: ARCHITECTURE

Project Number: 0493

Scale @ A0: 1:10

Revision: P03.01

Drawing Number: DCS20109-NWA-DC-ZZ-ZZ-DR-A-47502

TECHNICAL DATA SUBMISSION

1.3 Subcontractor Roof specifications

BUFR Cold Roof System

CONTENTS:

1. Specification Summary
2. Site Locations of Buildings
3. Product Data Sheets

- Primers
- Waterproofing
- Lightning Conductor Clips
- Walkway Membrane -Where Required (Red)
- Angle Fillet

4. Certifications


- Waterproofing

5. EPD

- Waterproofing

SPECIFICATION SUMMARY

BUFR Cold Roof System



The above illustrates the primary roof build-up for this project.

Product / Component	Unit	Thickness	Length	Width	Approx Weight

Cold roof Area



TECHNICAL DATA SUBMISSION


BUFR Warm Roof System

CONTENTS:

- 1. Specification Summary**
- 2. Site Locations of Buildings**
- 3. Product Data Sheets**
 - Primers
 - Vapour Control Layer
 - Insulation
 - Aqua Panel
 - Waterproofing
 - Lightning Conductor Clips
 - Walkway Membrane (Red)
 - Angle Fillet
 - Fixings
- 4. Calculations**
 - CTF Scheme
 - Wind up-lift
 - u Value
- 5. Certifications**
 - Waterproofing
 - Insulation
- 6. EPD**
 - Waterproofing
 - Insulation

SPECIFICATION SUMMARY


BUFR Warm Roof System



The above illustrates the primary roof build-up for this project.

Product / Component	Unit	Thickness	Length	Width	Approx Weight

Main roof area



TECHNICAL DATA SUBMISSION

BUFR Warm Roof System

CONTENTS:

1. Specification Summary

2. Site Locations of Buildings

3. Product Data Sheets

- Primers
- Vapour Control Layer
- Insulation
- Aqua Panel
- Waterproofing
- Outlets
- Lightning Conductor Clips
- Walkway Membrane -Red Where Required
- Paving
- Paving Supports
- Protection Fleece
- Angle Fillet
- Fixings

4. Calculations

- CTF Scheme
- U-Value
- Wind Up-Lift

5. Certifications


- Waterproofing
- Insulation

6. EPD

- Waterproofing
- Insulation

SPECIFICATION SUMMARY

BUFR Warm Roof System



The above illustrates the primary roof build-up for this project.

Product / Component	Unit	Thickness	Length	Width	Approx Weight
Aqua Panel					
Impertene Bitumen Primer	1	N/A	N/A	N/A	20L TINS

Paved Roof Area



TECHNICAL DATA SUBMISSION


BUFR - Warm Roof System

CONTENTS:

- 1. Specification Summary**
- 2. Site Locations of Buildings**
- 3. Product Data Sheets**
 - Primers
 - Vapour Control Layer
 - Insulation
 - Waterproofing
 - Outlets
 - Lightning Conductor Clips
 - Angle Fillets
- 4. Calculations**
 - CTF Scheme
 - U-Value
 - Wind Load
- 5. Certifications**
 - Waterproofing
 - Insulation

SPECIFICATION SUMMARY


BUFR - Warm Roof System



The above illustrates the primary roof build-up for this project.

Product / Component	Unit	Thickness	Length	Width	Approx Weight

Green Roof Area



Technical Data Sheet

Impertene Bitumen Primer

Limitations:

- Do not use in temperatures less than +5°C.
- It is the user's responsibility to ensure suitability for use. Safety Data Sheet available on request.
- Read the label carefully for essential health and safety information prior to use.

Technical Specification:

Composition	Based on organic solvent bitumens.
Product type	Single-component, ready to use. The product must not be diluted
Appearance	Black liquid.
Specific weight	g/dm ³ 950 (±50)
Viscosity Ford 4 cup at 20°C	15 ÷ 25 sec

Further Information:

In the event of further queries or problems concerning the use of this product, please contact MOY Technical Services.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

Technical Data Sheet


Paraflex ARD/S

Product Description / Use:

Paraflex ARD/S is a modified bitumen SBS polymer waterproofing membrane intended for all waterproofing applications including; Flat Roofs, Terraces, Podiums, Car Parks and Bridge Decks, Tunnels, Foundations and Underground Structures.

The Paraflex range of waterproofing membranes, is FM approved and may be used in new build and refurbishment applications and is suitable for application in low temperature conditions. Paraflex remains flexible at low temperatures and exhibits high resistance to thermal stress.

Paraflex ARD/S is manufactured with a mineral slate or mineral stone granule coating to the upper surface of the membrane in various colours, offering UV protection and slip resistance. The membrane compound is reinforced with a synthetic non-woven continuous filament polyester fabric, enabling plasticity, elastic behaviour and superior resistance to mechanical damage. The lower face is coated with Termotene® fusible film which aids unrolling and facilitates torch bonding to various substrates.



The Paraflex SBS bitumen compound's special formulation ensures high mechanical performance, cold flexibility at temperatures down to -25°C and excellent fatigue strength.

Paraflex membranes contain no asbestos, tar or other dangerous substances.

Certification:



NSAI



System Fire Testing:

Classification Standard BS EN 13501-5: 2016
Test Standard: CEN/TS 1187:2012

warringtonfire

Determination of external fire performance is a system test which will be influenced by the components within the roofing system.

Whilst Paraflex ARD/S can be included in compliant B_{ROOF}(t4) systems, always check with MOY Technical Services for the very latest information on fire testing carried out.



Technical Data Sheet

Paraflex ARD/S

Technical Specification:

Specifications	EN Standards	Unit of Measure	Tolerances (1)	Paraflex ARD/S (2,10)
Roll dimensions	1848-1	m	≥	8 x 1 (-1%)
Thickness	1849-1	mm	±5%	-
Mass per unit area	1849-1	kg/m ²	±10%	4.5
Watertightness	1928-B	kPa	≥	60
Cold flexibility	1109	°C	≤	-25
Flow resistance at elevated temperature	1110	°C	≥	+100
L/T tensile strength	12311-1	N/5cm	±20%	800/600
L/T tensile elongation	12311-1	%	±15 (3)	50/50
L/T dimensional stability	1107-1	%	2	0.3
Static puncture	12730	kg	≥	NPD (4)
Dynamic puncture	12691-B	mm	≥	1250
L/T tear resistance	12310-1	N	±30%	160/180
Joint peel resistance	12316-1	N/5cm	±20 N	NPD (4)
Joint cut resistance	12317-1	N/5cm	±20%	NPD (4)
Durability after ageing:				
• Cold flexibility	1296-1109	°C	+15°C	-10
• Flow resistance at elevated temperature	1296-1110	°C	-10°C	+100
• UV Ageing	1297	-	-	NPD (4)
• Watertightness	1296-1928	kPa	≥	60
• Chemical resistance	-	-	-	NPD (4)
• L/T tensile strength	12311-1	N/5cm	±20%	700/500
• L/T tensile elongation	12311-1	%	±15 (3)	45/45
Steam permeability	1931	μ	≥	20,000
Root resistance	13948		-	NPD (4)
External fire behaviour	13501-5	EC (6)	-	NPD (9)
Fire reaction	13501-1	EC (6)	-	F
Solar Reflectance Index (SRI)	ASTM Standard E1980	%	-	82.1 (8)

Notes:

- (1) In compliance with the applicable AISPEC/SITEB-MBP Guidelines.
- (2) Upper finish in slate flakes standard colour Natural grey. Other colours may be available upon request Red, Green, White Reflecta.
- (3) ±2 for Glass Mat reinforcements.
- (4) Characteristic not determined because it is not relevant for use.
- (5) RFG: Failure away from joint. Or ≥ 500.
- (6) Euroclass.
- (7) Internal report
- (8) Only Reflecta White version, in heavy wind conditions
- (9) Determination of external fire performance is a system test which can be influenced by system components, thus performance for each individual product cannot be given.
- (10) Variation in coating between mineral slate flake and mineral stone granules may occur between batches.

Colour:

Paraflex ARD/S is available in a range of colours. Standard colours are Anthracite and Slate Grey. Other colours are available upon request; Red, Green, Bianco Reflecta. Some shade variation in colours may occur between rolls.

Technical Data Sheet Paraflex ARD/S

Delivery form:

Rolls.

Storage:

Rolls must be stored in their original package, in vertical position and under cool and dry conditions between temperatures of +5 °C and +35 °C. They must be protected from direct sunlight, rain, snow and ice.

Shelf life:

They can be stored for up to 24 months in cool, dry conditions.

Safety:

Safety precautions to be taken when using this product is given in the Safety Data Sheet.

Disposal:

Information for this product is given in the Safety Data Sheet.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

Technical Data Sheet

Paraflex NT3

Product Description / Use:


Paraflex NT3 is a modified bitumen SBS polymer waterproofing membrane for use as a base layer or air and vapour control layer, under Paraflex waterproofing systems including; Flat Roofs, Green Roofs and Terraces, Podiums, Car Parks and Bridge Decks, Tunnels, Foundations and Underground Structures.

The Paraflex range of waterproofing membranes, is FM approved and may be used in new build and refurbishment applications and is suitable for application in low temperature conditions. Paraflex remains flexible at low temperatures and exhibits high resistance to thermal stress.

The membrane compound is reinforced with a synthetic non-woven continuous filament polyester fabric, enabling plasticity, elastic behaviour and superior resistance to mechanical damage. The lower face is coated with Termotene® fusible film which aids unrolling and facilitates torch bonding to various substrates.

The Paraflex NT3 SBS bitumen compound's special formulation ensures high mechanical performance, cold flexibility at temperatures down to -25°C and excellent fatigue strength.

Paraflex membranes contain no asbestos, tar or other dangerous substances.



Whilst it's primarily used as a base layer, it can also be used as an air and vapour control layer (AVCL) within a built-up warm roof, subject to the building use below. Buildings with high humidity conditions will require a foil faced vapour barrier (Sticker Helast VB 500 or Elotene DSN), or one with a foil lining within the membrane, like Vapobar 1 torch applied or Sticker Sanded AL (Foilcore), self-adhesive AVCL.

Certification:



NSAI



System Fire Testing:

Classification Standard BS EN 13501-5: 2016
Test Standard: CEN/TS 1187:2012

warringtonfire

Determination of external fire performance is a system test which will be influenced by the components within the roofing system.

Whilst Paraflex NT3 can be included in compliant B_{ROOF} (t4) systems, always check with MOY Technical Services for the very latest information on fire testing carried out.



Technical Data Sheet

Paraflex NT3

Technical Specification:

Specifications	EN Standards	Unit of Measure	Tolerances ⁽¹⁾	Paraflex NT3
Roll dimensions	1848-1	m	≥	10 x 1 (-1%)
Thickness	1849-1	mm	±5%	3
Mass per unit area	1849-1	kg/m ²	±10%	3.5
Watertightness	1928-B	kPa	≥	60
Cold flexibility	1109	°C	≤	-25
Flow resistance at elevated temperature	1110	°C	≥	+100
L/T tensile strength	12311-1	N/5cm	±20%	800/600
L/T tensile elongation	12311-1	%	±15 ⁽²⁾	50/50
L/T dimensional stability	1107-1	%	2	0.3
Static puncture	12730	kg	≥	NPD ⁽³⁾
Dynamic puncture	12691-B	mm	≥	NPD ⁽³⁾
L/T tear resistance	12310-1	N	±30%	160/180
Joint peel resistance	12316-1	N/5cm	±20 N	NPD ⁽³⁾
Joint cut resistance	12317-1	N/5cm	±20%	NPD ⁽³⁾
Durability after ageing:				
• Cold flexibility	1296-1109	°C	+15°C	-10
• Flow resistance at elevated temperature	1296-1110	°C	-10°C	+100
• UV Ageing	1297	-	-	NPD ⁽³⁾
• Watertightness	1296-1928	kPa	≥	60
• Chemical resistance	-	-	-	NPD ⁽³⁾
• L/T tensile strength	12311-1	N/5cm	±20%	700/500
• L/T tensile elongation	12311-1	%	±15 ⁽³⁾	45/45
Moisture resistance factor	1931	μ	-	83,700
Vapour resistance	1931	MN.s/g	-	1,175
Water vapour diffusion - equivalent air layer thickness S _d	1931	m	-	235
Root resistance	13948		-	NPD ⁽³⁾
External fire behaviour	13501-5	EC ⁽⁴⁾	-	NPD ⁽⁵⁾
Fire reaction	13501-1	EC ⁽⁴⁾	-	F

Notes:

- (1) In compliance with the applicable AISPEC/SITEB-MBP Guidelines.
- (2) ±2 for Glass Mat reinforcements.
- (3) Characteristic not determined because it is not relevant for use.
- (4) Euroclass.
- (5) Determination of external fire performance is a system test which can be influenced by system components, thus performance for each individual product cannot be given.

Delivery form:

Rolls.

Storage:

Rolls must be stored in their original package, in vertical position and under cool and dry conditions between temperatures of +5 °C and +35 °C. They must be protected from direct sunlight, rain, snow and ice.

Technical Data Sheet

Paraflex NT3

Shelf life:

They can be stored for up to 24 months in cool, dry conditions.

Safety:

Safety precautions to be taken when using this product are given in the Safety Data Sheet.

Disposal:

Information for this product is given in the Safety Data Sheet.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

Technical Data Sheet

HARDROCK® Multi-Fix Angle Fillets

Product Description / Use:

HARDROCK® Multi-Fix Angle Fillets have been designed to fully support the waterproof membrane at 90° abutments, providing a smooth transition between the horizontal and vertical interface.

The product is manufactured with an integral mineral-coated glass fibre fleece, which secures a strong bond between membrane and insulation for both hot and cold applied bituminous membrane systems.

Benefits:

- Can help to prolong the life of the waterproof membrane
- Excellent heat resistance; ideal for torch-applied bituminous systems
- Cost effective and easy to install
- Single-size solution compatible with bituminous membranes and GRP systems



Certification:



Reaction to Fire:

HARDROCK® Multi-Fix (DD) has a Euroclass rating of A2-s1, d0. (HARDROCK® Multi-Fix (DD) Underlay Slab has a Euroclass rating of A1).

System Fire Testing:

Test Standard: CEN/TS 1187: 2012
Classification Standard: BS EN 13501-5: 2016*



* Determination of external fire performance is a system test which will be influenced by the components within the roofing system.

Whilst HARDROCK® Multi-Fix (DD) can be included in compliant B_{ROOF} systems, always check with MOY Technical Services for the very latest information on fire testing carried out.

Applications:

For use with bituminous or GRP waterproofing systems in conjunction with HARDROCK® Multi-Fix flat roof insulation boards.

Technical Information:

Length (mm)	1200
Width (mm)	75
Thickness (mm)	30

Handling:

When handling Angle Fillets they should be properly supported along their length.



Technical Data Sheet

HARDROCK® Multi-Fix Angle Fillets

Installation:

HARDROCK® Multi-Fix Angle Fillets must be installed in dry conditions. With the white glass fleece facing outward, place the Angle Fillet along the 90° abutment at the interface between the horizontal and vertical surfaces and fix the Angle Fillet to the horizontal surface using a compatible adhesive. Angle Fillets can be cut easily using a fine-tooth saw.

Storage:

Angle Fillets should be stored under cover. Angle Fillets that have become wet should be allowed to fully dry out naturally before use, at which point they should regain their original properties.

Health & Safety:

The safety of stone wool is confirmed by current UK and Republic of Ireland health & safety regulations and EU directive 97/69/EC:ROCKWOOL fibres are not classified as a possible human carcinogen.

A Material Safety Data Sheet is available and can be downloaded to assist in the preparation of risk assessments, as required by the Control of Substances Hazardous to Health Regulations (COSHH).

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

Technical Data Sheet

HARDROCK® Multi-Fix (DD)

Product Description / Use:

HARDROCK® Multi-Fix (DD) is a high density, non-combustible thermal insulation board which has also been tested for acoustic applications and fire resistance. It has been proven to improve the ability of lightweight flat roof systems to control both noise ingress and egress through the building envelope.

HARDROCK® Multi-Fix (DD) is a stone wool insulation board faced with a mineral-coated white fleece, compatible with a wide range of MOY adhered and mechanically fixed waterproofing systems - including bitumen, single-ply and liquid membranes, as well as green roof systems.

Benefits:

- Compatible with most MOY roofing systems
- The product presents no smoke hazard, and will not contribute to fire growth in any stages of a fire (including the fully developed stage of a fire)
- The product is deemed to be non-combustible in accordance with UK building regulations
- LPCB approved to highest classification, LPS1181: Part 1 EXT - A rated constructions
- Excellent acoustic reduction, absorption and impact (rain noise) performance
- Solutions to meet all BB93 (Education) and HTM08- 01 (Healthcare) acoustic requirements
- Acoustic solutions provide opportunity for additional BREEAM points
- Dimensionally stable
- Consistent thermal performance with no blowing agents. Zero ODP and GWP
- HARDROCK® Multi-Fix (DD) can be recycled and reprocessed, reducing landfill and costs
- Also available as a tapered insulation system, to create the falls in the roof (HARDROCK® Multi-Fix (DD) Tapered)



Certification:



For FM Approval must be used as part of an FM Approved Assembly.

Reaction to Fire:

HARDROCK® Multi-Fix (DD) has a Euroclass rating of A2-s1, d0. (HARDROCK® Multi-Fix (DD) Underlay Slab has a Euroclass rating of A1).

System Fire Testing:

Test Standard: CEN/TS 1187: 2012
Classification Standard: BS EN 13501-5: 2016*

[warringtonfire](http://warringtonfire.com)

* Determination of external fire performance is a system test which will be influenced by the components within the roofing system.

Whilst HARDROCK® Multi-Fix (DD) can be included in compliant B_{ROOF} (t4) systems, always check with MOY Technical Services for the very latest information on fire testing carried out.



Technical Data Sheet

HARDROCK® Multi-Fix (DD)

Thermal Conductivity:

The thermal conductivity (or lambda value) shows how well a material can conduct heat. The lower the thermal conductivity, the better the insulator.

HARDROCK® Multi-Fix (DD) has a thermal conductivity of 0.039 W/mK.

Board Sizes:

- 1000 x 1200 mm

Thicknesses:

- HARDROCK® Multi-Fix (DD); 60 mm, 85 mm, 105 mm, 115 mm, 150 mm, 185 mm
- HARDROCK® Underlay Slab for multi-layer systems (DD); 150 mm.

Consult MOY Materials Ltd as thicknesses may be subject to availability and minimum order volumes

Weight:

HARDROCK® Multi-Fix (DD) has an approximate weight of 3.5 kg/m² at a thickness of 100mm.

Compressive strength:

Compressive strength is a material's ability to maintain its structural integrity when compressed. The higher the compressive strength the better the material is at maintaining its structural integrity.

The compressive strength of HARDROCK® Multi-Fix (DD) typically exceeds 70 kPa at 10% compression.

Technical Specification:

Detailed product characteristics for this product are given in Declaration of Performance [DoP].

Sustainability Information:

Relying on entrapped air for its thermal properties, HARDROCK® insulation does not contain gases that have ozone depleting potential (ODP) or global warming potential (GWP) and as such complies with the relatively modest threshold of GWP<5.

HARDROCK® Multi-Fix (DD) can be recycled and reprocessed reducing landfill and costs.

Installation and handling:

For information on installation and handling please refer to specific product guidance and the project specification.

Storage:

Insulation products must be kept dry and protected from wet weather during storage and installation.

Disposal:

In accordance with REACH health and environment regulations, there are no hazardous classifications associated with HARDROCK® mineral wool in respect to physical, health and environmental considerations, however information for this product are given in the Safety Data Sheet.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

Technical Data Sheet

AQUAPANEL® Cement Board Rooftop

Product Description / Use:

AQUAPANEL® Cement Board Rooftop is a lightweight cement board made of aggregated Portland cement with coated glass fibre mesh embedded in the front and back surfaces.

It is moisture and mold resistant, non-combustible and robust, adding structural strength and durability to the entire roofing system. It meets the requirements of category D, class 2 in compliance with EN 12467.

12.5mm thick and available in various board sizes.

The ends are cut square and edges are reinforced for extra strength (the EasyEdge®). The panel provides a solid base that withstands extreme weather conditions.



Characteristics:

- Recommended for accessible roofs
- Strong, robust, impact-resistant and durable
- High compressive strength
- Weather and 100% water-resistant
- Non-combustible (Class A1)
- Can be cut to shape using "score and snap" technique
- Simple and easy to install

Certification:



BBA-UKTA-0836-22/6407.

Can be used as part of an FM Approved system.

System Fire Testing:

Test Standard: CEN/TS 1187: 2012

Classification Standard: BS EN 13501-5: 2016 *

* Determination of external fire performance is a system test which will be influenced by the components within the roofing system.

Whilst AQUAPANEL® Cement Board Rooftop can be included in compliant B_{ROOF} systems, always check with MOY Technical Services for the very latest information on fire testing carried out.



Technical Data Sheet

AQUAPANEL® Cement Board Rooftop

Technical Properties:

Thickness (mm)	12.5	
Length (mm)	1200/2400/2250	2400
Width (mm)	900	1200
Weight (kg/m ²)	approx. 16.5	
Dry bulk density (kg/m ³) according to EN 12467	1150	
Bending strength (MPa) according to EN 12467	≥ 7	
Thermal conductivity (W/mK) according to EN ISO 10456	0.35	
Thermal expansion (10 ⁻⁶ K ⁻¹)	7	
Water vapour diffusion coefficient μ (-) according to EN ISO 12572	66	
Length variation 65% - 85% humidity (mm/m) according to EN 318	0.23	
Mold resistance	No growth (IBR certified)	
pH-Value	12	
Building material class according to EN 13501	A1 non-combustible	

Additional detailed product characteristics for this product are given in Declaration of Performance (DoP).

Application:

AQUAPANEL® Cement Board Rooftop is used in commercial low slope roofing systems. It enhances roof system performance in several ways and functions:

1. As a cover board installed between the insulation and the waterproofing layer.
 - protects roof insulation underneath
 - reduces stress on the membrane
 - Adds structural strength to the entire roof system
 - provides a robust basis for accessible and ballasted roofs
2. As a substrate board installed directly onto the steel deck acting as:
 - substrate for the vapor barrier
 - basis for the roofing constructors to work on

Installation and handling:

AQUAPANEL® Cement Board Rooftop is attached to the surrounding layers inside the roof system. It can be mechanically fastened or adhered with appropriate MOY adhesive. During the planning phase the wind loads must be considered.

AQUAPANEL® Cement Board Rooftop is suited for a variety of rigid roof insulation and waterproofing membranes like single-ply, modified bitumen or liquid applied membranes. Consult the project specific specification or MOY Technical Services for details.

Storage:

Always carry boards upright using a board trolley or on a pallet using a forklift truck. When setting the boards down, make sure that corners and edges are not damaged.

The supporting surface must be able to carry the weight of the boards. A pallet of AQUAPANEL® Cement Board Rooftop 12.5mm applies a floor loading from about 900 to 1450 kg (as delivered).

AQUAPANEL® Cement Board Rooftop must be protected from the effects of moisture and weather before installation. Boards that have become damp must be dried on both sides before use.

Technical Data Sheet

AQUAPANEL® Cement Board Rooftop

Allow time for the boards to acclimatise to the ambient temperature and moisture conditions before installation. The material, ambient air and background temperature must not be below +5°C.

Disposal:

Information for this product is given in the Safety Data Sheet.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

Standard Pimple 600 x 600 x 50

Date Created: 24/11/22



Standard Pimple -
Natural

Available in a range of colour and size options, Marshalls' Standard Pimple Paving provides a durable, functional and flexible paving solution that excels in urban environments.

With innovative fibre technology and raised pimples on its surface, Marshalls' Standard Pimple Paving offers maximum skid and slip resistance, and goes beyond industry standards for hardwearing stone.

Available in a range of thicknesses catering for different loading requirements, Standard Pimple Paving is an ideal choice for areas with high pedestrian traffic - such as train stations and urban park spaces. Marshalls' Standard Pimple Paving complies with BS EN 1339:2003.

DESCRIPTION

Appearance	Solid unit with pimple surface
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003
Type	Solid unit with pimple surface
UKCA Marking/DOP	https://www.marshalls.co.uk/declarations
NBS Specification	Q25 315

Standard Pimple 600 x 600 x 50

Date Created: 24/11/22

PHYSICAL PROPERTIES

Work Dimensions (mm)	598 x 598 x 50
Nominal Dimensions (mm)	600 x 600 x 50
Tolerances on Work Dimensions (mm)	Length ± 2 mm, width ± 2 mm, thickness ± 3 mm
Abrasion Resistance (mm)	≤ 23 mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw)	≤ 1.0 kg/m ² as a mean with no individual value > 1.5 kg/m ²
Material Density	2300 kg/m ³ (typically)
Slip/Skid Resistance (polished)	Mean polished skid resistance value (PSRV) : > 45
Slip/Skid Resistance (unpolished)	Mean unpolished skid resistance value (USRV) : > 45 .
Thermal Conductivity (K value)	Design data as defined to BS EN 13369 : 2013
Transverse/Flexural Split/Breaking	Characteristic bending strength of 4.0 MPa with no individual result less than 3.2 MPa

SPECIFICATION

Approx unit weight (kg)	43
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy. See commission decision 2000/553/ECU
Reaction to fire	Class A1, See commission decision 2000/605/EC
Materials Control	UKCA Marked to BS EN 1339 : 2003 Concrete Flags

SUSTAINABILITY

Breeam	These units can achieve an "A" rated system when used in conjunction with the correct sub-base components
Carbon Footprint	13 kg CO ₂

APPLICATION

Suitability	Laid in accordance with BS7533-4 : 2006
Loading Classification	Category 6 - 0.5msa Adopted highways and commercial/industrial developments used by a moderate number of commercial vehicles. Pedestrian areas subjected to regular overrun of commercial vehicles. Industrial premises. Petrol station forecourts.

SITE WORKS

Coverage (m ²)	2.8
----------------------------	-----

SUPPLY

Units Per Pack	20
Av. pack weight (kg)	860

Packaging All packs are suitable for crane off-load

FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details. Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233

RPA

Self-levelling Adjustable Paving Pedestal

Overview

The RPA self-levelling adjustable paving pedestal supports all types of calibrated paving up to an impressive height of 1000mm.

- 'Ball and socket' floating head allows slope correction of up to 10.5% (6°)
- Spacer tabs provide consistent spacing between slabs. 'Snap off' design allows for easy removal.
- Adjustable thread allows millimetre perfect adjustment
- Height extension collar raises the height by 100mm
- Holes in base allow drainage and fixing to substrates
- Base can be cut down to allow for placement against wall abutment



Performance

Material	Polypropylene (recyclable)
Biological/chemical	Resistant to moulds, algae, alkali, bitumen
Compression	2100kg (certified compression data available on request)
Base diameter	210mm / 220mm
Head diameter	130mm
Spacer tab thickness	2mm / 4mm (standard) / 6mm / 8mm / 10mm
Working temperature	-40°C to 120°C
Reaction to fire	BRoof(t4) in accordance with EN 13505:2018 when used as part of the complete TerraSmart Pedestal System

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.

Compression tests

Code	Height of the specimen (mm)	Maximum load (N)	Maximum load (Kg)	Deflection at max load (mm)
RPA-1	48	21,485	2,190	10.2
RPA-2	60	26,360	2,687	10.7
RPA-3	90	28,797	2,935	12.0
RPA-4	135	27,111	2,764	11.2
RPA-5	180	29,817	3,039	12.7
RPA-6	250	29,464	3,003	14.8
RPA-7	350	29,049	2,961	15.9
RPA-8	450	28,440	2,899	18.2
RPA-9	550	28,856	2,942	22.3
RPA-10	650	28,226	2,878	24.0
RPA-11	750	28,757	2,931	24.6
RPA-12	850	26,777	2,730	26.3
RPA-13	950	26,791	2,731	26.9

Sizes


Code	Adjustable height range
RPA-1	40-56mm
RPA-2	50-70mm
RPA-3	70-110mm
RPA-4	110-160mm
RPA-5	150-210mm
RPA-6	200-300mm
RPA-7	300-400mm
RPA-8	400-500mm
RPA-9	500-600mm
RPA-10	600-700mm
RPA-11	700-800mm
RPA-12	800-900mm
RPA-13	900-1000mm

Accessories



Edge spring clip


The edge spring clip fits on top of paving supports around the periphery of paved areas to ensure uniform spacing against wall abutments, helping ensure rapid drainage. By tensioning the tile bed, it counteracts creepage and movement.

**Head shock pads**

Head shock-absorbent gaskets fit on top of the paving supports, cushioning tiles and removing the possibility for grit to cause grinding between tile and pedestal head.

**Base shock pads**

Base shock-absorbent membrane pads can be installed under the pedestal/support base to enhance acoustic properties, or to provide additional protection to the waterproof system.

Compatible Systems**Got questions?****Speak to one of our expert advisors**

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.

Technical Data Sheet

VLU-300 Protection Fleece

Product Description / Use:

VLU-300 Protection Fleece is a rotproof multicoloured mechanical protection layer made of 100% synthetic fibres and thermally treated on both sides. A loose laid layer, which can be used in some applications as a separation/cushion layer, or for the protection of the waterproofing layers, such as reinforced bitumen membrane, single ply or cold applied liquid waterproofing systems.

Installation and Handling:

Loose laid with a minimum 100mm overlap.

For information on installation and handling, refer to specific product guidance and the project specification.



Technical Specification:

Characteristics	Dim.	VLU-300
Surface weight	g/m ²	300
Thickness	mm	1.8
Tensile strength MD	kN/m	2.7
Tensile strength CMD	kN/m	3.7
Elongation MD	%	75-90
Elongation CMD	%	65-85
Static puncture test (CBR)	kN	1
Characteristic opening size O90	mm	0.134
Water permeability	mm/s	95
Robustness class	GRK	2
Method of production		Heat treated on both sides

Specifications are subject to change without notice.

Delivery Form:

100 m²/roll; packaging weight: 30 kg/roll.

Storage:

Ideally, store inside a building. If, however, outside storage cannot be avoided, then rolls should be stacked clear of the ground and covered with an opaque polythene sheet or weatherproof tarpaulin.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.



Notes(s): Contractor To Confirm Sizes And Heights On Site Prior

To Delivery Of The Proposed Tapered Scheme

Scheme Designed On The Assumption Of A Flat Level Deck.

U Value Calculation(s) Based On A

200mm Concrete

Deck Construction.

Drawn & Designed From The Following Source(s):

DCS20109-NWA-DC-B1-04-DR-A-20240

DCS20109-NWA-DC-B1-06-DR-A-20260 (1)


DCS20109-NWA-DC-B1-01-DR-A-20210

TAPERED BOARD LEGEND

Schedule	Thickness	Fall
Type: Rockwool Multi-fix		
A	40 - 60	1:60
B	60 - 80	1:60
C	80 - 100	1:60
D	100 - 120	1:60
E	120 - 140	1:60
F	140 - 160	1:60
G	160 - 180	1:60
H	180 - 200	1:60
I	200 - 220	1:60
J	220 - 240	1:60
K	240 - 260	1:60
L	260 - 280	1:60
M	280 - 300	1:60
N	300 - 320	1:60
O	320 - 340	1:60
2	140 - 155	1:80
3	155 - 170	1:80
4	170 - 185	1:80
5	185 - 200	1:80
6	200 - 215	1:80
7	215 - 230	1:80
8	230 - 245	1:80
9	245 - 260	1:80
10	260 - 275	1:80
11	275 - 290	1:80
12	290 - 305	1:80
13	305 - 320	1:80
14	320 - 335	1:80
15	335 - 350	1:80
16	350 - 365	1:80
17	365 - 380	1:80
18	380 - 395	1:80
19	395 - 410	1:80
Flat 30	30	
Flat 120	120	
Flat 300	300	


LVL02 - 111m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL04 - 3298m²
0.24 W/m²K U Value
(Effective)

Flat 30mm Gutter

Roof Dimensions / Roof Extents TBC
Roof Penetrations TBC
Outlet Locations / Max. Height Restriction TBC

LVL01 - 299m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter




LVL01 - 116m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL01 - 29m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL01 - 109m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 31m²
0.17 W/m²K U Value
(Effective) (Targeting 0.18 W/m²K)

Flat 300mm Infill



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

Flat 120mm Gutter



LVL02 - 17m²
0.18 W/m²K U Value
(Effective)

TECHNICAL DATA SUBMISSION


Sky Garden Living Roof Systems



CONTENTS:

- 1. Specification Summary**
- 2. Site Locations of Buildings**
- 3. Product Data Sheets**
 - a. Extensive Mix Substrate**
 - b. Sedum Blanket**
 - c. Drainage Board & W-Fleece**
 - d. Protection Fleece**
 - e. Aluminium Retention Bar**
 - f. Riverstone Border & Ballast**
- 4. Calculations**
 - a. provided within Tech sub showing system
DCS20109-MRC-DC-ZZ-ZZ-TS-X-27006**

SPECIFICATION SUMMARY




The above is for illustration purposes only.

Roof System Element	Unit	Thickness	Length	Width	Weight (kg/m ²)

SYSTEM DIAGRAM


SKY GARDEN SEDUM BLANKET SYSTEM



 <p>Head Office Unit 3, Miller Court Tewkesbury, Gloucestershire, GL20 8DN 01242 620905 Email - enquiries@sky-garden.co.uk</p>	<p>Q37 Details</p> <p>Protection Fleece</p> <ul style="list-style-type: none"> - 3.5mm non-woven geotextile <p>Drainage Layer</p> <ul style="list-style-type: none"> - 20mm Drainage reservoir board <p>Filter Fleece</p> <ul style="list-style-type: none"> - 2mm (nominal) non-woven geotextile <p>Separation Detail</p> <ul style="list-style-type: none"> - 1.5mm Aluminium profile 100mm (H) x 80mm (W) 	<p>System Name Sedum Blanket System</p>
		<p>Drawn By: DH</p> <p>Scale: Do not scale</p>

Indicative Build-up Height - 103.5mm
Indicative Dry Weight - 67kg (60mm Substrate Depth)
Indicative Saturated Weight - 109kg (60mm Substrate Depth)

Drawing Reference
SBS01



1 LEVEL 01 ROOF - GA PLAN


1 : 50

LEGEND

- STONE BALLAST
- GREEN ROOF SYSTEM
- FLAT 120 MM GUTTER
- RWO

KEY PLAN

1 : 500




General Notes

- Do not scale from this drawing. All dimensions indicated are in millimetres unless otherwise stated. Validate all measurements on site.
- Any discrepancies between the drawings and other documents should be brought to the attention of the contractor.
- This drawing is not an installation drawing. It is the contractor's responsibility to make final coordinated installation shop drawings.
- The contents of this drawing shall be read in conjunction with the current revisions of Architectural, Civil, Structural, Mechanical, Electrical, Telecoms drawings and all relevant sections of the specifications.

2000 0 2000 4000 6000 8000
SCALE: 1:200



Key Plan



P02	S4 - FOR APPROVAL	SRH/XX	03/04/2024
P01	S3 - FOR REVIEW AND COMMENT	SRH/XX	09/02/2024
Rev	Details	By / Chk / App	Date

Client
colt
Data Centre Services

Colt House, 20 Great Eastern Street
London, EC2A 3EH, United Kingdom
www.coltdatcentres.net

General Contractor
ISG

ISG Limited
Aldgate House
33 Aldgate High Street,
EC2N 1AO
United Kingdom

MEP Consultant
&

28-30 Worship Street
London, EC2A 2AH
United Kingdom
www.bw-engineering.com

Architect Consultant
NWA

The Old Dairy
Harpenden Farm
Redbourn, Hertfordshire
AL3 9QA, United Kingdom
www.nwarchitects.co.uk

Structural / Civil Consultant
ARUP

Central Square, Forn Street
Newcastle Upon Tyne
NE1 3PL, United Kingdom
www.arup.com

Fire Consultant
salus

Primrose House, Marla Court
Maple Drive, Hinckley, Leicestershire
LE10 3BF, United Kingdom
www.salusai.co.uk

Security Consultant
Control Risks

Cotters Centre, Cotters Lane
London, SE1 2QG, United Kingdom
www.controlrisks.com

Project Title
Colt London 4

Drawing Title
LEVEL 01 ROOF - GA PLAN

Project Status
WIP

Discipline
ROOFING

Status Code
S4


Project Number
DCS20109

Scale @ A1
As indicated

Revision
P02

Drawing Number
DCS20109-MRC-DC-B1-01-DR-X-27200

Project — Originator — Functional — Spatial — Level — Form — Discipline — Number
Breakdown — Breakdown




LEGEND

FLAT 120 MM GUTTER

GREEN ROOF SYSTEM

STONE BALLAST

RWO



KEY PLAN
1 : 500


1 ROOF LEVEL 02 -STAIRCASE 1 GA PLAN
1 : 30

General Notes

- Do not scale from this drawing. All dimensions indicated are in millimetres unless otherwise stated. Validate all measurements on site.
- Any discrepancies between the drawings and other documents should be brought to the attention of the contractor.
- This drawing is not an installation drawing. It is the contractor's responsibility to make final coordinated installation shop drawings.
- The contents of this drawing shall be read in conjunction with the current revisions of the relevant sections of the specifications.

ISS-A0-Plan-1044
2000 0 2000 4000 6000 8000
SCALE: 1:200
N

Key Plan



P02	S4 - FOR APPROVAL	SR/H/XX	28/03/2024
P01	S3 - FOR REVIEW AND COMMENT	SR/H/XX	08/02/2024
Rev	Details	By / Child / App	Date

Client
colt
Data Centre Services
General Contractor
ISG

MEP Consultant
&
28-30 Worship Street
London, EC2A 2AH
United Kingdom
www.bw-engineering.com


Architect Consultant
NWA
The Old Dairy
Hardenbury Farm
Redbourn, Hertfordshire
AL3 0QA, United Kingdom
www.nwarchitects.co.uk

Structural / Civil Consultant
ARUP
Central Square, Foss Street
Newcastle Upon Tyne
NE1 3PL, United Kingdom
www.arup.com

Fire Consultant
salus
Building Compliance without Complexity
Project Title
Primes House, Marina Court
Maple Drive, Hinckley, Leicestershire
LE10 3BF, United Kingdom
www.salus.co.uk

Security Consultant
Control Risks
Cotters Centre, Cotters Lane
London, SE1 2QG, United Kingdom
www.controlrisks.com

Project Title
Colt London 4
Drawing Title
**ROOF LEVEL 02 (STAIR 1) GREEN
ROOF- GA PLAN**
Project Status
WIP
Discipline
ROOFING
Status Code
S4
Project Number
DCS20109
Scale @ A1
As indicated
Revision
P02
Drawing Number
DCS20109-MRC-DC-B1-06-DR-X-27211
Project --- Originator --- Functional --- Spatial --- Level --- Form --- Discipline --- Number
Breakdown --- Breakdown




LEGEND

- STONE BALLAST
- GREEN ROOF SYSTEM
- FLAT 120 MM GUTTER
- RWO

1 ROOF LEVEL 02 GREEN ROOF STAIR 2- GA PLAN
1 : 20

KEY PLAN
1 : 500



General Notes												
1. Do not scale from this drawing. All dimensions indicated are in millimetres unless otherwise stated. Validate all measurements on site.												
2. Any discrepancies between the drawings and other documents should be brought to the attention of the Contractor.												
3. This drawing is not an installation drawing. It is the Contractors responsibility to make final coordinated installation shop drawings.												
4. The contents of this drawing shall be read in conjunction with the current revisions of Architecture, Civil, Structural, Mechanical, Electrical, Security, Telecoms drawings and all relevant sections of the specifications.												
SCALE: 1:200												
Key Plan												
<table border="1"> <tr> <td>P02 S4 - FOR APPROVAL</td><td>SR/H/XX</td><td>29/03/2024</td></tr> <tr> <td>P01 S3-FOR REVIEW AND COMMENT</td><td>NP/H/XX</td><td>09/02/2024</td></tr> <tr> <td>Rev Details</td><td>By / Child / App</td><td>Date</td></tr> </table>				P02 S4 - FOR APPROVAL	SR/H/XX	29/03/2024	P01 S3-FOR REVIEW AND COMMENT	NP/H/XX	09/02/2024	Rev Details	By / Child / App	Date
P02 S4 - FOR APPROVAL	SR/H/XX	29/03/2024										
P01 S3-FOR REVIEW AND COMMENT	NP/H/XX	09/02/2024										
Rev Details	By / Child / App	Date										
<p>Client Colt House, 20 Great Eastern Street London, EC2A 3EH, United Kingdom www.coltdatcentres.net</p>												
<p>General Contractor ISG Limited Allegate House 33 Allegate High Street, EC3N 1AO United Kingdom</p>												
<p>MEP Consultant B&W Engineering 28-30 Worship Street London, EC2A 2AH United Kingdom www.bw-engineering.com</p>												
<p>Architect Consultant NWA The Old Dairy Harpendenbury Farm Redbourn, Hertfordshire AL3 9QA, United Kingdom www.nwarchitects.co.uk</p>												
<p>Structural / Civil Consultant ARUP Central Square, Firth Street Newcastle Upon Tyne NE1 3PL, United Kingdom www.arup.com</p>												
<p>Fire Consultant salus Building Compliance without Complexity Prime House, Marina Court Maple Drive, Hinckley, Leicestershire LE10 3PF, United Kingdom www.salusai.co.uk</p>												
<p>Security Consultant Control Risks Cottons Centre, Cottons Lane London, SE1 2QG, United Kingdom www.controlisks.com</p>												
<p>Project Title Colt London 4</p>												
<p>Drawing Title ROOF LEVEL 02 (STAIR 2) GREEN ROOF - GA PLAN</p>												
<p>Project Status WIP</p>												
<p>Discipline ROOFING</p>												
<p>Scale @ A1 S4</p>												
<p>Project Number DCS20109</p>												
<p>Revision P02</p>												
<p>Drawing Number DCS20109-MRC-DC-B1-06-DR-X-27213</p>												
<p>Project — Originator — Functional — Spatial — Level — Form — Discipline — Number Breakdown — Breakdown</p>												