



This architectural elevation drawing shows a long, low building facade. The facade is divided into several sections. On the left, there is a section with a grid of windows, some of which are shaded. This is followed by a section with a large, solid wall. To the right of this, there is another section with a grid of windows, similar to the first one. Further right, there is a large, solid wall section. On the far right, there is a section with a grid of windows, some of which are shaded. The drawing includes 13 numbered callouts (1-13) pointing to various features of the facade, such as windows, doors, and structural elements. The callouts are arranged in a row at the top of the drawing.

EXTERNAL MATERIALS		
01	External Cladding 2	Rockwool insulated flat metal composite trimo panels with pre-finished corners. Horizontally laid 1000mm wide. Colour: Prima White RAL 9010, Sirius, Orion and Zeus.
02	External Cladding 2	Fully insulated sinusoidal solid up cladding laid horizontally.
03	External Cladding 3	Fully insulated half round built up cladding laid horizontally.
04	External Cladding 4	Prime SFX rainscreen cladding system laid horizontally.
05	Roof Fascia and External Feature Band	Secret fixed fascia, HP5200 Ultra Colour: Green RAL 6016
06	Roof	Non-Fragile Twin-Therm® [Cerberus] fully insulated roof assembly system assembly, Colourscoat HP5200 colour: Alabaster
07	Translucent wall system	Twinkl modular polycarbonate translucent panel cladding system
08	External Glazing & Entrance Door	Clear high performance solar control toughened and heat soaked tested glass in polyester powder coated aluminium curtain walling system colour RAL 7016 (Anthracite Grey)
09	Personel & Fire Exit Door	Coated steel door to match adjacent cladding
10	Level access doors	5.0m wide x 5.5m high double-skinned steel sectional door. Stucco finished aluminium to specification. Colour RAL 9006-Silver
11	Loading Doors	Stucco finished aluminium. Finish PPC Sirius (RAL 9006)
12	Dock Surrounds	Prowall Insulated Concrete Panel
13	Brise Soleil	Powder Coated Aluminium Horizontal Aerofac Fins. Colour Metallic RAL 9006

This architectural elevation drawing shows a long, low building with a complex roofline. The facade is divided into several vertical sections. The roof is composed of multiple gabled sections with varying pitches. The main body of the building has a light-colored, horizontally-ribbed or paneled exterior. On the right side, there is a section with three rectangular windows, each divided into four panes. A small, dark rectangular feature, possibly a door or a vent, is located near the bottom right. Thirteen numbered callouts (1-13) are placed above the building, with lines pointing to specific architectural details: 1 points to the leftmost roof edge; 2 points to the first roof slope; 6 points to the ridge of the first gable; 5 points to the horizontal paneling below the first gable; 2 points to the horizontal paneling below the second gable; 3 points to the ridge of the second gable; 2 points to the horizontal paneling below the third gable; 7 points to the ridge of the third gable; 2 points to the horizontal paneling below the fourth gable; 3 points to the ridge of the fourth gable; 9 points to the horizontal paneling below the fifth gable; 1 points to the horizontal paneling below the sixth gable; 2 points to the horizontal paneling below the seventh gable; 5 points to the horizontal paneling below the eighth gable; 8 points to the horizontal paneling below the ninth gable; 4 points to the horizontal paneling below the tenth gable; and 13 points to the horizontal paneling below the eleventh gable.

PROVIDE ONE HOUR FIRE PROTECTION TO UPPER FLOORS
CONSTRUCTION AND ONE HOUR FIRE PROTECTION TO
SUPPORTING STRUCTURE.

COMPLY WITH ALL PARTS OF APPROVED DOCUMENTS
IN PARTICULAR PART B, PART L2 AND PART M.

ENSURE SEALING OF ALL JUNCTIONS TO COMPLY WITH PART L.

U-VALUES SUBJECT TO SBEM CALCULATION.

ROOF AND WALL CLADDING TO BE DESIGNED BY SPECIALIST
CONTRACTOR.

CLADDING DETAILS TO BE READ IN CONJUNCTION WITH THE
SPECIFICATION AND ALL RELEVANT BRITISH STANDARDS,
INCLUDE VAPOUR BARRIER TAPE AROUND ALL OPENINGS AND
JUNCTIONS.

ALL DIMENSIONS TO BE CHECKED ON SITE.

STEEL COLUMN SIZES TO BE CONFIRMED AND TOLERANCES TO BE
AGREED.

PLANNING

B	30.06.2020	Prologis sign added to elevation	SS	SD
A	23.06.2020	Updated fro Planning	SS	SD
*	10.06.2020	First issue	SS	SD
REV	DATE	NOTE	DRAWN	CHECKED



CHARTERED ARCHITECTS

11PLATO PLACE
ST. DIONIS ROAD
LONDON SW6 4TU

TELEPHONE 020 7736 6162
www.msa-architects.co.uk

TITLE
IRONBRIDGE ROAD, HAYES

DRAWING

DC 2 GA Elevations

CLIENT

PROLOGIS UK LTD

DATE	SCALE	DRAWN	
04/04/2020	1 : 200@A1	SS	
MSA NUMBER	STATUS	CHECKED	MSA SERIES
30928	PLANNING	SD	PL

DRAWING NUMBER
30928 PL 206B