



#### NOTES

**Retaining walls to rear garden**  
 Finished height of the retaining walls to be dictated by the rear boundary fence line and new Thuja hedge. Wall height need to be checked. Wall to be 100mm thick. Wall to be faced with 200mm solid concrete block backing and Hydra Beige porcelain cladding, installed as per manufacturers specifications. Coping to be Warm Beige 600x300mm porcelain coping stones. To backfill behind the walls with previous excavations, free draining material and new imported topsoil. Rear of wall below ground or soil level to be painted with 2 coats bitumen paint. Weep holes at 2m centres or as required. Joints to be pointed with Steintech Beige Tuff Top pointing compound.

**Paving areas**  
 Stone to be Warm Beige porcelain tiles, 600x600mm, from London Stone or TBA, with the client. Paving to be laid on a 50mm sand/cement half bed over a 100mm compacted MOT type 1, depth dependent on ground conditions, and a geo-textile membrane. Pointing with Steintech Tuff Top in beige colour.  
 To supply and install slot drains as required to remove surface water runoff. To be connected into the existing storm water gullies.

**Porcelain sett edge to lawn**  
 Bespoke size porcelain sets, size to be 100x200mm, 20mm thick to match terrace stone. Edge to be laid over concrete footings and 50mm full mortar laying bed. Joints to be pointed with Steintech Beige Tuff Top pointing compound.

**Granite sets and drive aprons to front garden**  
 Drive aprons to be laid with 5 rows of 100x200x50mm granite sets, set over 100mm reinforced concrete base and full mortar laying bed. Joints to be pointed with Steintech Beige Tuff Top pointing compound.  
 Sett edging to be single row of 100x200x50mm granite sets, set over concrete footings and full mortar laying bed. Joints to be pointed with Steintech Beige Tuff Top pointing compound.

**Stepping stones**  
 Flag stepping stones to be porcelain tiles, 600x900mm, from London Stone, laid on a 100mm sand/cement full bed with the sides well haunched.

\*All porcelain products stated as specified by London Stone Ltd.

\*All paving to be laid to appropriate falls.

**Resin bound gravel drive**  
 Base to be 150mm compacted MOT type 3 over a woven geo-textile membrane.

Porous macadam and Sureset surface dressing to be installed as per manufacturers specification, TBA.

**Gravel infill**  
 Aggregate to be 20mm white lime stone chippings. Aggregate to be 35mm deep once compacted. Base to be 50mm compacted MOT type 1 over a geo-textile membrane.

**Raised vegetable beds**  
 Sawn oak, 50mm by 250mm. Timber to be fixed together at right angles as drawings, with steel fixings and screws, hidden with oak plugs. Filled with soil suitable for growing vegetables to 25mm below top level of wooden frame.

**Planting areas**  
 All planting beds to be dug over to 450mm depth and 40L per m<sup>2</sup> of well-rotted organic matter incorporated into the soil. 25g/m<sup>2</sup> bone-meal to be incorporated. New topsoil to BS standard to be imported where required for raised planters.

**Lawn** (where re-grading is required)  
 Lawn areas to be culmated to a depth of 150mm. Where required, 20L of organic matter and 20L of coarse grit sand to be incorporated per m<sup>2</sup>. Turf to be Rollawn RB meditation or similar sports grade turf.

**Garden Buildings**  
 Building to be Vermont Summer House supplied by Wayfair, as per link: <https://www.wayfair.co.uk/garden/pdp/home-essence-vermont-summer-house-hes8676.html?pid=SummerHouse> to be constructed over a 100mm reinforced concrete base.

**Lighting**  
 To supply and install 12V lighting as per design plan. Lighting to be sourced from Lighting for Gardens as per links:

Pole Duo Spotlight  
<https://www.lightingforgardens.com/pole-spot-duo-black-12v>

Spike Spotlight  
<https://www.lightingforgardens.com/compact-spike-spotlight-black-12v-mr16>

From Gardens - Pole lights x 9  
 From Gardens - Spike Uplights x 2  
 Back Gardens - Pole lights x 6  
 Back Gardens - Spike Uplights x 6

**CDM (Construction, Design, Management) NOTES**  
 There are low walls in the design so young children should be supervised when using the garden. Paved areas and steps should be kept free of algae and moss to prevent them becoming slippery. Extra care should be taken when they are wet.

Client consulted Yes date - At presentation meeting

EXAMPLE OF VERMONT SUMMER HOUSE



SPIKE SPOTLIGHTS



POLE DUO SPOTLIGHTS



<b>THE GARDEN COMPANY</b>	
Chipperfield Garden Centre Tower Hill Herts WD4 9LH	
Tel: 01442 832666 <a href="http://www.thegardenco.co.uk">www.thegardenco.co.uk</a>	
e-mail: <a href="mailto:sales@thegardenco.co.uk">sales@thegardenco.co.uk</a>	
PROJECT 15 King Edward Road Ruislip HA4 7AE	
TITLE Front and Rear Garden Plan	
CLIENT Mr. Mohal	
SCALE: 1:50 @ A1 DATE: April 2019 DRAWING No.: M01TGC2019	
Do not scale from this drawing. All dimensions to be checked on site.	
© The Garden Company Ltd James Scott MSGD SOCIETY OF GARDEN DESIGNERS REGISTERED PRACTICE	