


MXZ-F OUTDOOR UNITS	MXZ-3F68VF3	MXZ-6F122VF
NUMBER OF CONNECTABLE INDOOR UNITS	2-3	2-6
CAPACITY		
Heating (nominal)	7.0 (2.6-9.0)	14.0 (3.5-16.5)
Cooling (nominal)	5.4 (2.9-6.8)	12.2 (3.5-13.5)
Heating (UK)	5.81 (2.16-7.47)	11.6 (2.90-13.71)
Cooling (UK)	5.30 (1.10-5.60)	12.1 (3.47-13.39)
COP/EER (nominal) <sup>1)</sup>	4.60 / 4.10	4.23 / 3.33
SCOP (nsc) / SEER (nsc) (BS EN14825)	4.61 / 8.52	4.65 (183.1%) / 7.65 (303%)
ErP ENERGY EFFICIENCY CLASS	A++ / A+++	A++ / A++
Heating/Cooling		
MAX AIRFLOW (m <sup>3</sup> /min)		
Heating/Cooling	43.0 / 42.1	77 / 63
SOUND PRESSURE LEVEL (dBA)		
Heating/Cooling	50 / 46	57 / 55
SOUND POWER LEVEL (dBA)		
Cooling	59	69
DIMENSIONS (mm) WxDxH	840 x 330 x 710	950 x 330 x 1048
WEIGHT (kg)	58	87
ELECTRICAL SUPPLY	220 - 240v, 50Hz	220 - 240v, 50Hz
PHASE	Single	Single
POWER INPUT		
Heating/Cooling (nominal)	1.52 / 1.32	3.31 / 3.66
Heating/Cooling (UK)	1.38 / 1.06	3.04 / 3.44
STARTING CURRENT (A)	7.0	16.1
RUNNING CURRENT (A)	7.0 / 5.9 [18.0]	14.5 / 16.1 [29.8]
INTERCONNECTING CABLE No. CORES	4 Core	4 Core
TOTAL PIPE LENGTH (m)	50	80
MAX PIPE LENGTH PER INDOOR UNIT (m)	25	25
MAX HEIGHT DIFFERENCE (m)	15 (10 if OU higher than IU)	15
CHARGE REFRIGERANT (kg) / CO <sub>2</sub> EQUIVALENT (t) - R32 (GWP 675)	2.4 / 1.62 (50m)	2.4 / 1.62 (80m)
FUSE RATING (BS88) - HRC (A)	25	32

Condenser Unit External Dimensions



Model		PURY-P250YNW-A (-BS)	
Power source		3-phase 4-wire 380-400-415 V 50/60 Hz	
Cooling capacity (Nominal)	*1 kW	28.0	
	kcal/h	25,000	
	BTU/h	95,500	
Power input	kW	5.97	
Current input	A	10.0-9.5-9.2	
EER	kW/kW	4.69	
Temp. range of cooling	Indoor	W.B.	15.0-24.0°C (59-75°F)
	Outdoor	D.B.	-5.0-52.0°C (23-126°F)
Heating capacity (Max)	*2 kW	31.5	
	kcal/h	27,100	
	BTU/h	107,500	
Power input	kW	6.06	
Current input	A	10.2-9.7-9.3	
COP	kW/kW	5.19	
(Nominal)	*3 kW	28.0	
	kcal/h	25,000	
	BTU/h	95,500	
Power input	kW	5.27	
Current input	A	8.8-8.4-8.1	
COP	kW/kW	5.31	
Temp. range of heating	Indoor	D.B.	15.0-27.0°C (59-81°F)
	Outdoor	W.B.	-20.0-15.5°C (-4-60°F)
Indoor unit connectable	Total capacity	50-150%	P15-P250/1-25
	Model/Quantity		
Sound pressure level (measured in anechoic room) <sup>4)</sup>	dB <A>	60.5/61.0	
Sound power level (measured in anechoic room) <sup>4)</sup>	dB <A>	78.5/80.0	
Refrigerant	High pressure mm (in.)	19.05 (3/4) Brazed	
piping diameter	Low pressure mm (in.)	22.2 (7/8) Brazed	
FAN	Type x Quantity	Propeller fan x 1	
	Air flow rate m <sup>3</sup> /min	185	
	L/s	3,083	
	cfm	6,532	
	Control, Driving mechanism	Inverter-control, Direct-driven by motor	
	Motor output kW	0.92 x 1	
	*5 External static press.	0 Pa (0 mmH <sub>2</sub> O)	
Compressor	Type	Inverter scroll hermetic compressor	
	Manufacture	AC&R Works, MITSUBISHI ELECTRIC CORPORATION	
	Starting method	Inverter	
	Motor output kW	7.0	
	Case heater kW	-	
	Lubricant	MEL32	
External finish	Pre-coated galvanized steel sheets (+powder coating for -BS type)		
External dimension H x W x D mm	<MUNSELL 5Y 8/1 or similar>		
	1,858 (1,798 without legs) x 920 x 740		
Protection devices	High pressure protection	High pressure sensor, High pressure switch at 4.15 MPa (601 psi)	
	Inverter circuit (COMP/FAN)	Over-heat protection, Over-current protection	
	Compressor	-	
	Fan motor	-	
Refrigerant	Type x original charge	R410A x 5.2 kg (12 lbs)	
	Control	Indoor LEV and BC controller	
Net weight	kg (lbs)	229 (505)	
Heat exchanger		Salt-resistant cross fin & copper tube	
HIC circuit (HIC: Heat Inter-Changer)		-	
Defrosting method	Auto-defrost mode (Reversed refrigerant cycle)		
Drawing	External	WKS947748	
	Wiring	WKE94G339	
Standard attachment	Document	Installation Manual	
	Accessory	-	
Optional parts	Joint: CMY-Y102SS-G2, CMY-Y102LS-G2, CMY-R160-J1 BC controller: CMB-P104, 106, 108, 1012, 1016V-J Main BC controller: CMB-P108, 1012, 1016V-JA, CMB-P1016V-KA Sub BC controller: CMB-P104, 108V-KB		
Remarks	Details on foundation work, duct work, insulation work, electrical wiring, power source switch, and other items shall be referred to the Installation Manual. Due to continuing improvement, above specifications may be subject to change without notice.		
Notes:			
1. Nominal cooling conditions (subject to JIS B8615-2) Indoor: 27°CDB/19°CWB, (81°FDB/66°FWB), Outdoor: 35°CDB/24°CWB, (95°FDB/75°FWB) Pipe length: 7.5 m (24-9/16 ft), Level difference: 0 m (0 ft)			
2. Nominal heating conditions (subject to JIS B8615-2) Indoor: 20°CDB, (68°FDB), Outdoor: 7°CDB, 6°CWB, (45°FDB/43°FWB)			
3. Nominal heating conditions (subject to JIS B8615-2) Indoor: 20°CDB, (68°FDB), Outdoor: 7°CDB, 6°CWB, (45°FDB/43°FWB) Pipe length: 7.5 m (24-9/16 ft), Level difference: 0 m (0 ft)			
4. Cooling mode/Heating mode			
5. External static pressure option is available (30 Pa, 60 Pa, 80 Pa/3.1 mmH <sub>2</sub> O, 6.1 mmH <sub>2</sub> O, 8.2 mmH <sub>2</sub> O). Consult your dealer about the specification when setting External static pressure option.	*Above specification data is subject to rounding variation.		
	Unit converter		
	BTU/h	=kW x 3.412	
	cfm	=m <sup>3</sup> /min x 35.31	
	lbs	=kg/0.4536	

Bullet GG Antennas



**GENERAL NOTES**

- No dimensions are to be scaled from the drawing. All dimensions, material, and finish are to be determined by the Contractor and must be consistent with any conditions, including checking the dimensions and report in writing of any discrepancies with the information depicted in this drawing or the specifications.
- Specifications, Schedules and Bill of Quantities (the Contract Information) provide the basis for the work to be performed. The Contractor shall advise in writing of any inconsistencies or contradictions of any of the information contained therein and shall obtain further instructions from CBRE prior to proceeding.
- Contractors to advise on suitability of all details and to ensure structural integrity, stability and strength of all components for the intended performance.
- Contractors are responsible for obtaining all relevant manufacturing data and recommendations. Contractors are responsible for obtaining all relevant recommendations from CBRE prior to proceeding.
- Contractors to ensure that all materials and construction complies with Building Regulations, Environmental Health, Planning, CDM and any other relevant regulations and requirements.
- Contractors to ensure all specified materials, fixtures and fittings are provided and meet all aspects of the project programme and must advise CBRE if any items will not be available in sufficient time and to request further instructions.

**Copyright notice:**  
This and all other documents authored by CBRE and all information and communications provided and implied therein are the sole property of CBRE. Reproduction or transmission in any form is strictly forbidden unless prior permission is obtained in writing from CBRE. Construction based on the depicted information at any time or location not related to this project is strictly prohibited unless prior permission is obtained in writing from CBRE.

REV. DATE DETAILS DRAWN CHECKED

/ 30/10/23 Issued for Planning NT IC

**PHYSICAL CHARACTERISTICS – 3.3V & 5V DC ANTENNAS**

Dimensions.....3.05" D x 2.61" H (77.5mm x 66.2mm)  
Weight.....6.0oz (170grams)  
Enclosure.....Off-white plastic  
Connector.....F-type & TNC (5V) – TNC (3.3V only)  
Mounting.....1" – 14" thread or 1/4" pipe thread

0 2 4 6 8 10m

SCALE 1 : 200

PROJECT  
ZUK131 Uxbridge  
Charter Pl, Uxbridge  
UB8 1JG

TITLE  
Proposed Condenser Details

CLIENT NAME  
CBRE

STATUS	PLANNING	SCALE
DATE	Oct 2023	1 : 1 @ A1
DRAWN		CHECKED
IC	NT	
DRAWING NUMBER	ZUK - BOX - XX - XX - DR - A (20)010	
REVISION		JOB NUMBER
		831,113

**CBRE**

CBRE GWS  
Principle PJM  
61 Southwark Street  
London, SE1 0HL