

| | |
|----------------|---|
| Calculated by: | Sohan Ghimire |
| Site name: | 32 Ferndale Crescent, Uxbridge, Middlesex UB8 2AX |
| Site location: | 32 Ferndale Crescent, Uxbridge, Middlesex UB8 2AX |

This is an estimation of the greenfield runoff rates that are used to meet normal best practice criteria in line with Environment Agency guidance "Rainfall runoff management for developments", SC030219 (2013) , the SuDS Manual C753 (Ciria, 2015) and the non-statutory standards for SuDS (Defra, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

Reference:

3520371292

Date:

Aug 12 2024 09:47

Runoff estimation approach

IH124

Site characteristics

Total site area (ha): 0.10

Methodology

Q_{BAR} estimation method:

Calculate from SPR and SAAR

SPR estimation method:

Calculate from SOIL type

Soil characteristics

SOIL type:

| | Default | Edited |
|--|---------|--------|
| | 2 | 2 |
| | N/A | N/A |
| | 0.3 | 0.3 |

HOST class:
SPR/SPRHOST:

Hydrological characteristics

SAAR (mm):

| | Default | Edited |
|--|---------|--------|
| | 629 | 629 |
| | 6 | 6 |
| | 0.85 | 0.85 |
| | 2.3 | 2.3 |
| | 3.19 | 3.19 |
| | 3.74 | 3.74 |

Hydrological region:
Growth curve factor 1 year:
Growth curve factor 30 years:
Growth curve factor 100 years:
Growth curve factor 200 years:

Notes

(1) Is $Q_{BAR} < 2.0 \text{ l/s/ha}$?

When Q_{BAR} is $< 2.0 \text{ l/s/ha}$ then limiting discharge rates are set at 2.0 l/s/ha .

(2) Are flow rates $< 5.0 \text{ l/s}$?

Where flow rates are less than 5.0 l/s consent for discharge is usually set at 5.0 l/s if blockage from vegetation and other materials is possible. Lower consent flow rates may be set where the blockage risk is addressed by using appropriate drainage elements.

(3) Is $SPR/SPRHOST \leq 0.3$?

Where groundwater levels are low enough the use of soakaways to avoid discharge offsite would normally be preferred for disposal of surface water runoff.

Greenfield runoff rates

| | Default | Edited |
|-------------------------|---------|--------|
| Q _{BAR} (l/s): | 0.16 | 0.16 |
| 1 in 1 year (l/s): | 0.14 | 0.14 |
| 1 in 30 years (l/s): | 0.37 | 0.37 |
| 1 in 100 year (l/s): | 0.51 | 0.51 |
| 1 in 200 years (l/s): | 0.6 | 0.6 |

This report was produced using the greenfield runoff tool developed by HR Wallingford and available at www.eksuds.com. The use of this tool is subject to the UK SuDS terms and conditions and licence agreement , which can both be found at www.eksuds.com/terms-and-conditions.htm. The outputs from this tool are estimates of greenfield runoff rates. The use of these results is the responsibility of the users of this tool. No liability will be accepted by HR Wallingford, the Environment Agency, CEH, Hydrosolutions or any other organisation for the use of this data in the design or operational characteristics of any drainage scheme.