


SCALE BAR 1:50 @ A1



PROPOSED GROUND FLOOR
SCALE BAR 1:50 @ A1

Plumbing Installation
Complete installation to be subject to and capable of withstanding testing in accordance with BS 5572:1978. Above ground level foul drainage pipe work shall be PVC-u to BS 4514.

Pipework must be designed in accordance with BS 5572 and installed to ensure that appliances drain efficiently without causing crossflow, backfall, leakage or blockage to lengths and at junctions - changes of direction to be provided. No branch connection to be within 450mm above foot of soil pipe. All PVC-u pipework to be installed to BS 4514.

Minimum pipe sizes for sanitary plumbing to be:

- WC's soil pipes - 100mm dia Nominal size.
- Handbasins - 32mm dia Nominal size.
- Showers - 32mm dia Nominal size.
- Overflow - 19mm dia Nominal size.


All fittings to have a 75mm deep seal traps. All waste pipes to be laid to falls 25mm per metre run. All sanitary fittings to be installed as per manufacturers instructions. The maximum lengths of waste pipes shall be as follows.

- 32mm pipe - 1.7m Maximum length.
- 40mm pipe - 3.0m Maximum length.
- 50mm pipe - 4.0m Maximum length.
- 100mm pipe - 6.0m Maximum length.

Soil and Ventilating stacks @ head of drainage run to be ventilated to the external air
(Min 900mm above any openable window head or within 3m horizontally).

Soil pipes passing through habitable rooms (including kitchens) to be lagged with minimum 50mm sound deadening quilt and 2 layers of 12.5mm plasterboard in 38mm x 38mm softwood framing. Access and rodding eye fittings to be provided to ensure all pipework is accessible as required. Pipework laid between joists to be adequately supported. Underground pipes with less than 750mm ground cover shall be insulated. Any rising mains are to be insulated.

New 100mm dia stub stack as indicated with rodding access to serve new shower/ensuites. Surface water to be conveyed to existing rainwater drainage system.




PROPOSED FIRST FLOOR
SCALE BAR 1:50 @ A1

Ventilation
All habitable rooms to have rapid ventilation via windows/doors of an openable area of at least 1/20th of the floor area, part of the ventilation area is to be 1.75m above floor area.

Windows are to provide 4000 sq/mm minimum of background ventilation via controlled trickle vents in utility room, en suite and bedroom. All habitable rooms to achieve 8000 sq/mm. Alternatively the sum of all trickle vents must equal 6000 sq/mm as specified in Table 1 of approved document F1.

Shower to be ventilated mechanically ventilated with a wall mounted fan which can achieve extract to external air @ 15 litres per second.

Mechanical vents are to be tested and commissioned in accordance with regulation 42 and part F1 2010.



PROPOSED LOFT FLOOR
SCALE BAR 1:50 @ A1

New Staircase
Staircase to be closed plan - min going 220mm maximum pitch to be 42 degrees. Maximum rise to be 190mm. Staircase balustrade designed to prevent a 100mm sphere passing through. Balusters to be vertical and a 1100 c/c. handrail to be min 900mm above pitch line max 1000mm. Clear unobstructed width min 725mm minimum landing to be 725mm. Alternative the sum of all proposed staircase. Two way switches to be fitted to top & bottom of stairs.

PROPOSED LOFT FLOOR
SCALE BAR 1:50 @ A1

Aspirator walls - Stud partition, Internal walls offering separation between a room containing a water closet and other rooms within the dwelling to achieve a reasonable resistance to the passage of sound (Minimum 40dB). Timber stud walls to have a minimum of 55mm between linings with one layer of 15mm plasterboard to both sides achieving a minimum mass of 10kg/m² between the stud partitioning. Sound deadening quilt insulation to fill cavity.

Doors
Two coat sand cement render on Exomat mesh, building paper - 10mm Marine ply nailed to 47mm x 100mm vertical timber studs @ 400mm o.c. Insulation to be 100mm Between timber studs. 50mm insulation over studs. Joints taped as VCL, 3.0mm Plaster skim.

Gas:

All works to the boiler and heating system to be carried out by a Gas Safety Registered person.

The hot water supply to baths/sinks/showers must incorporate measures to ensure that the temperature of the water does not exceed 48 degrees celsius. Thermostatic mixing valves to be provided. Hot Water pipes to be insulated to conserve heat in unheated spaces with material having a thermal conductivity at 40 degrees celsius not exceeding 0.035 W/m2K, having a thickness equal to the diameter of the pipe up to a maximum of 40mm.

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke Detectors
Smoke detection system to be designed and installed in accordance with BS5839-6: 2004 and BS 5446-1:2002 and BS 5446-2:2003. Detectors are to be mains operated with a secondary power supply for back-up.

Lighting
All light switches are to be fitted 1200mm from finished floor level. Lighting. 75 % of new light fittings to be energy efficient.

Lighting layout to be confirmed by client

Fire Doors
Doors should be fitted with three hinges that have a melting point of 800 degrees celsius.

Smoke