

Marley Eternit uses cookies to track usage. By continuing to browse the site you are agreeing to our use of cookies. To find out more about cookies and how to manage them, take a look at our [cookie policy \(/StandardItems/Ref/Cookie-Policy.aspx\)](#).

Continue

Modern Interlocking Tile

Large format in a traditional flat profile

Advantages



Excellent covering capacity
Achieves the highest score in the Green Guide to Specification

- (/)
- > An 'Excellent' certification for BES 6001
- > Interested in an affordable upgrade? [Click here for more information \(/edgemere\)](#)
- Concrete Tiles (/Roofing/Concrete-Tiles.aspx) : Modern Interlocking Tile



1/3



Colours & Samples



Click on a colour to view a larger version and to select a sample

Modern - Anthracite (MA10438S)

Add to Sample Basket

Go to Sample Basket (/Roofing/Resources/Roofing-Sample-Requests.aspx)



1/6



Marley Eternit uses cookies to track usage. By continuing to browse the site you are agreeing to our use of cookies. To find out more about cookies and how to manage them, take a look at our [cookie policy \(/StandardItems/Ref/Cookie-Policy.aspx\)](#).

Continue

Description

Keep up to date with our roofing blog

Enter your email address here...

Keep me updated



The Modern interlocking tile is a flat, smooth, single-lap interlocking design with a slate-like appearance enhanced by a broken bond laying pattern.

All of our concrete interlocking tiles can achieve an 'A+' rating (the lowest environmental impact) in the Building Research Establishment's Green Guide to Specification (* element ref: 812410007, 812410018, 812410049).

Accreditation to the BES 6001 framework standard for 'Responsible Sourcing' means that projects using our concrete tiles can now achieve extra credits under BREEAM and the Home Quality Mark (HQM). Click here to find out more (/resources/sustainability.aspx#1).

Have you also considered the Edgemere interlocking slate range? With an 18mm thin leading edge, Edgemere provides an affordable upgrade to standard interlocking tiles and comes in Standard, Riven or Duo formats, providing three distinct and slate-like finishes. Click here to find out more (/edgemere)

Please note The British Standard for Slating and Tiling (BS 5534) has recently been updated, making significant changes to tile fixing requirements. To ensure that your roof is compliant to the new standard, our fixing specification service is available and can be accessed by clicking here (/Resources/Technical-services/Landing-Page.aspx)

If you would like to find out more about our truly complete roof system, underwritten by a 15 year warranty, please click here (/Roof-System.aspx).

Brochures



(/~/media/Files/Product-Files/Roofing/Brochure-Request/Roofing-Accessories-Brochure.pdf)

Roofing Accessories

(/~/media/Files/Product-

Files/Roofing/Brochure-Request/Roofing-

Accessories-Brochure.pdf)

Request/Roofing-Accessories-

Brochure.pdf)

PDF | 56 | 7.00 MB

> Send printed brochure by post (/Roofing/Resources/Roofing-Brochure-Request.aspx?b=99e30866-ad6b-4075-979d-a8d2f91bd4a7)

Technical Info



Size of Tile

420mm x 330mm

Minimum Pitch

22.5° Smooth (75mm headlap)
17.5° Smooth (100mm headlap)
30° Granular (75mm headlap)
25° Granular (100mm headlap)

Maximum Pitch

90°

Minimum Headlap

75mm

Maximum Gauge

345mm