



April 4, 2025

Sweet Projects
Union Park
Hayes
UB34QQ

RE: Land at Bulls Bridge Industrial Estate North Hyde Gardens Hayes – SuDS Verification Information

To Whom It May Concern,

HDR have been requested to draft a verification statement of the current design strategy and collate relevant SuDS details, as-built information, and certifications of manufacturers.

The following design information can be verified by HDR as compliant with the original planning application and documentation. This information was part of the design package provided to the contractor.

Block 2

- HDR-0472-SWS-BG-DR-C-520210 Rev P18
- HDR-0472-SWS-BG-DR-C-520211 Rev P16
- HDR-0472-SWS-BG-DR-C-520212 Rev P10
- HDR-0472-SWS-BG-DR-C-520213 Rev P13
- HDR-0472-SWS-BG-DR-C-520215 Rev P01
- HDR-0472-SWS-BG-DR-C-520501 Rev P02
- HDR-0472-SWS-BG-DR-C-520502 Rev P02
- HDR-0472-SWS-BG-DR-C-520503 Rev P04
- HDR-0472-SWS-BG-DR-C-520504 Rev P03
- HDR-0472-SWS-BG-DR-C-520505 Rev P02
- HDR-0472-SWS-BG-SCH-C-520010 Rev P17
- HDR-0472-SWS-BG-SCH-C-520020 Rev P17

The above information has been appended to this letter.

The following information was provided by Sweet Projects as additional supporting information.

hdrinc.com

HDR Consulting Limited. Company Reg No: 26943273. Incorporated in: England & Wales.
Registered address: 240 Blackfriars Road, London, SE1 8NW, United Kingdom
+44 (0) 20 7429 3333




- TOU-0472-UP2-BG-TS-X-0038_Rain Water Harvesting Tanks
- TOU-0472-UP2-BG-TS-X-0039_Kingspan Klargester NSFP006 Full Retention Separator
- TOU-0472-UP2-BG-TS-X-0040_Kingspan Klargester Class II Forecourt Separator

The above information has been appended to this letter.

Yours faithfully,
HDR Consulting Limited

A handwritten signature in black ink that reads 'Groenewald'.


Ulrich Groenewald *MIET CEng*
Associate Director



© THIS DRAWING IS THE COPYRIGHT PROPERTY OF HDR AND IS THEREFORE CONFIDENTIAL AND MUST NOT BE LENT, COPIED, REPRODUCED IN ANY WAY WHATSOEVER WITHOUT WRITTEN PERMISSION.

NOTES:

1. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
2. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
4. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025



LEGEND

PLANNING BOUNDARY	
PHASE ONE CONSTRUCTION BOUNDARY	
EXISTING SURFACE WATER	
EXISTING PRIVATE FOUL WATER	
EXISTING PUBLIC FOUL WATER	
PROPOSED SURFACE WATER	
PROPOSED BACK DROP	
PROPOSED FOUL WATER	
EXISTING THAMES VALLEY SEWER	
PERMEABLE PAVING CONNECTIONS	
RAINWATER & CHANNEL CONNECTIONS (RWP01.XX)	
DRAINAGE CHANNEL (CH01.XX, FWCH01.XX)	
SOIL VENT PIPE & FLOOR GULLY CONNECTIONS (SV01.XX, FG01.XX)	
GULLY CONNECTION (GU01.XX)	
EXISTING GULLY CONNECTION (EXGU01.XX)	
SEWER NETWORK TO BE ABANDONED	
SWALE (SL01.XX)	
FILTRATION TRENCH (FT01.XX)	
LAND DRAIN (REFER DETAILS)	
SETTING OUT POINTS FOR SWALE, CHANNELS, TANKS	

Drawing Status: **FOR APPROVAL** Suitability: **S4**

HDR 4TH FLOOR
KNOLLYS HOUSE
17 ADDINGTON ROAD
CROYDON CR0 6SR
UNITED KINGDOM
t: +44 (0) 20 8763 5900
e: info@drinc.com
w: www.drinc.com


Client: **SWEET PROJECTS**
Architect: **NWA**
Project: **UNION PARK**
Title: **BLOCK 2
BELOW FINISHED GROUND LEVEL
FOUL AND SURFACE DRAINAGE
LAYOUT SHEET 1 OF 4**

HDR Project Number: **10274713**
Cad File Name: **HDR-0472-SWS-BG-DR-C-520211**
Drawn: **RJJ** Checked/Approved: **JJ/JUG** Date: **27/03/24** Scale @ A1: **1:200**
Drawing Number: **HDR-0472-SWS-BG-DR-C-520211** Revision: **P16**

© THIS DRAWING IS THE COPYRIGHT PROPERTY OF HDR AND IS THEREFORE CONFIDENTIAL AND MUST NOT BE LENT, COPIED, REPRODUCED IN ANY WAY WHATSOEVER WITHOUT WRITTEN PERMISSION.

NOTES:

1. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
2. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
4. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025



EC3 ENERGY CENTRE

SSL:31.000

NORTH HYDE GARDENS

EC2 E
S

LEGEND

PLANNING BOUNDARY	
PHASE ONE CONSTRUCTION BOUNDARY	
EXISTING SURFACE WATER	
EXISTING PRIVATE FOUL WATER	
EXISTING PUBLIC FOUL WATER	
PROPOSED SURFACE WATER	
PROPOSED BACK DROP	
PROPOSED FOUL WATER	
EXISTING THAMES VALLEY SEWER	
PERMEABLE PAVING CONNECTIONS	
RAINWATER & CHANNEL CONNECTIONS (RWP01.XX)	
DRAINAGE CHANNEL (CH01.XX, FWCH01.XX)	
SOIL VENT PIPE & FLOOR GULLY CONNECTIONS (SVP01.XX, FG01.XX)	
GULLY CONNECTION (GU01.XX)	
EXISTING GULLY CONNECTION (EXGU01.XX)	
SEWER NETWORK TO BE ABANDONED	
SWALE (SL01.XX)	
FILTRATION TRENCH (FT01.XX)	
LAND DRAIN (REFER DETAILS)	
SETTING OUT POINTS FOR SWALE, CHANNELS, TANKS	

NORTH HYDE GARDENS

Gantry

SW TO DISCHARGE TO PERMEABLE COURSE GRADE AGGREGATE LAYER OF POROUS PAVING

P10	STAGE 4 ISSUE	08/11/24
P09	STAGE 4 ISSUE	14/06/24
P08	STAGE 4 ISSUE	27/03/24
P07	STAGE 4 ISSUE	05/03/24
P06	STAGE 4 ISSUE	20/12/23
P05	STAGE 4 ISSUE	25/10/23
P04	STAGE 4 ISSUE	04/05/23
P03	STAGE 4 ISSUE	24/02/23
P02	STAGE 4 ISSUE	15/02/23
P01	STAGE 3 ISSUE	16/12/22
Rev	Description	Date

Drawing Status: FOR APPROVAL Suitability: S4

HDR
4TH FLOOR
KNOLLYS HOUSE
17 ADDINGTON ROAD
CROXTHWAITE ROAD
UNITED KINGDOM
t: +44 (0) 20 8763 5900
e: info@drinc.com
w: www.drinc.com

Client: SWEET PROJECTS
Architect: NWA

Project: UNION PARK

Title: BLOCK 2
BELOW FINISHED GROUND LEVEL
FOUL AND SURFACE DRAINAGE
LAYOUT, SHEET 2 OF 4

HDR Project Number: 10274713


Cad File Name: HDR-0472-SWS-BG-DR-C-520212

Drawn: RJJ Chkd/Appd: JJ/JUG Date: 08/11/24 Scale @ A1: 1:200


Drawing Number: HDR-0472-SWS-BG-DR-C-520212 Revision: P10


NOTES:

1. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
2. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
4. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025




KEYPLAN






NORTH GANTRY

SCALE 1:100



SOUTH GANTRY

SCALE 1:100



DRAINAGE CHANNEL SECTION

SCAI

LEGEND

PLANNING BOUNDARY	
PHASE ONE CONSTRUCTION BOUNDARY	
EXISTING SURFACE WATER	 EX-SW  EX-SW  EX-SW
EXISTING PRIVATE FOUL WATER	 EX-FW  EX-FW  EX-FW
EXISTING PUBLIC FOUL WATER	 EX-FW  EX-FW  EX-FW
PROPOSED SURFACE WATER	
PROPOSED BACK DROP	 BD
PROPOSED FOUL WATER	
EXISTING THAMES VALLEY SEWER	 TVS
PERMEABLE PAVING CONNECTIONS	 PP01.XX
RAINWATER & CHANNEL CONNECTIONS (RWP01.XX)	 RWP01.XX
DRAINAGE CHANNEL (CH01.XX, FWCH01.XX)	 CH  CH  CH
SOIL VENT PIPE & FLOOR GULLY CONNECTIONS (SVP01.XX, FG01.XX)	
GULLY CONNECTION (GU01.XX)	

1	STAGE 4 ISSUE	14/05/24
v	Description	Date
ng Status:	Suitability:	
FOR APPROVAL		S4

TH FLOOR
MOLLYS HOUSE
ADDISCOMBE ROAD
ROYDON, CR0 6SR
UNITED KINGDOM
+44 (0) 20 8763 5900
info@hdrinc.com

SWEET PROJECTS

ect:

NWA


BLOCK 2 BELOW FINISHED GROUND LEVEL GANTRY DRAINAGE LAYOUT

Journal of Management


Project Number: **10274713**

File Name: HDR-0472-SWS-BG-DR-C-520215			
Chkd/Appd:	Date:	Scale @ A1:	
AC	JJ/UG	14/05/24	1:100
Drawing Number:			Revision:


DR-0472-SWS-BG-DR-C-520215 P01




TYPICAL MANHOLE DETAIL - TYPE A1




TYPICAL MANHOLE DETAIL - TYPE B




PLAN



SUMP MANHOLE DETAIL



RECTANGULAR PRECAST MANHOLE - TYPE 3



PLAN

© THIS DRAWING IS THE COPYRIGHT PROPERTY OF HDR AND IS THEREFORE CONFIDENTIAL AND MUST NOT BE LENT, COPIED, REPRODUCED IN ANY WAY WHATSOEVER WITHOUT WRITTEN PERMISSION.

NOTES:

1. THIS DRAWING MUST NOT BE USED FOR CONSTRUCTION OR INSTALLATION PURPOSES UNLESS WRITTEN APPROVAL TO DO SO.
2. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
3. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
4. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
5. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025

P02	STAGE 4 ISSUE	15/02/23
P01	STAGE 3 ISSUE	16/12/22
Rev	Description	Date

Drawing Status: **FOR APPROVAL** Suitability: **S4**



Client: **SWEET PROJECTS**

Architect: **NWA**

Project: **UNION PARK**

Title: **BLOCK 2**
BELLOW FINISHED GROUND LEVEL
DRAINAGE TYPICAL DETAILS
SHEET 1 OF 5

HDR Project Number: **10274713**


Cad File Name: **HDR-0472-SWS-BG-DR-C-520501**

Drawn: **RJ/HJ** Checked/Approved: **JJ/JUG** Date: **15/02/23** Scale @ A1: **AS SHOWN**


Drawing Number: **HDR-0472-SWS-BG-DR-C-520501** Revision: **P02**

NOTES:


1. THIS DRAWING MUST NOT BE USED FOR CONSTRUCTION OR INSTALLATION PURPOSES UNLESS WRITTEN APPROVAL TO DO SO.
2. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
3. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
4. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
5. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025




TYPICAL VERTICAL BACKDROP DETAIL



PIPES CROSSING THROUGH PILE CAP




INTERNAL STACK CONNECTIONS





BEDDING BENEATH AND AT THE SIDES OF THE PIPE TO BE WELL COMPAKTED. THE FIRST 300mm OF FILL ABOVE THE CROWN OF THE PIPE IS TO BE LIGHTLY TAMPED BY HAND. MECHANICAL COMPAKCTION MAY BE USED ONLY ABOVE THIS LEVEL. GEOTEXTILES MAY BE USED WHERE DIRECTED OR APPROVED BY THE ENGINEER TO CONTAIN BEDDING MATERIAL IN CERTAIN SOILS E.G. RUNNING SAND IN VERY WET CONDITIONS, WHERE DIRECTED OR APPROVED BY THE ENGINEER A TEMPORARY LAND DRAIN MAY BE LAID WITHIN THE GRANULAR BED.

GRANULAR BEDDING FOR FLEXIBLE PIPES

CLASS 8 BEDDING




PLAN



SECTION

CONCRETE SURROUND SHALL BE PROVIDED WHERE THE DISTANCE BETWEEN THE SOFFIT OF THE LOWER DRAIN AND THE BARREL OF THE HIGHEST DRAIN IS LESS THAN 300mm.

PIPE TO PIPE CROSSOVER




DRAIN SLEEVE/DUCT TO BE LOCATED WHOLLY WITHIN THE MIDDLE THIRD OF THE FOUNDATION DEPTH. THE ENGINEER (HDR) IS TO BE ADVISED IF THIS IS NOT POSSIBLE. IN NORMAL SOIL CONDITIONS THE SLEEVE/DUCT IS TO GIVE A 50mm CLEARANCE ALL ROUND THE OUTSIDE OF THE DRAIN PIPE (THIS MAY BE ACHIEVED BY LIGHTLY PACKING THE SPACE WITH COMPRESSIBLE FILLER MATERIAL).

DRAINS THROUGH FOUNDATIONS

P02	STAGE 4 ISSUE	15/02/23
P01	STAGE 3 ISSUE	16/12/22
Rev	Description	Date

Drawing Status: FOR APPROVAL Suitability: S4



Client: SWEET PROJECTS
Architect: NWA

Project: UNION PARK


Title: BLOCK 2
BELOW FINISHED GROUND LEVEL
DRAINAGE TYPICAL DETAILS
SHEET 2 OF 5

HDR Project Number: 10274713

Cad File Name: HDR-0472-SWS-BG-DR-C-520502


Drawn: RJ/HA Chkd/Appd: JJ/JUG Date: 15/02/23 Scale @ A1: 1:20

Drawing Number: HDR-0472-SWS-BG-DR-C-520502 Revision: P02




TYPICAL INSPECTION CHAMBER DETAIL - TYPE E

DEPTH FROM COVER LEVEL TO SOFFIT OF PIPE UP TO 3m FLEXIBLE MATERIAL CONSTRUCTION FOR USE IN AREAS SUBJECT TO VEHICLE LOADING



INTERCEPTOR VENT PIPES




TYPICAL SWALE SECTION

INTERNAL FG-06 FLOOR GULLY PLAN VIEW


CONNECTIONS SHOWN INDICATIVELY AND WILL NEED TO BE SET OUT AND COORDINATED WITH MEP ENGINEER

INTERNAL STANDPIPE GULLY




INTERNAL FIRE WATER / FLOOR GULLY

INTERNAL FG-06 FLOOR GULLY - SECTION




SECTION



PLAN

POLYPROPYLENE INSPECTION CHAMBER

DEPTH FROM COVER LEVEL TO SOFFIT OF PIPE UP TO 1.2m



RODDING EYE

MARSHALLS PRECAST CONCRETE PERMEABLE PAVING TO BE LAID AS PER LANDSCAPE ARCHITECTS SPECIFICATION
WASHED 6mm AGGREGATE (SEE TABLE 2 ON DRAWING HDR-0472-SEW-XX-TN-C-95080), 50mm DEPTH.

OPEN GRADED CRUSHED STONE AS PER TABLE 2 ON DRAWING HDR-0472-SEW-XX-TN-C-95080 OR APPROVED ALTERNATIVE.

TERRAM 1000 GEOTEXTILE MATERIAL 225mm DIAMETER PERFORATED DRAIN


IMPERVIOUS MEMBRANE BROUGHT UP TO TOP OF HAUNCHED KERB AND CUT OFF FLUSH WITH SURFACE OF POROUS PAVING

BASE COURSE 125mm THICK DENSE BASE ASPHALT CONCRETE IN ACCORDANCE WITH SPECIFICATION FOR HIGHWAYS WORKS CLAUSE 906. NOMINAL AGGREGATE SIZE 32mm, 100 / 150 REC. LAID & COMPACTED TO CLAUSE 903. TO BE CORED WITH 100mm Ø HOLES ON A 750mm ORTHOGONAL GRID. THE HOLES SHOULD BE FILLED WITH WASHED 6mm AGGREGATE (SEE TABLE 2), 50mm DEPTH.


INVERT LEVEL (IL) OF SUBBASE NOT TO REFLECT SURFACE LEVEL. FOR SUBBASE LEVELS PLEASE REFER TO LEVEL STRATEGY LAYOUT.

LAND DRAIN DETAIL

FOR DETAILED TYPICAL SECTION THROUGH LINED POROUS ROAD PLEASE REFER TO HIGHWAYS CONSTRUCTION DETAILS DRAWING NUMBER HDR-0472-SEW-GL-DR-C-920504




SECTION



TYPICAL MANHOLE DETAIL - TYPE C

(SCALE 1:20)



ACO MULTIDRAIN M200D 0.0 IN CONCRETE PAVEMENT

FOR FURTHER DETAILS PLEASE REFER TO THE MANUFACTURER DRAWINGS AND INFORMATION AVAILABLE ON THEIR WEBSITE.

LOAD CLASS	D400		
MINIMUM DIMENSIONS (mm)	X	Y	Z
	200	FULL CHANNEL HEIGHT (LESS Y2 WHERE APPLICABLE)	200

P04	STAGE 4 ISSUE	16/02/24
P03	STAGE 4 ISSUE	24/02/23
P02	STAGE 4 ISSUE	15/02/23
P01	STAGE 3 ISSUE	16/12/22
Rev	Description	Date

Drawing Status:	FOR APPROVAL	Suitability:
		S4

HDR
4TH FLOOR
KNOLLYS HOUSE
17 ADDINGTON ROAD
CROYDON CR0 6SR
UNITED KINGDOM
t: +44 (0) 20 8763 5900
e: info@drinc.com
w: www.drinc.com

Client: SWEET PROJECTS

Architect: NWA

Project: UNION PARK

Title: BLOCK 2
BELOW FINISHED GROUND LEVEL
DRAINAGE TYPICAL DETAILS
SHEET 3 OF 5

HDR Project Number: 10274713

Cad File Name: HDR-0472-SWS-BG-DR-C-520503


Drawn: AC Chkd/Appd: JJ/JUG Date: 16/02/24 Scale @ A1: AS SHOWN

Drawing Number: HDR-0472-SWS-BG-DR-C-520503 Revision: P04

© THIS DRAWING IS THE COPYRIGHT PROPERTY OF HDR AND IS THEREFORE CONFIDENTIAL AND MUST NOT BE LENT, COPIED, REPRODUCED IN ANY WAY WHATSOEVER WITHOUT WRITTEN PERMISSION.

NOTES:



1. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
2. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT THE WORKS.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
4. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025



© THIS DRAWING IS THE COPYRIGHT PROPERTY OF HDR AND IS THEREFORE CONFIDENTIAL AND MUST NOT BE LENT, COPIED, REPRODUCED IN ANY WAY WHATSOEVER WITHOUT WRITTEN PERMISSION.

NOTES:

1. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
2. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
4. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025




END ELEVATION

TWIN RAINWATER HARVESTING TANK
NOMINAL CAPACITY 25000 LITRES EACH

P03	STAGE 4 ISSUE	03/07/24
P02	STAGE 4 ISSUE	15/02/23
P01	STAGE 3 ISSUE	16/12/22
Rev	Description	Date
Drawing Status:		Suitability:
FOR APPROVAL		S4
		4TH FLOOR KNOLLYS HOUSE 17 ADDINGTON ROAD CROYDON CR0 6SR UNITED KINGDOM t: +44 (0) 20 8763 5900 e: info@drinc.com w: www.drinc.com
Client:		SWEET PROJECTS
Architect:		NWA
Project:		UNION PARK
Title:		BLOCK 2 BELOW FINISHED GROUND LEVEL DRAINAGE TYPICAL DETAILS SHEET 4 OF 5
HDR Project Number:		10274713
Cad File Name:		HDR-0472-SWS-BG-DR-C-520504
Drawn:	Chkd/Appd:	Date: 03/07/2024 Scale @ A1: AS SHOWN
Drawing Number:	Revision:	
HDR-0472-SWS-BG-DR-C-520504		P03

NOTES:

1. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
2. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
3. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S, REPORTS AND SPECIFICATIONS.
4. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025



NOTES:

1. THIS DRAWING MUST NOT BE USED FOR CONSTRUCTION OR INSTALLATION PURPOSES UNLESS WRITTEN APPROVAL TO DO SO.
2. DO NOT SCALE OFF THIS DRAWING. ALWAYS WORK TO NOTED DIMENSION.
3. ALL DIMENSIONS MUST BE VERIFIED ON SITE BEFORE COMPLETING SHOP DRAWINGS OR SETTING OUT OF THE WORKS.
4. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER DISCIPLINE'S DRAWINGS, REPORTS AND SPECIFICATIONS.
5. REFER TO GENERAL NOTES DRAWING HDR-0472-SWS-XX-TN-C-000025

SURFACE WATER MANHOLE AND PIPE SCHEDULE																
REF NO.	APPROXIMATE COVER LEVEL (m)	INVERT LEVEL (m)	PIPE INVERT LEVELS (m)	DEPTH (m)	EASTING	NORTHING	INTERNAL CHAMBER SIZE (mm)	COVER LOADING TO BS EN 124	RECESSED	LOCKED	SEALED	VENTED	ACCESS COVER OPENING (mm)	DOWNSTREAM PIPE DIAMETER (mm)	DOWNSTREAM PIPE GRADIENT	REMARKS
SW02.01	30.772	27.696	Out = 27.696	3.08	510406.955	179372.360	1800	D400	YES	YES	YES	NO	600x600	600	1:10	TYPE A1
SW02.03	30.910	29.983	In = 30.038 from CH02.02 In = 29.988 from CH02.01 Out = 29.988	0.93	510407.897	179368.439	600	D400	NO	YES	YES	NO	600x600	150	1:10	PPIC
SW02.04(P1)	30.884	30.421	In = 28.975 from SW02.03 Out = 29.875	0.46	510409.907	179368.467	0	D400	YES	YES	YES	NO	600x600	150	1:10	PETROL INTERCEPTOR
SW02.05(RWH)	31.186	30.040	In = 30.140 from RW02.07 Out = 30.040	1.15	510409.981	179356.163	0	D400	NO	YES	YES	NO	600x600	150	1:10	RWH
SW02.06	30.990	28.758	In = 28.808 from GBL UP2-00-RWP-02 In = 28.808 from GBL UP2-00-RWP-01 Out = 28.758	2.23	510439.430	179362.732	450	D400	NO	YES	YES	NO	450x450	150	1:56	TYPE E
SW02.07	30.980	28.644	In = 28.719 from GBL UP2-00-RWP-03 In = 28.744 from SW02.08 In = 28.659 from SW02.06 Out = 28.644	2.34	510444.418	179362.768	600	D400	NO	YES	YES	NO	600x600	225	1:51	TYPE E
SW02.08	30.973	28.764	In = 28.814 from GBL UP2-00-RWP-05 In = 28.744 from GBL UP2-00-RWP-04 Out = 28.764	2.21	510447.484	179362.797	450	D400	NO	YES	YES	NO	450x450	150	1:10	TYPE E
SW02.09(RWH)	30.960	30.316	In = 28.612 from SW02.07 Out = 28.580 Out = 28.541	0.64	510444.436	179364.376	0	D400	NO	YES	YES	NO	600x600	225 150	1:121	RWH
SW02.10(RWH)	30.941	30.331	In = 28.473 from SW02.09(RWH) Out = 28.376	0.61	510452.639	179364.496	0	D400	NO	YES	YES	NO	600x600	225	1:24	RWH
SW02.11	30.925	27.615	In = 27.615 from SW02.10(RWH) Out = 27.615	3.31	510471.186	179365.406	1200	D400	NO	YES	YES	NO	600x600	225	1:149	TYPE A1
SW02.12	31.000	30.095	In = 30.095 from CH02.15 Out = 30.095	0.90	510424.907	179205.900	600	D400	YES	YES	YES	NO	600x600	225	1:40	PPIC
SW02.13	31.173	30.114	In = 28.946 from CH02.16 In = 29.946 from SW02.12 Out = 29.946	1.06	510430.877	179206.003	600	D400	YES	YES	YES	NO	600x600	225	1:30	PPIC
SW02.17	30.417	28.673	In = 29.426 from PP02.07 Out = 28.670 Out = 28.671	1.74	510506.981	179244.921	600	D400	YES	YES	YES	NO	600x600	225 150	1:100	TYPE E
SW02.22(P1)	30.105	28.859	In = 28.659 from SW02.25 Out = 28.859	0.36	510412.813	179305.517	0	D400	YES	YES	YES	NO	600x600	150	1:40	PETROL INTERCEPTOR
SW02.23	30.284	28.620	In = 28.620 from SW02.22(P1) Out = 28.620	1.66	510412.977	179295.983	600	D400	NO	YES	YES	NO	600x600	150	1:21	TYPE E
SW02.24	30.381	29.101	In = 29.101 from PC2.6 Out = 29.101	1.28	510454.199	179190.724	1200	D400	YES	YES	YES	NO	750x750	225	1:94	TYPE C
SW02.25	30.092	28.933	In = 28.933 from CH02.14 In = 29.561 from CH02.13 Out = 28.933	1.16	510412.771	179308.494	600	D400	YES	YES	YES	NO	600x600	150	1:40	PPIC
SW02.26	30.362	29.270	In = 29.270 from In = 29.327 from PC-01 Out = 29.270	1.09	510478.336	179203.775	1350	D400	YES	YES	YES	NO	1200x750	225	1:77	TYPE B
SW02.27	30.404	27.742	In = 28.388 from SW02.23 Out = 27.742	2.66	510410.296	179291.774	1800	D400	YES	YES	YES	NO	600x600	600	1:600	TYPE B
SW02.28	30.622	27.728	In = 27.728 from SW02.27 In = 28.138 from PC2.1 Out = 27.728	2.89	510415.353	179285.083	1800	D400	YES	YES	YES	NO	600x600	600	1:450	TYPE B
SW02.29	30.851	27.350	In = 27.350	3.50	510440.632	179288.480	1200	D400	NO	YES	YES	NO	600x600	450	1:213	TYPE A
SW02.30	30.535	27.250	In = 27.250 from SW02.29 In = 28.869 from GU01.01 In = 29.869 from	3.29	510461.957	179238.744	1200	D400	NO	YES	YES	NO	600x600			TYPE A

SURFACE WATER RWP, GULLY & CHANNEL CONNECTION SCHEDULE							
REFERENCE	COVER LEVEL (m)	PIPE INVERT LEVELS (m)	DOWNSTREAM PIPE DIAMETER (mm)	DOWNSTREAM PIPE GRADIENT	EASTING	NORTHING	SPECIAL REQUIREMENTS
CH02.01	30.854	Out = 30.006	150	1:149	510406.230	179370.545	SETTING OUT TBC BY OTHERS
CH02.02	30.826	Out = 30.107	150	1:40	510409.676	179370.541	SETTING OUT TBC BY OTHERS
CH02.03	31.275	Out = 28.943	150	1:150	510423.465	179360.126	SETTING OUT TBC BY OTHERS
CH02.04	31.275	Out = 28.963	150	1:150	510435.264	179360.333	SETTING OUT TBC BY OTHERS
CH02.05	31.275	Out = 28.960	150	1:150	510449.516	179360.579	SETTING OUT TBC BY OTHERS
CH02.06	31.275	Out = 28.987	150	1:150	510464.408	179360.816	SETTING OUT TBC BY OTHERS
CH02.09	31.275	Out = 27.962	150	1:80	510425.430	179286.736	SETTING OUT TBC BY OTHERS
CH02.10	31.275	Out = 27.934	150	1:80	510436.496	179286.937	SETTING OUT TBC BY OTHERS
CH02.11	31.275	Out = 29.760	150	1:80	510456.260	179287.294	SETTING OUT TBC BY OTHERS
CH02.12	31.275	Out = 27.850	150	1:80	510471.930	179287.578	SETTING OUT TBC BY OTHERS
CH02.13	30.98	Out = 29.609	150	1:71	510409.523	179309.533	SETTING OUT TBC BY OTHERS
CH02.14	30.088	Out = 28.961	150	1:40	510412.932	179309.583	SETTING OUT TBC BY OTHERS
CH02.15	31.100	Out = 30.171	225	1:84	510424.906	179212.295	SETTING OUT TBC BY OTHERS
CH02.16	31.100	Out = 30.159	225	1:30	510430.874	179212.398	SETTING OUT TBC BY OTHERS
CH02.17	31.150	Out = 30.584	150	1:52	510426.767	179200.561	SETTING OUT TBC BY OTHERS
FG02.01	30.670	Out = 28.251	150	1:40	510475.497	179295.407	SETTING OUT TBC BY OTHERS
FG02.02	30.951	Out = 28.063	150	1:100	510471.914	179288.679	SETTING OUT TBC BY OTHERS
PP02.05	30.665	Out = 30.007	150	1:40	510410.911	179376.553	SETTING OUT TBC BY OTHERS
PP02.06	30.303	Out = 29.920	150	1:40	510471.279	179188.167	SETTING OUT TBC BY OTHERS
PP02.08	30.600	Out = 28.262	150	1:40	510410.401	179284.922	SETTING OUT TBC BY OTHERS
PP02.10	30.3						

FOUL WATER SVP, GULLY & CHANNEL CONNECTION SCHEDULE						
REFERENCE	COVER LEVEL (m)	PIPE INVERT LEVELS (m)	DOWNSTREAM PIPE DIAMETER (mm)	DOWNSTREAM PIPE GRADIENT	SPECIAL REQUIREMENTS	
FG69A	31.300	Out = 30.600	150	1:40		
FG69B	31.300	Out = 30.551	150	1:40		
GBL-UP2-00-BRC-01	31.300	Out = 28.887	150	1:40		
GBL-UP2-00-BRC-02	31.300	Out = 30.325	150	1:40		
GBL-UP2-00-BRC-03	31.295	Out = 30.188	150	1:40		
GBL-UP2-00-BRC-04	31.300	Out = 30.490	150	1:40		
GBL-UP2-00-BRC-06	31.300	Out = 29.850	150	1:40		
GBL-UP2-00-CDS-01	31.289	Out = 29.779	150	1:37		
GBL-UP2-00-CDS-02	31.295	Out = 29.556	150	1:28		
GBL-UP2-00-CDS-03	31.300	Out = 29.637	150	1:25		
GBL-UP2-00-CDS-05	30.900	Out = 29.927	150	1:40		
GBL-UP2-00-FG-01	30.900	Out = 30.327	150	1:40		
GBL-UP2-00-FG-02	30.900	Out = 30.087	150	1:40		
GBL-UP2-00-FG-03	30.900	Out = 29.916	150	1:40		
GBL-UP2-00-FG-04	30.900	Out = 30.343	150	1:40		
GBL-UP2-00-FG-05	30.900	Out = 29.978	150	1:40		
GBL-UP2-00-FG-06	30.900	Out = 29.925	150	1:39		
GBL-UP2-00-FG-07	30.900	Out = 30.041	150	1:40		
GBL-UP2-00-FG-08	30.900	Out = 29.258	150	1:34		
GBL-UP2-00-FG-09	30.900	Out = 29.708	150	1:38		
GBL-UP2-00-FG-10	31.300	Out = 29.759	150	1:10		
GBL-UP2-00-FG-11	31.295	Out = 29.190	150	1:40		
GBL-UP2-00-FG-12	31.300	Out = 29.592	150	1:28		
GBL-UP2-00-FG-13	31.300	Out = 30.179	150	1:40		
GBL-UP2-00-FG-14	31.300	Out = 30.520	150	1:40		
GBL-UP2-00-FWG-01	31.300	Out = 29.985	150	1:40		
GBL-UP2-00-FWG-02	31.300	Out = 30.316	150	1:40		
GBL-UP2-00-FWG-03	31.300	Out = 30.266	150	1:40		
GBL-UP2-00-FWG-04	31.300	Out = 30.312	150	1:41		
GBL-UP2-00-FWG-05	31.300	Out = 30.761	150	1:40		
GBL-UP2-00-FWG-06	31.300	Out = 30.625	150	1:40		
GBL-UP2-00-FWG-07	31.300	Out = 30.620	150	1:40		
GBL-UP2-00-FWG-08	31.300	Out = 30.600	150	1:38		
GBL-UP2-00-FWG-09	31.300	Out = 30.568	150	1:40		
GBL-UP2-00-FWG-10	31.300	Out = 30.475	150	1:46		
GBL-UP2-00-FWG-11	31.300	Out = 30.473	150	1:40		
GBL-UP2-00-FWG-12	31.300	Out = 30.449	150	1:40		
GBL-UP2-00-FWG-13	31.300	Out = 30.427	150	1:40		
GBL-UP2-00-FWG-14	31.300	Out = 29.591	150	1:24		
GBL-UP2-00-FWG-15	31.300	Out = 29.435	150	1:8		
GBL-UP2-00-FWG-16	31.300	Out = 29.691	150	1:26		
GBL-UP2-00-FWG-17	31.300	Out = 29.794	150	1:44		
GBL-UP2-00-FWG-18	31.300	Out = 29.761	150	1:39		
GBL-UP2-00-FWG-19	31.300	Out = 29.327	150	1:7		
GBL-UP2-00-FWG-20	31.300	Out = 29.339	150	1:22		
GBL-UP2-00-FWG-21	31.300	Out = 29.338	150	1:21		
GBL-UP2-00-FWG-22	31.300	Out = 29.958	150	1:40		
GBL-UP2-00-FWG-23	31.300	Out = 29.421	150	1:19		
GBL-UP2-00-FWG-24	31.300	Out = 28.697	150	1:40		
GBL-UP2-00-FWG-25	31.300	Out = 28.489	150	1:40		
GBL-UP2-00-FWG-26	31.300	Out = 29.219	150	1:23		
GBL-UP2-00-FWG-27	31.300	Out = 29.163	150	1:21		
GBL-UP2-00-FWG-28	31.300	Out = 28.039	150	1:40		
GBL-UP2-00-FWG-29	31.300	Out = 29.366	150	1:40		
GBL-UP2-00-FWG-30	31.300	Out = 29.019	150	1:40		
GBL-UP2-00-FWG-31	31.300	Out = 29.052	150	1:40		
GBL-UP2-00-FWG-32	31.300	Out = 30.561	150	1:40		
GBL-UP2-00-FWG-33	31.300	Out = 30.495	150	1:40		
GBL-UP2-00-FWG-34	31.300	Out = 30.593	150	1:40		
GBL-UP2-00-FWG-35	31.300	Out = 30.481	150	1:40		
GBL-UP2-00-FWG-36	31.300	Out = 30.444	150	1:40		
GBL-UP2-00-FWG-37	31.300	Out = 29.810	150	1:40		
GBL-UP2-00-FWG-38	31.300	Out = 29.594	150	1:40		
GBL-UP2-00-FWG-39	31.300	Out = 29.888	150	1:40		
GBL-UP2-00-FWG-40	31.300	Out = 30.239	150	1:40		
GBL-UP2-00-FWG-41	31.300	Out = 30.069	150	1:40		
GBL-UP2-00-FWG-42	31.300	Out = 30.426	150	1:40		
GBL-UP2-00-FWG-43	31.300	Out = 29.650	150	1:40		
GBL-UP2-00-FWG-44	31.300	Out = 30.437	150	1:40		
GBL-UP2-00-FWG-45	31.300	Out = 29.351	150	1:76		
GBL-UP2-00-FWG-46	31.300	Out = 28.984	150	1:40		
GBL-UP2-00-FWG-47	31.300	Out = 28.897	150	1:40		
GBL-UP2-00-FWG-48	31.300	Out = 30.667	150	1:40		
GBL-UP2-00-FWG-49	31.300	Out = 29.738	150	1:40		
GBL-UP2-00-FWG-50	31.300	Out = 30.312	150	1:40		
GBL-UP2-00-FWG-51	31.300	Out = 29.671	150	1:29		
GBL-UP2-00-FWG-52	31.300	Out = 30.305	150	1:40		
GBL-UP2-00-FWG-53	31.300	Out = 30.135	150	1:40		
GBL-UP2-00-FWG-55	31.300	Out = 29.811	150	1:40		
GBL-UP2-00-FWG-56	31.300	Out = 29.745	150	1:40		
GBL-UP2-00-FWG-57	31.300	Out = 29.625	150	1:40		
GBL-UP2-00-FWG-59	31.300	Out = 30.390	150	1:40		
GBL-UP2-00-FWG-62	31.300	Out = 30.324	150	1:40		
GBL-UP2-00-FWG-63	31.300	Out = 30.237	150	1:40		
GBL-UP2-00-FWS-01	30.900	Out = 29.927	150	1:43		
GBL-UP2-00-FWS-02	30.900	Out = 29.188	150	1:40		
GBL-UP2-00-FWK-01	30.900	Out = 30.246	150	1:40	STAND PIPE	

FOUL WATER SVP, GULLY & CHANNEL CONNECTION SCHEDULE						
REFERENCE	COVER LEVEL (m)	PIPE INVERT LEVELS (m)	DOWNSTREAM PIPE DIAMETER (mm)	DOWNSTREAM PIPE GRADIENT	SPECIAL REQUIREMENTS	
GBL-UP2-00-SPK-02	30.900	Out = 30.341	150	1:40	STAND PIPE	
GBL-UP2-00-SPK-03	30.900	Out = 29.953	150	1:40	STAND PIPE	
GBL-UP2-00-SPK-04	30.900	Out = 29.878	150	1:40	STAND PIPE	
GBL-UP2-00-SVP-01	31.300	Out = 29.508	150	1:40		
GBL-UP2-00-SVP-02	31.300	Out = 30.285	150	1:40		
GBL-UP2-00-SVP-03	31.300	Out = 30.597	150	1:40		

Technical Submittal Form



Please use this form as a 'front sheet' for all technical submittals. Ensure you include as much information as possible to receive a status. Where you provide an attachment, please reference the technical submittal ref. in the 'Subject/Title' field. and refer to the attachment in the 'Description' field.

Form Title Ref.:

TOU-0472-UP2-BG-TS-X-0038

Subject / Title:

UP2 Rain Water Harvesting Tanks 2No

Description (example: product name; location; specification details; supplier; etc.):

2No 25000litre Rain water harvesting tanks for UP2 north from Edincare. Spec R18 310 Pump Info On next Tech Sub

Is the proposal specification compliant?

Yes




Is the proposal an alternative to specification?

No

Details of reason for deviation from specification / alternative to specification:

WaterGuard Commercial (25,000 litres)

SW02.09



CUSTOMER APPROVAL	
Date	
Approved by (print)	
Signed	

PROJECT ADDRESS	PROJECT UNION (SW02.09)				
CLIENT	TOUREEN CONTRACTORS				
PRODUCT NAME	WATERGUARD COMMERCIAL 25,000 LITRES				
CHAMBER WEIGHT	TBC	TOLERANCE	+/-3%	DRAWN BY	DM
CAPACITY (LITRES)	25,000	DATE	01/09/23	SCALE	NTS

DIMENSIONS ARE SUBJECT TO DIMENSIONAL TOLERANCES.
If critical, check physically prior to installation.

Our policy is one of continuous product improvement, we reserve the right to change specifications and prices without prior notice. All information is given in good faith. No responsibility can be accepted for errors, omissions or incorrect assumptions. © Copyright 2023 Omni Pump International Ltd t/a Edincare Pumps. All rights reserved.

WATER TABLE & BURIAL DEPTH
The customer must check chamber specification is compatible with ground water table level (in winter) and burial depth. Contact Edincare if in doubt.


PLEASE NOTE THAT THIS DOCUMENT MUST BE READ INCONJUNCTION WITH THE INSTALLATION & OPERATING GUIDELINES.
DRAWING NOT TO SCALE.

01442 211554
info@edincare.com
www.edincare.com
Twitter EdincarePumps


PU/TC/WGC/SW02.09/010923/1.1

WaterGuard Commercial (25,000 litres)

SW02.10



CUSTOMER APPROVAL	
Date	
Approved by (print)	
Signed	

PROJECT ADDRESS	PROJECT UNION (SW02.10)				
CLIENT	TOUREEN CONTRACTORS				
PRODUCT NAME	WATERGUARD COMMERCIAL 25,000 LITRES				
CHAMBER WEIGHT	TBC	TOLERANCE	+/-3%	DRAWN BY	DM
CAPACITY (LITRES)	25,000	DATE	01/09/23	SCALE	NTS

DIMENSIONS ARE SUBJECT TO DIMENSIONAL TOLERANCES.
If critical, check physically prior to installation.

Our policy is one of continuous product improvement, we reserve the right to change specifications and prices without prior notice. All information is given in good faith. No responsibility can be accepted for errors, omissions or incorrect assumptions. © Copyright 2023 Omni Pump International Ltd t/a Edincare Pumps. All rights reserved.

WATER TABLE & BURIAL DEPTH
The customer must check chamber specification is compatible with ground water table level (in winter) and burial depth. Contact Edincare if in doubt.

PLEASE NOTE THAT THIS DOCUMENT MUST BE READ IN CONJUNCTION WITH THE INSTALLATION & OPERATING GUIDELINES.
DRAWING NOT TO SCALE.

01442 211554
info@edincare.com
www.edincare.com
Twitter EdincarePumps


PU/TC/WGC/SW02.10/010923/1.1

Technical Submittal Form



Please use this form as a 'front sheet' for all technical submittals. Ensure you include as much information as possible to receive a status. Where you provide an attachment, please reference the technical submittal ref. in the 'Subject/Title' field. and refer to the attachment in the 'Description' field.

Form Title Ref.:

TOU-0472-UP2-BG-TS-X-0039

Subject / Title:

Petrol Interceptors

Description (example: product name; location; specification details; supplier; etc.):

Klargester NSFP006, UP2 West, R12 421 with Darcy Separator Monitor Type 14300 - AS supplied in Phase 1

Is the proposal specification compliant?

Yes

Is the proposal an alternative to specification?

No

Details of reason for deviation from specification / alternative to specification:



**MAINS KLARGESTER
SEPARATOR ALARM
INSTALLATION &
OPERATIONS MANUAL**

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Contents

IMPORTANT	3
General Description	4
General Operation.....	4
Changing Factory Settings	4
Alarm Type.....	4
Check Interval	5
Testing the Probe Sensors.....	5
Installation	5
Control Unit	5
Probes (High Oil & High Liquid Level Probes).....	5
Silt Probe	5
Cable Distribution Box	6
Connection to Control Unit.....	6
Using a Junction Box	6
Maintenance and Repair	6
Technical Information	7
Electrical	7
Apparatus Supply and I/O Parameters.....	7
Probe Cables.....	7
Mechanical	7
Probe Enable Jumper Links.....	8
Probe Cable Terminals	9
Flashing Beacon Wiring.....	9
Accessories.....	10

14300 Klärgester Separator Alarm

Installation, Operation & Maintenance

Name and Address of Manufacturer	Darcy Products Limited Brook House Larkfield Trading Estate New Hythe Lane, Larkfield Kent ME20 6GN
European Directive	94/9/EC
Equipment Name and Type	Separator Monitor Type 14300
Certificate Number	Baseefa 08ATEX0110/2 IECEx BAS 11.0095
Specific Marking of Explosion Protection	[Ex ia] IIC (-20°C ≤ Ta ≤ +50°C)
ATEX Directive Marking	Ex II (1) G
Notified Body	Baseefa 1180 Buxton UK
CE Mark with Notified Body Number	CE ₁₁₈₀
Harmonised Standards Used	EN 60079-0:2009 EN 60079-11:2012
Serial Number and Year of Manufacture	Displayed underneath the control unit
On behalf of the above named company, I declare that, on the date the equipment accompanied by this declaration is placed on the market, the equipment conforms with all technical and regulatory requirements of the above listed directives.	
 P.G. Bowden - Director	

IMPORTANT

Note: In all cases good, standard electrical practice should be followed, and the installation must conform to the appropriate local code of practice – e.g. BS EN 60079-25 in the UK. In essence, the installation must be such that the intrinsic safety is not compromised by: - exposure to risk of mechanical damage, unauthorised modification or interference, exposure to moisture, dust and foreign bodies, excessive heat, invasion of intrinsically safe circuit by other electrical equipment or circuitry. (See Note in installation section)

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

General Description

The standard system is supplied complete with an intrinsically safe control unit together with a high oil probe. The control unit is capable of monitoring up to 3 probe units, displaying their current status via a 2 x 16 display. The output relay enables this status to be signalled to a remote location or activate a beacon if required.

General Operation

The Control Unit monitors the condition of the connected probe units by checking their condition every 30 minutes¹, their current status is displayed on the display located on the front of the unit. If an alarm condition is detected, a warning message is displayed followed by notification of the alarm condition detected, e.g. ***HAZARD ALERT* High Oil Alarm**, the output relay becomes de-energised and the internal buzzer is audible.

The unit then gives the option, via the display, to accept/acknowledge the alarm. On doing so, the output relay energises, the buzzer is muted and the display instructs the user to take the appropriate action, e.g. empty the separator. After the separator has been emptied and refilled with water, the control unit re-scans the probe sensors attached and presuming no alarm condition is detected, **'All Correct'** will be displayed. If the push button is pressed before the separator has been emptied, or it has been emptied but not refilled with water, then the control simply scans the probe sensor(s) and reverts to the alarm condition. Please note the output relay is *de-energised* on detection of any alarm condition or mains failure.

Changing Factory Settings

Alarm Type

The factory setting is STD (standard), this is where the output relay de-energises upon fault detection and energises upon acceptance of the fault.

Alarm Type EXT (Extended) allows the relay to remain de-energised until all alarm conditions become normal.

To enter the "Set Up" mode, firstly remove power from the unit. Whilst holding down the Push Switch, power up the unit keeping the Push Switch depressed, after about 10 seconds the screen will display "Set Up", at this point release the Push Switch.

The display will now show Alarm Type: with a flashing cursor over STD, to change this function to EXT, press the Push Switch once.

¹ The unit is factory set to 30 minutes, but in extreme conditions, this can be manually changed from 2 to 60 minutes at one minute intervals. (see Changing Factory Settings)

Check Interval

Whilst still in the Set Up mode, power down and then power up the unit, the flashing cursor will now be next to Check Intvl: - by pressing the Push Switch, the time can be altered in increments of 1 minute between 2 and 60.

To exit the Set Up mode at any time, hold the Push Switch whilst powering down and then power up again before releasing the Switch, this will return to the main screen sequence.

Testing the Probe Sensors

The probe interrogation function can be activated at any time by simply pressing the push switch.

Installation

This product has been designed and certified as being intrinsically safe. It is of paramount importance, that the unit should not be modified in any way and the installation be carried out by an approved installer, in accordance with the Environment Agency guidelines (PPG3). Any deviation from this could invalidate the certification warranty and render the unit unsafe for its intended use.

Control Unit

Refer to Table 4 on page 7 for required cable specifications.

The control unit must be positioned in a non-hazardous area. For all wiring details, refer to Figure 1, Table 5 and Table 6 on page 9.

Probes (High Oil & High Liquid Level Probes)

The high oil probe is to be installed in the separator tank such that the float housing is below the static liquid level. If a high liquid probe is required, this needs to be installed such that the float switch housing is located above the static liquid level. Both probe cables can be secured inside the neck of the separator using a probe cord guide.

Please note the distance above or below the static liquid level will be determined by the type, style and/or size of separator, this information can be obtained from the separator manufacturer. However, as a general *rule of thumb*, the high liquid level probe should be placed 300mm above the static liquid level and the high oil probe 150mm below.

Due to the varying neck lengths (turrets) that occur within each separator, each normal probe unit is fitted with 5 metres of cable.

Silt Probe

The probe is suspended in the separator to a pre determined depth and the cable can be secured to the neck of the separator using a probe cord guide.

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Cable Distribution Box

It is advisable to connect the probe cables to a cable distribution box which should be fixed near to the top of the separator neck. The probe cable can then be terminated with a waterproof plug (provided with the distribution box). The plug is then connected to the bulkhead socket (provided with the distribution box). A cable must then be laid to connect the distribution box and the control unit. The type of connection cable required will be dependent on the environment it is used in, the route taken and maximum allowable cable capacitance and inductance (see cable parameters in Table 4 on page 7).

After making the connections in the distribution box, it is advisable to spray the terminals with a conformal coating lacquer to prevent moisture ingress before finally sealing them with waterproof putty.

Connection to Control Unit

The Probe cable should be fed through the appropriate gland in the bottom right hand side of the control unit and connected to the terminals as instructed. The mains cable, and if used, any beacon or sounder cable, must be fed through the appropriate gland on the bottom left hand side of the control unit and connected to the terminals as instructed.

IMPORTANT NOTE: Under NO circumstances must the control unit casing be drilled to allow cable entry in any area(s) other than those already provided, as this would infringe the certification and therefore safety of the product.

Using a Junction Box

An intrinsically safe junction box should be used where incoming cable sizes have to be reduced to gain entry through the cable glands in the base of the control unit.

IMPORTANT NOTE: Under NO circumstances must mains and probe cable joints be made within the same junction box other than a junction box that is approved Intrinsically safe for such purpose, as this would infringe the certification and therefore safety of the installed system.

Maintenance and Repair

Due to the harsh environments which the probes can be subjected to, it is advised that they are inspected and cleaned with a damp cloth at regular intervals. The control unit does not contain user serviceable parts.

Technical Information

Electrical

Supply Voltage	230V $\pm 10\%$ 50Hz	
Input Current	Normal condition	41mA
	Alarm condition	40mA
Fusing	Primary (FS2)	T 315mA H 250V
	Secondary (FS3)	50mA (Baseefa approved)
Max probe cable length	200m (less if values in Table 4 would be exceeded)	
Relay Output	Volt-free SPCO contact	
	3A	
Panel rating	IP65	
Panel dimensions	180mm x 180mm x 60mm	

Table 1 – Electrical Specifications

Apparatus Supply and I/O Parameters

U_m	253Vrms
-------	---------

Table 2 – Mains Supply and Relay Contact Terminals (TB2 & TB3)

U_o	12.6V
I_o	87mA
P_o	273mW
C_i	0
L_i	0

Table 3 – Hazardous Area Terminals (TB1)

Group	Capacitance (μF)	Inductance (mH)	OR	L/R Ratio ($\mu\text{H}/\Omega$)
IIC	1.15	4.6	74	
IIB	7.4	18.7	298	
IIA	27	37.5	596	

Table 4 – TB1 Load Parameters

Probe Cables

The total capacitance and inductance of the cable used between the control unit and the probe must not exceed that shown in [Table 4](#).

Mechanical

Protection and/or screening of the cable should also be taken into account. The maximum length of cable between probe and control unit must not exceed 200 metres or less if the values in [Table 4](#) would be exceeded.

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Probe Enable Jumper Links




Figure 1 - Probe enable jumper links

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

To operate a probe, REMOVE appropriate jumper link

Probe Type	Remove Link
High Oil	OIL
High Liquid	LQD
Silt	SLT

Table 5 – Probe enable jumper links

Probe Cable Terminals

Probe Type	A	B	C	D	E	F	G	H
High Oil	BROWN	BLUE						
High Liquid			-	RED	BLUE			
Liquid (Optical)			BROWN	GREEN/YELLOW	BLUE			
Silt						BROWN	GREEN/YELLOW	BLUE

Table 6 - Probes cable wiring connection details

Flashing Beacon Wiring

The relay output terminals, TB2, may be used to operate a 230V flashing beacon when an alarm occurs. The beacon should be wired according to Table 7 and Table 8. Any commoning of live and neutral connections must be done externally to the unit's enclosure.

TB2 Terminal	Connect To
NO	No Connection
COM	TB3 Mains live
NC	Beacon Live Terminal

Table 7 – wiring from relay output to beacon

TB3 Mains Terminal	Connect To
L out	TB2 COM Terminal
N out	Beacon Neutral Terminal
E	Mains earth

Table 8 – wiring to beacon from relay output

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Accessories

	Part No.
High Oil Probe -----	14201
High Level Probe -----	14210
Silt Probe -----	14220
230 VAC Flashing Amber Beacon (Includes mounting bracket and glands) -----	14012
230 VAC Flashing Amber Beacon & Siren (Includes mounting bracket and glands) -----	14100
Probe Cord Guide -----	14103
Signal Distribution Box -----	14039
Intrinsically Safe Junction Box (Power & Probe) -----	14006

SEPARATORS

A RANGE OF FUEL/OIL SEPARATORS
FOR PEACE OF MIND



60 YEARS OF
1955-2015 Expertise &
Innovation



Separators

A RANGE OF FUEL/OIL SEPARATORS FOR PEACE OF MIND

Surface water drains normally discharge to a watercourse or indirectly into underground waters (groundwater) via a soakaway. Contamination of surface water by oil, chemicals or suspended solids can cause these discharges to have a serious impact on the receiving water.

The Environment Regulators, Environment Agency, England and Wales, SEPA, Scottish Environmental Protection Agency in Scotland and Department of Environment & Heritage in Northern Ireland, have published guidance on surface water disposal, which offers a range of means of dealing with pollution both at source and at the point of discharge from site (so called 'end of pipe' treatment). These techniques are known as 'Sustainable Drainage Systems' (SuDS).

Where run-off is draining from relatively low risk areas such as car-parks and non-operational areas, a source control approach, such as permeable surfaces or infiltration trenches, may offer a suitable means of treatment, removing the need for a separator.

Oil separators are installed on surface water drainage systems to protect receiving waters from pollution by oil, which may be present due to minor leaks from vehicles and plant, from accidental spillage.

Effluent from industrial processes and vehicle washing should normally be discharged to the foul sewer (subject to the approval of the sewerage undertaker) for further treatment at a municipal treatment works.

SEPARATOR STANDARDS AND TYPES

A British (and European) standard (EN 858-1 and 858-2) for the design and use of prefabricated oil separators has been adopted. New prefabricated separators should comply with the standard.

SEPARATOR CLASSES

The standard refers to two 'classes' of separator, based on performance under standard test conditions.

CLASS I

Designed to achieve a concentration of less than 5mg/l of oil under standard test conditions, should be used when the separator is required to remove very small oil droplets.

CLASS II

Designed to achieve a concentration of less than 100mg/l oil under standard test conditions and are suitable for dealing with discharges where a lower quality requirement applies (for example where the effluent passes to foul sewer).

Both classes can be produced as full retention separators. The oil concentration limits of 5 mg/l and 100 mg/l are only applicable under standard test conditions. It should not be expected that separators will comply with these limits when operating under field conditions.

FULL RETENTION SEPARATORS

Full retention separators treat the full flow that can be delivered by the drainage system, which is normally equivalent to the flow generated by a rainfall intensity of 65mm/hr.

On large sites, some short term flooding may be an acceptable means of limiting the flow rate and hence the size of full retention systems.

Get in touch for a **FREE** professional site visit and a representative will contact you within 5 working days to arrange a visit.

helpingyou@klarvester.com
to make the right decision
or call **028 302 66799**

BYPASS SEPARATORS

Bypass separators fully treat all flows generated by rainfall rates of up to 6.5mm/hr. This covers over 99% of all rainfall events. Flows above this rate are allowed to bypass the separator. These separators are used when it is considered an acceptable risk not to provide full treatment for high flows, for example where the risk of a large spillage and heavy rainfall occurring at the same time is small.

FORECOURT SEPARATORS


Forecourt separators are full retention separators specified to retain on site the maximum spillage likely to occur on a petrol filling station. They are required for both safety and environmental reasons and will treat spillages occurring during vehicle refuelling and road tanker delivery. The size of the separator is increased in order to retain the possible loss of the contents of one compartment of a road tanker, which may be up to 7,600 litres.

SELECTING THE RIGHT SEPARATOR

The chart on the following page gives guidance to aid selection of the appropriate type of fuel/oil separator for use in surface water drainage systems which discharge into rivers and soakaways.

For further detailed information, please consult the Environment Agency Pollution Prevention Guideline 03 (PPG 3) 'Use and design of oil separators in surface water drainage systems' available from their website.

Kingspan Klarvester has a specialist team who provide technical assistance in selecting the appropriate separator for your application.



1 You must seek prior permission from your local sewer provider before you decide which separator to install and before you make any discharge.

2 You must seek prior permission from the relevant environmental body before you decide which separator to install.

3 In this case, if it is considered that there is a low risk of pollution a source control SuDS scheme may be appropriate.

4 In certain circumstances, the sewer provider may require a Class 1 separator for discharges to sewer to prevent explosive atmospheres from being generated.

5 Drainage from higher risk areas such as vehicle maintenance yards and goods vehicle parking areas should be connected to foul sewer in preference to surface water.

6 In certain circumstances, a separator may be one of the devices used in the SuDS scheme. Ask us for advice.

Bypass NSB RANGE

APPLICATION

Bypass separators are used when it is considered an acceptable risk not to provide full treatment, for very high flows, and are used, for example, where the risk of a large spillage and heavy rainfall occurring at the same time is small, e.g.

- Surface car parks.
- Roadways.
- Lightly contaminated commercial areas.

PERFORMANCE

Klargester were one of the first UK manufacturers to have separators tested to EN 858-1. Klargester have now added the NSB bypass range to their portfolio of certified and tested models. The NSB number denotes the maximum flow at which the separator treats liquids.

The British Standards Institute (BSI) tested the required range of Kingspan Klargester Bypass separators and certified their performance in relation to their flow and process performance assessing the effluent qualities to the requirements of EN 858-1. Klargester bypass separator designs follow the parameters determined during the testing of the required range of bypass separators.

Each bypass separator design includes the necessary volume requirements for:

- Oil separation capacity. ■ Oil storage volume.
- Silt storage capacity. ■ Coalescer.

The unit is designed to treat 10% of peak flow. The calculated drainage areas served by each separator are indicated according to the formula given by PPG3 NSB = 0.0018A(m²). Flows generated by higher rainfall rates will pass through part of the separator and bypass the main separation chamber.

Class I separators are designed to achieve a concentration of 5mg/litre of oil under standard test conditions.


SIZES AND SPECIFICATIONS

UNIT NOMINAL SIZE	FLOW (l/s)	PEAK FLOW RATE (l/s)	DRAINAGE AREA (m ²)	STORAGE CAPACITY (litres) SILT	UNIT LENGTH (mm)	UNIT DIA. (mm)	ACCESS SHAFT DIA. (mm)	BASE TO INLET INVERT (mm)	BASE TO OUTLET INVERT	STANDARD FALL ACROSS (mm)	MIN. INLET INVERT (mm)	STANDARD PIPework DIA.
NSBP003	3	30	1670	300	45	1700	1350	600	1420	1320	100	500
NSBP004	4.5	45	2500	450	60	1700	1350	600	1420	1320	100	500
NSBP006	6	60	3335	600	90	1700	1350	600	1420	1320	100	500
NSBE010	10	100	5560	1000	150	2069	1220	750	1450	1350	100	700
NSBE015	15	150	8335	1500	225	2947	1220	750	1450	1350	100	700
NSBE020	20	200	11111	2000	300	3893	1220	750	1450	1350	100	700
NSBE025	25	250	13890	2500	375	3575	1420	750	1680	1580	100	700
NSBE030	30	300	16670	3000	450	4265	1420	750	1680	1580	100	700
NSBE040	40	400	22222	4000	600	3230	1920	600	2185	2035	150	1000
NSBE050	50	500	27778	5000	750	3960	1920	600	2185	2035	150	1000
NSBE075	75	750	41667	7500	1125	5841	1920	600	2235	2035	200	950
NSBE100	100	1000	55556	10000	1500	7661	1920	600	2235	2035	200	950
NSBE125	125	1250	69444	12500	1875	9548	1920	600	2235	2035	200	950

 Rotomoulded chamber construction

 GRP chamber construction

* Some units have more than one access shaft – diameter of largest shown.



Advanced rotomoulded construction on selected models

- Compact and robust
- Require less backfill
- Tough, lightweight and easy to handle

FEATURES

- Light and easy to install.
- Inclusive of silt storage volume.
- Fitted inlet/outlet connectors.
- Vent points within necks.
- Oil alarm system available (required by EN 858-1 and PPG3).
- Extension access shafts for deep inverts.
- Maintenance from ground level.
- GRP or rotomoulded construction (subject to model).

To specify a nominal size bypass separator, the following information is needed:-

- The calculated flow rate for the drainage area served. Our designs are based on the assumption that any interconnecting pipework fitted elsewhere on site does not impede flow into or out of the separator and that the flow is not pumped.
- The drain invert inlet depth.
- Pipework type, size and orientation.

Full Retention NSF RANGE

APPLICATION

Full retention separators are used in high risk spillage areas such as:

- Fuel distribution depots.
- Vehicle workshops.
- Scrap Yards

PERFORMANCE

Kingspan Klärgäste were the first UK manufacturer to have the required range (3-30 l/sec) certified to EN 858-1 in the UK. The NSF number denotes the flow at which the separator operates.

The British Standards Institute (BSI) have witnessed the performance tests of the required range of separators and have certified their performance, in relation to their flow and process performance to ensure that they met the effluent quality requirements of EN 858-1. Larger separator designs have been determined using the formulas extrapolated from the test range.


Each full retention separator design includes the necessary volume requirements for:

■ Oil separation capacity.	■ Oil storage volume.
■ Silt storage capacity.	■ Coalescer (Class I units only).
■ Automatic closure device.	

Klärgäste full retention separators treat the whole of the specified flow.

FEATURES

- Light and easy to install.
- Class I and Class II designs.
- 3-30 l/sec range independently tested and performance sampled, certified by the BSI.
- Inclusive of silt storage volume.
- Fitted inlet/outlet connectors.



- Oil alarm system available.
- Vent points within necks.
- Extension access shafts for deep inverts.
- Maintenance from ground level.
- GRP or rotomoulded construction (subject to model).

To specify a nominal size full retention separator, the following information is needed:-

- The calculated flow rate for the drainage area served. Our designs are based on the assumption that any interconnecting pipework fitted elsewhere on site does not impede flow into or out of the separator and that the influent is not pumped.
- The required discharge standard. This will decide whether a Class I or Class II unit is required.
- The drain invert inlet depth.
- Pipework type, size and orientation.

SIZES AND SPECIFICATIONS

UNIT NOMINAL SIZE	FLOW (l/s)	DRAINAGE AREA (m ²) PPG-3 (0.018)	STORAGE CAPACITY		UNIT LENGTH (mm)	UNIT DIA. (mm)	BASE TO INLET INVERT (mm)	BASE TO OUTLET INVERT	MIN. INLET INLET (mm)	STANDARD PIPEWORK DIA. (mm)
			SILT	OIL						
NSFP003	3	170	300	30	1700	1350	1420	1345	500	160
NSFP006	6	335	600	60	1700	1350	1420	1345	500	160
NSFA010	10	555	1000	100	2610	1225	1050	1000	500	200
NSFA015	15	835	1500	150	3910	1225	1050	1000	500	200
NSFA020	20	1115	2000	200	3200	2010	1810	1760	1000	315
NSFA030	30	1670	3000	300	3915	2010	1810	1760	1000	315
NSFA040	40	2225	4000	400	4640	2010	1810	1760	1000	315
NSFA050	50	2780	5000	500	5425	2010	1810	1760	1000	315
NSFA065	65	3610	6500	650	6850	2010	1810	1760	1000	315
NSFA080	80	4445	8000	800	5744	2820	2500	2450	1000	300
NSFA100	100	5560	10000	1000	6200	2820	2500	2450	1000	400
NSFA125	125	6945	12500	1250	7365	2820	2500	2450	1000	450
NSFA150	150	8335	15000	1500	8675	2820	2550	2450	1000	525
NSFA175	175	9725	17500	1750	9975	2820	2550	2450	1000	525
NSFA200	200	11110	20000	2000	11280	2820	2550	2450	1000	600

 Rotomoulded chamber construction  GRP chamber construction

Washdown & Silt

APPLICATION

This unit can be used in areas such as car wash and other cleaning facilities that discharge directly into a foul drain, which feeds to a municipal treatment facility.

If emulsifiers are present the discharge must not be allowed to enter an NS Class I or Class II unit.


- Car wash.
- Tool hire depots.
- Truck cleansing.
- Construction compounds cleansing points.

PERFORMANCE

Such wash down facilities must not be allowed to discharge directly into surface water but must be directed to a foul connection leading to a municipal treatment works as they utilise emulsifiers, soaps and detergents, which can dissolve and disperse the oils.

SIZES AND SPECIFICATIONS

REF.	TOTAL CAPACITY (litres)	MAX. REC. SILT	MAX. FLOW RATE (l/s)	LENGTH (mm)	DIAMETER (mm)	ACCESS SHAFT DIA. (mm)	BASE TO INLET INVERT (mm)	BASE TO OUTLET INVERT (mm)	STANDARD FALL ACROSS UNIT (mm)	MIN. INLET INVERT (mm)	STANDARD PIPEWORK DIA. (mm)	APPROX EMPTY (kg)
W1/010	1000	500	3	1123	1225	460	1150	1100	50	500	160	60
W1/020	2000	1000	5	2074	1225	460	1150	1100	50	500	160	120
W1/030	3000	1500	8	2952	1225	460	1150	1100	50	500	160	150
W1/040	4000	2000	11	3898	1225	460	1150	1100	50	500	160	180
W1/060	6000	3000	16	4530	1440	600	1360	1310	50	500	160	320
W1/080	8000	4000	22	3200	2020	600	2005	1955	50	500	160	585
W1/100	10000	5000	27	3915	2020	600	2005	1955	50	500	160	680
W1/120	12000	6000	33	4640	2020	600	2005	1955	50	500	160	770
W1/150	15000	7500	41	5435	2075	600	1940	1890	50	500	160	965
W1/190	19000	9500	52	6865	2075	600	1940	1890	50	500	160	1200



FEATURES

- Light and easy to install.
- Inclusive of silt storage volume.
- Fitted inlet/outlet connectors.
- Vent points within necks.
- Extension access shafts for deep inverts.
- Maintenance from ground level.


Car Wash Silt Trap

APPLICATION

Car Wash silt trap is designed for use before a separator in car wash applications to ensure effective silt removal.

FEATURES

- FACTA Class B covers.
- Light and easy to install.
- Maintenance from ground level.



Forecourt

APPLICATION

The forecourt separator is designed for installation in petrol filling station forecourts and similar applications. The function of the separator is to intercept hydrocarbon pollutants such as petroleum and oil and prevent their entry to the drainage system, thus protecting the environment against hydrocarbon contaminated surface water run-off and gross spillage.

PERFORMANCE

Operation ensures that the flow cannot exit the unit without first passing through the coalescer assembly.

In normal operation, the forecourt separator has sufficient capacity to provide storage for separated pollutants within the main chamber, but is also able to contain up to 7,600 litres of pollutant arising from the spillage of a fuel delivery tanker compartment on the petrol forecourt. The separator has been designed to ensure that oil cannot exit the separator in the event of a major spillage, subsequently the separator should be emptied immediately.

FEATURES

- Light and easy to install.
- Inclusive of silt storage volume.
- Fitted inlet/outlet connectors.
- Vent points within necks.
- Extension access shafts for deep inverts.
- Maintenance from ground level.

SIZES AND SPECIFICATIONS

ENVIROCEPTOR CLASS	TOTAL CAP. (litres)	DRAINAGE AREA (m ²)	MAX. FLOW RATE (l/s)	LENGTH (mm)	DIAMETER (mm)	ACCESS SHAFT DIA. (mm)	BASE TO INLET INVERT (mm)	BASE TO OUTLET INVERT (mm)	STD. FALL ACROSS UNIT (mm)	MIN. INLET INVERT (mm)	STD. PIPEWORK (mm)	EMPTY WEIGHT (kg)
I	10000	555	10	3963	1920	600	2110	2060	50	400	160	500
II	10000	555	10	3963	1920	600	2110	2060	50	400	160	500
I	10000	1110	20	3963	1920	600	2110	2060	50	400	200	500
II	10000	1110	20	3963	1920	600	2110	2060	50	400	200	500



- Class I and Class II design.
- Oil storage volume.
- Coalescer (Class I unit only).
- Automatic closure device.
- Oil alarm system available.

INSTALLATION

The unit should be installed on a suitable concrete base slab and surrounded with concrete or pea gravel backfill. See sales drawing for installation.

If the separator is to be installed within a trafficked area, then a suitable cover slab must be designed to ensure that loads are not transmitted to the unit.

The separator should be installed and vented in accordance with Health and Safety Guidance Note HS(G)41 for filling stations, subject to Local Authority requirements.

Alarm Systems

British European Standard EN 858-1 and Environment Agency Pollution Prevention Guideline PPG3 requires that all separators are to be fitted with an oil level alarm system and that it should be installed and calibrated by a suitably qualified technician so that it will respond to an alarm condition when the separator requires emptying.

- Easily fitted to existing tanks.
- Excellent operational range.
- Visual and audible alarm.
- Additional telemetry option.



PROFESSIONAL INSTALLERS

Kingspan Klärgesteter Accredited Installers

Experience shows that correct installation is a prerequisite for the long-lasting and successful operation of any wastewater treatment product. This is why using an installer with the experience and expertise to install your product is highly recommended.



Services include :

- Site survey to establish ground conditions and soil types
- Advice on system design and product selection
- Assistance on gaining environmental consents and building approvals
- Tank and drainage system installation
- Connection to discharge point and electrical networks
- Waste emptying and disposal

Discover more about the Accredited Installers and locate your local expert online.

www.kingspanenviro.com/klargester



COMMERCIAL WASTEWATER SOLUTIONS

■ BIODISC® & ENVIROSAFE

HIGH PERFORMANCE SEWAGE TREATMENT SYSTEMS

■ PACKAGE PUMP STATIONS

■ PUMPSTOR24 PUMPING SYSTEMS

■ OIL/WATER SEPARATORS

■ BELOW GROUND STORAGE TANKS

■ GREASE & SILT TRAPS

RAINWATER SOLUTIONS

■ BELOW GROUND RAINWATER HARVESTING SYSTEMS

■ ABOVE GROUND RAINWATER HARVESTING SYSTEMS

Klärgesteter

UK: College Road North, Aston Clinton, Aylesbury, Buckinghamshire HP22 5EW

Tel: +44 (0) 1296 633000 Fax: +44 (0) 1296 633001 Scottish Office: Tel: +44 (0) 1355 248484
email: klargester@kingspan.com

Ireland: Unit 1a, Derryboy Road, Carnbane Business Park, Newry, Co. Down BT35 6QH

NI Tel : +44 (0) 28 302 66799 Fax: +44 (0) 28 302 60046 ROI Tel: 048 302 66799 Fax: 048 302 60046
email: klargesterinfo@kingspan.com

Visit our website www.kingspanenviro.com/klargester



In keeping with Company policy of continuing research and development and in order to offer our clients the most advanced products, Kingspan Environmental reserves the right to alter specifications and drawings without prior notice.

Issue No. 21: September 2015



CARE & MAINTENANCE

Kingspan Environmental Services

Who better to look after your treatment plant than the people who designed and built it?

Kingspan Environmental have a dedicated service division providing maintenance for wastewater products.

Factory trained engineers are available for site visits as part of a planned maintenance contract or on a one-off call out basis.



To find out more about protecting your investment and ensuring peace of mind, call us on:

0844 846 0500

or visit us online:
www.kingspanenvservice.com




Alarm Probe Tube
(see note 7)



Unit Ref No	Nominal Flow	Dim L (mm)	Approx Empty Weight (kgs)	Fall across unit
NSFP003	3 L/s	1700	180	75
NSFP006	6 L/s	1700	180	75

Concrete cover slab cast by client
(to suit wet site conditions)

Neck can be trimmed
down to required invert



Notes:-

1. Inlet/Outlet pipes are plain pipe Ø 160 mm PVCu. The standard EN 858 states minimum connection sizes, units ordered with different sized connections are not fully compliant with the standard.

2. Extension necks for deeper inverts can be provided. These can be cut in 200 mm sections. Max 2.0m Invert recommended. Please ask our sales department for further details.

3. All units require appropriate cover and frame to suit applied loadings.

4. This drawing should be used for dimensional information only. It is essential that this drawing is read in conjunction with the installation guidelines supplied with the unit. (Copies are available from our sales dept.).

5. This drawing is also available on our website
www.kingspanenv.com.

6. A Ø 76 mm tube (internal) is supplied to house an oil alarm probe.

7. Wet site conditions - Concrete Backfill
Dry site conditions - Pea Shingle Backfill

Please refer to installation manual for details of correct backfilling.

Please check with Kingspan Environmental that this drawing is the latest issue

Issue	Date	Drawn by	Approved by	Description
04	15/12/10	S.Gill		CC934
03	24/02/10	S. Gill		CC794
02	23/09/09	S.Gill		Drawing Description Changed/Table Corrected
01	19/03/09	S.Gill		Initial Release

Material : n/a Tolerance : n/a
Finish : n/a Thickness : n/a
Weight : Kgs n/a Surface Area : n/a

Kingspan Environmental reserve the
right to alter the details of this drawing without prior notice.
This drawing is copyright and may not be reproduced or used without
the written permission of Kingspan Environmental.

Drawing : NSFP 003-006 Sales Drawing

Page 1 of 1

Drg No - DSO992

All dimensions in mm

Scale: Not to scale


Kingspan
Environmental

Technical Submittal Form



Please use this form as a 'front sheet' for all technical submittals. Ensure you include as much information as possible to receive a status. Where you provide an attachment, please reference the technical submittal ref. in the 'Subject/Title' field. and refer to the attachment in the 'Description' field.

Form Title Ref.:

TOU-0472-UP2-BG-TS-X-0040

Subject / Title:

Forecourt Separator

Description (example: product name; location; specification details; supplier; etc.):

Klargester 10000litre Class II Forecourt Separator, EC2 South West, R12 411 with oil probe and alarm. As supplied to Phase 1.

Is the proposal specification compliant?

Yes

Is the proposal an alternative to specification?

No

Details of reason for deviation from specification / alternative to specification:



**MAINS KLARGESTER
SEPARATOR ALARM
INSTALLATION &
OPERATIONS MANUAL**

Mains Powered Klärgester Separator Alarm

Installation, Operation and Maintenance

Contents

IMPORTANT	3
General Description	4
General Operation.....	4
Changing Factory Settings	4
Alarm Type.....	4
Check Interval	5
Testing the Probe Sensors.....	5
Installation	5
Control Unit	5
Probes (High Oil & High Liquid Level Probes).....	5
Silt Probe	5
Cable Distribution Box	6
Connection to Control Unit.....	6
Using a Junction Box	6
Maintenance and Repair	6
Technical Information	7
Electrical	7
Apparatus Supply and I/O Parameters.....	7
Probe Cables.....	7
Mechanical	7
Probe Enable Jumper Links.....	8
Probe Cable Terminals	9
Flashing Beacon Wiring.....	9
Accessories.....	10

14300 Klärgester Separator Alarm

Installation, Operation & Maintenance

Name and Address of Manufacturer	Darcy Products Limited Brook House Larkfield Trading Estate New Hythe Lane, Larkfield Kent ME20 6GN
European Directive	94/9/EC
Equipment Name and Type	Separator Monitor Type 14300
Certificate Number	Baseefa 08ATEX0110/2 IECEx BAS 11.0095
Specific Marking of Explosion Protection	[Ex ia] IIC (-20°C ≤ Ta ≤ +50°C)
ATEX Directive Marking	Ex II (1) G
Notified Body	Baseefa 1180 Buxton UK
CE Mark with Notified Body Number	CE ₁₁₈₀
Harmonised Standards Used	EN 60079-0:2009 EN 60079-11:2012
Serial Number and Year of Manufacture	Displayed underneath the control unit
On behalf of the above named company, I declare that, on the date the equipment accompanied by this declaration is placed on the market, the equipment conforms with all technical and regulatory requirements of the above listed directives.	
 P.G. Bowden - Director	

IMPORTANT

Note: In all cases good, standard electrical practice should be followed, and the installation must conform to the appropriate local code of practice – e.g. BS EN 60079-25 in the UK. In essence, the installation must be such that the intrinsic safety is not compromised by: - exposure to risk of mechanical damage, unauthorised modification or interference, exposure to moisture, dust and foreign bodies, excessive heat, invasion of intrinsically safe circuit by other electrical equipment or circuitry. (See Note in installation section)

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

General Description

The standard system is supplied complete with an intrinsically safe control unit together with a high oil probe. The control unit is capable of monitoring up to 3 probe units, displaying their current status via a 2 x 16 display. The output relay enables this status to be signalled to a remote location or activate a beacon if required.

General Operation

The Control Unit monitors the condition of the connected probe units by checking their condition every 30 minutes¹, their current status is displayed on the display located on the front of the unit. If an alarm condition is detected, a warning message is displayed followed by notification of the alarm condition detected, e.g. ***HAZARD ALERT* High Oil Alarm**, the output relay becomes de-energised and the internal buzzer is audible.

The unit then gives the option, via the display, to accept/acknowledge the alarm. On doing so, the output relay energises, the buzzer is muted and the display instructs the user to take the appropriate action, e.g. empty the separator. After the separator has been emptied and refilled with water, the control unit re-scans the probe sensors attached and presuming no alarm condition is detected, **'All Correct'** will be displayed. If the push button is pressed before the separator has been emptied, or it has been emptied but not refilled with water, then the control simply scans the probe sensor(s) and reverts to the alarm condition. Please note the output relay is *de-energised* on detection of any alarm condition or mains failure.

Changing Factory Settings

Alarm Type

The factory setting is STD (standard), this is where the output relay de-energises upon fault detection and energises upon acceptance of the fault.

Alarm Type EXT (Extended) allows the relay to remain de-energised until all alarm conditions become normal.

To enter the "Set Up" mode, firstly remove power from the unit. Whilst holding down the Push Switch, power up the unit keeping the Push Switch depressed, after about 10 seconds the screen will display "Set Up", at this point release the Push Switch.

The display will now show Alarm Type: with a flashing cursor over STD, to change this function to EXT, press the Push Switch once.

¹ The unit is factory set to 30 minutes, but in extreme conditions, this can be manually changed from 2 to 60 minutes at one minute intervals. (see Changing Factory Settings)

Check Interval

Whilst still in the Set Up mode, power down and then power up the unit, the flashing cursor will now be next to Check Intvl: - by pressing the Push Switch, the time can be altered in increments of 1 minute between 2 and 60.

To exit the Set Up mode at any time, hold the Push Switch whilst powering down and then power up again before releasing the Switch, this will return to the main screen sequence.

Testing the Probe Sensors

The probe interrogation function can be activated at any time by simply pressing the push switch.

Installation

This product has been designed and certified as being intrinsically safe. It is of paramount importance, that the unit should not be modified in any way and the installation be carried out by an approved installer, in accordance with the Environment Agency guidelines (PPG3). Any deviation from this could invalidate the certification warranty and render the unit unsafe for its intended use.

Control Unit

Refer to Table 4 on page 7 for required cable specifications.

The control unit must be positioned in a non-hazardous area. For all wiring details, refer to Figure 1, Table 5 and Table 6 on page 9.

Probes (High Oil & High Liquid Level Probes)

The high oil probe is to be installed in the separator tank such that the float housing is below the static liquid level. If a high liquid probe is required, this needs to be installed such that the float switch housing is located above the static liquid level. Both probe cables can be secured inside the neck of the separator using a probe cord guide.

Please note the distance above or below the static liquid level will be determined by the type, style and/or size of separator, this information can be obtained from the separator manufacturer. However, as a general *rule of thumb*, the high liquid level probe should be placed 300mm above the static liquid level and the high oil probe 150mm below.

Due to the varying neck lengths (turrets) that occur within each separator, each normal probe unit is fitted with 5 metres of cable.

Silt Probe

The probe is suspended in the separator to a pre determined depth and the cable can be secured to the neck of the separator using a probe cord guide.

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Cable Distribution Box

It is advisable to connect the probe cables to a cable distribution box which should be fixed near to the top of the separator neck. The probe cable can then be terminated with a waterproof plug (provided with the distribution box). The plug is then connected to the bulkhead socket (provided with the distribution box). A cable must then be laid to connect the distribution box and the control unit. The type of connection cable required will be dependent on the environment it is used in, the route taken and maximum allowable cable capacitance and inductance (see cable parameters in Table 4 on page 7).

After making the connections in the distribution box, it is advisable to spray the terminals with a conformal coating lacquer to prevent moisture ingress before finally sealing them with waterproof putty.

Connection to Control Unit

The Probe cable should be fed through the appropriate gland in the bottom right hand side of the control unit and connected to the terminals as instructed. The mains cable, and if used, any beacon or sounder cable, must be fed through the appropriate gland on the bottom left hand side of the control unit and connected to the terminals as instructed.

IMPORTANT NOTE: Under NO circumstances must the control unit casing be drilled to allow cable entry in any area(s) other than those already provided, as this would infringe the certification and therefore safety of the product.

Using a Junction Box

An intrinsically safe junction box should be used where incoming cable sizes have to be reduced to gain entry through the cable glands in the base of the control unit.

IMPORTANT NOTE: Under NO circumstances must mains and probe cable joints be made within the same junction box other than a junction box that is approved Intrinsically safe for such purpose, as this would infringe the certification and therefore safety of the installed system.

Maintenance and Repair

Due to the harsh environments which the probes can be subjected to, it is advised that they are inspected and cleaned with a damp cloth at regular intervals. The control unit does not contain user serviceable parts.

Technical Information

Electrical

Supply Voltage	230V $\pm 10\%$ 50Hz	
Input Current	Normal condition	41mA
	Alarm condition	40mA
Fusing	Primary (FS2)	T 315mA H 250V
	Secondary (FS3)	50mA (Baseefa approved)
Max probe cable length	200m (less if values in Table 4 would be exceeded)	
Relay Output	Volt-free SPCO contact	
	3A	
Panel rating	IP65	
Panel dimensions	180mm x 180mm x 60mm	

Table 1 – Electrical Specifications

Apparatus Supply and I/O Parameters

U_m	253Vrms
-------	---------

Table 2 – Mains Supply and Relay Contact Terminals (TB2 & TB3)

U_o	12.6V
I_o	87mA
P_o	273mW
C_i	0
L_i	0

Table 3 – Hazardous Area Terminals (TB1)

Group	Capacitance (μF)	Inductance (mH)	OR	L/R Ratio ($\mu\text{H}/\Omega$)
IIC	1.15	4.6	74	
IIB	7.4	18.7	298	
IIA	27	37.5	596	

Table 4 – TB1 Load Parameters

Probe Cables

The total capacitance and inductance of the cable used between the control unit and the probe must not exceed that shown in [Table 4](#).

Mechanical

Protection and/or screening of the cable should also be taken into account. The maximum length of cable between probe and control unit must not exceed 200 metres or less if the values in [Table 4](#) would be exceeded.

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Probe Enable Jumper Links




Figure 1 - Probe enable jumper links

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

To operate a probe, REMOVE appropriate jumper link

Probe Type	Remove Link
High Oil	OIL
High Liquid	LQD
Silt	SLT

Table 5 – Probe enable jumper links

Probe Cable Terminals

Probe Type	A	B	C	D	E	F	G	H
High Oil	BROWN	BLUE						
High Liquid			-	RED	BLUE			
Liquid (Optical)			BROWN	GREEN/YELLOW	BLUE			
Silt						BROWN	GREEN/YELLOW	BLUE

Table 6 - Probes cable wiring connection details

Flashing Beacon Wiring

The relay output terminals, TB2, may be used to operate a 230V flashing beacon when an alarm occurs. The beacon should be wired according to Table 7 and Table 8. Any commoning of live and neutral connections must be done externally to the unit's enclosure.

TB2 Terminal	Connect To
NO	No Connection
COM	TB3 Mains live
NC	Beacon Live Terminal

Table 7 – wiring from relay output to beacon

TB3 Mains Terminal	Connect To
L out	TB2 COM Terminal
N out	Beacon Neutral Terminal
E	Mains earth

Table 8 – wiring to beacon from relay output

Mains Powered Klargestor Separator Alarm

Installation, Operation and Maintenance

Accessories

	Part No.
High Oil Probe -----	14201
High Level Probe -----	14210
Silt Probe -----	14220
230 VAC Flashing Amber Beacon (Includes mounting bracket and glands) -----	14012
230 VAC Flashing Amber Beacon & Siren (Includes mounting bracket and glands) -----	14100
Probe Cord Guide -----	14103
Signal Distribution Box -----	14039
Intrinsically Safe Junction Box (Power & Probe) -----	14006

Forecourt

APPLICATION

The forecourt separator is designed for installation in petrol filling station forecourts and similar applications. The function of the separator is to intercept hydrocarbon pollutants such as petroleum and oil and prevent their entry to the drainage system, thus protecting the environment against hydrocarbon contaminated surface water run-off and gross spillage.

PERFORMANCE

Operation ensures that the flow cannot exit the unit without first passing through the coalescer assembly.

In normal operation, the forecourt separator has sufficient capacity to provide storage for separated pollutants within the main chamber, but is also able to contain up to 7,600 litres of pollutant arising from the spillage of a fuel delivery tanker compartment on the petrol forecourt. The separator has been designed to ensure that oil cannot exit the separator in the event of a major spillage, subsequently the separator should be emptied immediately.

FEATURES

- Light and easy to install.
- Inclusive of silt storage volume.
- Fitted inlet/outlet connectors.
- Vent points within necks.
- Extension access shafts for deep inverts.
- Maintenance from ground level.

SIZES AND SPECIFICATIONS

ENVIROCEPTOR CLASS	TOTAL CAP. (litres)	DRAINAGE AREA (m ²)	MAX. FLOW RATE (l/s)	LENGTH (mm)	DIAMETER (mm)	ACCESS SHAFT DIA. (mm)	BASE TO INLET INVERT (mm)	BASE TO OUTLET INVERT (mm)	STD. FALL ACROSS UNIT (mm)	MIN. INLET INVERT (mm)	STD. PIPEWORK (mm)	EMPTY WEIGHT (kg)
I	10000	555	10	3963	1920	600	2110	2060	50	400	160	500
II	10000	555	10	3963	1920	600	2110	2060	50	400	160	500
I	10000	1110	20	3963	1920	600	2110	2060	50	400	200	500
II	10000	1110	20	3963	1920	600	2110	2060	50	400	200	500



- Class I and Class II design.
- Oil storage volume.
- Coalescer (Class I unit only).
- Automatic closure device.
- Oil alarm system available.

INSTALLATION

The unit should be installed on a suitable concrete base slab and surrounded with concrete or pea gravel backfill. See sales drawing for installation.

If the separator is to be installed within a trafficked area, then a suitable cover slab must be designed to ensure that loads are not transmitted to the unit.

The separator should be installed and vented in accordance with Health and Safety Guidance Note HS(G)41 for filling stations, subject to Local Authority requirements.

Alarm Systems


British European Standard EN 858-1 and Environment Agency Pollution Prevention Guideline PPG3 requires that all separators are to be fitted with an oil level alarm system and that it should be installed and calibrated by a suitably qualified technician so that it will respond to an alarm condition when the separator requires emptying.

- Easily fitted to existing tanks.
- Excellent operational range.
- Visual and audible alarm.
- Additional telemetry option.




CONCRETE BACKFILL



APPROX. WEIGHT	
EMPTY	FULL
500 Kg	10,500Kg



NOTE:- THE DESIGN OF THIS UNIT IS BASED ON AN NS10 FULL RETENTION UNIT



EXTENSION COMPONENTS
SUPPLIED IF REQUIRED
FOR ON SITE FITTING
SEE ARTICLE STRUCTURE



Please Check with Environmental Treatment Systems Limited For The Latest Issue Of This Drawing

Issue	Date	Drawn by	Approved by	Description
03	19.02.18	T.Kelly		CC1405 - Coalescer Extension Chains were Pipes
02	29.02.16	T.Kelly		CC1297 - Full Weight Corrected (Both Sheets)

Material : Spray Laminate	Tolerance (unless stated) : $\pm 0.5\text{mm}$
Finish : n/a	Thickness : 3mm
Weight : 11.35 Kg Min	Surface Area : EXT 2.23 m ²
Modelled By :	

Drawing : DS1248

Page 1 of 2

Enviroceptor Forecourt Separator (NS10)

All Dimensions In mm

Scale: Do Not Scale




Kingspan Environmental reserve the right to alter the details of this drawing without prior notice. This drawing is copyright and may not be reproduced or used without the written permission of Kingspan Environmental


PEASHINGLE BACKFILL

NOTE:- THE DESIGN OF THIS UNIT IS BASED
ON AN NS10 FULL RETENTION UNIT

APPROX. WEIGHT	
EMPTY	FULL
500 Kg	10,500Kg



EXTENSION COMPONENTS
SUPPLIED IF REQUIRED
FOR ON SITE FITTING
SEE ARTICLE STRUCTURE



SECTION A-A

FEET MUST NOT BEAR
DIRECTLY ONTO
CONCRETE BASE SLAB


COALESCER ASSEMBLY
WITH SHUT OFF DEVICE
(REMOVABLE FOR
MAINTENANCE)

300mm MINIMUM
PEA SHINGLE BED

CONCRETE BASE SLAB
CAST BY CLIENT TO SUIT
SITE CONDITIONS

CONCRETE COVER SLAB
CAST BY CLIENT TO SUIT
SITE CONDITIONS

PEA SHINGLE BACKFILL



Material : Spray Laminate	Tolerance (unless stated) : $\pm 0.5\text{mm}$
Finish : n/a	Thickness : 3mm
Weight : 11.35 Kg Min	Surface Area : EXT 2.23 m ²
Modelled By :	

Drawing : DS1248

Page 2 of 2

Enviroceptor Forecourt Separator (NS10)

All Dimensions In mm

Scale: Do Not Scale

Third Angle Projection