



SRK35ZSP-S

Inverter Wall Mount



Compact and Light weight

The SRK-ZSP-S series offers great installation flexibility.



Wireless
remote control



SRK25ZSP-S
SRC35ZSP-S



SRC45ZSP-S

FUNCTIONS

Energy saving



Air flow



Clean operation & Filter



Comfort & Convenience



Others



SPECIFICATIONS


Indoor unit				SRK25ZSP-S	SRK35ZSP-S	SRK45ZSP-S
Outdoor unit				SRC25ZSP-S	SRC35ZSP-S	SRC45ZSP-S
Power source				1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min~Max)			kW	2.5(0.9~2.8)	3.2(0.9~3.5)	4.5(0.9~4.8)
Nominal heating capacity (Min~Max)			kW	2.8(0.8~3.9)	3.6(0.9~4.3)	5.0(0.8~5.8)
Power consumption		Cooling/Heating	kW	0.78 / 0.755	0.995 / 0.995	1.495 / 1.385
EER/COP		Cooling/Heating		3.21/3.71	3.22 / 3.62	3.01 / 3.61
Max. running current			A	9	9	14
Sound power level	Indoor	Cooling/Heating	dB(A)	58 / 57	59 / 58	58 / 62
	Outdoor	Cooling/Heating		58 / 59	60 / 60	63 / 64
Sound pressure level	Indoor	Cooling (Hi/Me/Lo)		45 / 34 / 23	45 / 36 / 23	44 / 39 / 24
		Heating (Hi/Me/Lo)		43 / 34 / 26	44 / 36 / 28	48 / 41 / 30
	Outdoor	Cooling/Heating	47 / 45	47 / 48	51 / 51	
Air flow	Indoor	Cooling (Hi/Me/Lo)	m³/min	10.0 / 7.3 / 4.2	9.5 / 6.8 / 4.2	9.0 / 7.2 / 3.8
		Heating (Hi/Me/Lo)		9.5 / 7.3 / 5.2	9.6 / 7.4 / 5.5	12.0 / 9.2 / 6.2
	Outdoor	Cooling/Heating		26.0 / 19.7	25.4 / 20.5	35.5 / 33.5
Exterior dimensions	Indoor	HeightxWidthxDepth	mm	267 x 783 x 210		
	Outdoor			540 x 645(+57) x 275		595 x 780(+62) x 290
Net weight		Indoor / Outdoor	kg	7.0 / 25	7.0 / 27	7.5 / 40
Refrigerant		Type/GWP		R410A / 2088		
		Charge	kg/TCO₂Eq	0.655 / 1.368	0.81 / 1.691	1.20 / 2.506
Refrigerant piping size		Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")		6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length			m	Max. 15		Max. 25
Vertical height differences		Outdoor is higher/lower	m	Max. 10 / Max. 10		Max. 15 / Max. 15
Outdoor operating temperature range		Cooling	°C	-15~46		
		Heating		-15~24		
Clean filter				—		



SRK35ZSP-S

Inverter Wall Mount

SRK35ZSP-S Indoor Unit



SRC35ZSP-S Outdoor Unit

